



# AUTOMOTIVE/OFFROAD CONTENTS

LED	LIGH'	Г٤
_	_	

Cannon Series	34
LIGHT BARS PX [Prime Xtreme]. XPR-S. XPR LPX [Lo-Pro Prime Xtreme]. Xmitter. Chaser Rear LED System.	47 48 49 50
LED HEADLIGHTS Vortex	57
VEHICLE SPECIFIC KITS  Jeep JK	62 63
HID Lighting	66
Halogen Lighting	68
AUTOMOTIVE ACCESSORIES  Polycarbonate Light Covers	

# INDUSTRIAL CONTENTS

HEAVY DUTY AND MED	YTUD MUIC
86	. PitMaster
88	Ripper
90	olstice Prime
92	
94	rotex [ATEX]
96 Utility Ma	arket Xtreme
98	Dura
INDUSTRIAL S	
102 BT Hea	vy Industrial
104	ght Industrial
	MARITIME
109 Maritin	
110	
111	me Explorer
LUCENT ENGINEERED S	
114	
115	
115	gh Bay Light
116	e LED PMX
118 Cube LED	Shockwave
INDUSTRIAL AGG	FOODIEO
INDUSTRIAL ACC	
120 Constructio	n Area Light
121 Video E	
121	be December
122	be Beacons
123 LED Vehic	cie iD Board
IZ.3 IVIINI INCIDEI	ii Kesponse





# **VISION X HISTORY**

Since 1997, Vision X has been providing the lighting solutions demanded by the market as well as innovating the next step for lighting. With the release of the HID series in late 2005, Vision X was the first to provide an HID internal ballast and starter to the mass market, simplifying installation and reducing external components. Again in 2008, Vision X revolutionized lighting with the LED bar originally produced for NASA's Back to the Moon Mission. Since then, Vision X has continued innovation with the Solo Pod - which gives as many lumens as a headlight from a single 2" x 2" housing - and heavy duty LED lighting for use in mining, industrial, and commercial applications. At Vision X, we are constantly striving to live up to our company motto of "Lighting Evolved."

# **QUALITY** AS A PRIORITY

# **PRODUCT TESTING**

#### CONSUMPTION/INPUT RANGE



All products are put on a digital power meter to test that it is consuming the correct amount of power, checking for any electrical

#### LONG TERM DURABILITY



Products are then switched on and off 20,000 times repeatedly to ensure that they remain functional after all testing.

#### SUBMERSION/AGING



Once products are assembled every product is run through a submersion (water dunk test), then placed onto an aging rack and powered up for 30 minutes.

#### THERMAL IMPACT



Products are placed in a -40°C chamber for 30 minutes, and then placed in a 80°C chamber for an additional 30 minutes. Products are then left on for 72 hours.

#### PHOTOMETRIC



Lights are tested in the Goniophotometer to model the beam pattern and depict the overall light output.

#### TEMPERATURE AND HUMIDITY



Products are placed in a 60°C, 94% humidity chamber and left operational for 72 hours. Afterwards, products are inspected for moisture and damage.



Products are sprayed from close distances with 80~100 BAR water pressure to verify the Ingress Protection rating, ensuring they are

#### /IBRATION



Products are placed on the vibration shock for 4 hours to test that they can withstand the rated vibration standard. Products tested at 60 Grms are performed off-site.

# HIGH LEVEL CERTIFICATIONS

# PHOTO BIOLOGICAL

IEC 62471 Ensures that light output has safe levels of UV exposure for both skin and eyes.

# E-MARK



European Regulatory certification for on highway use.

#### ROHS

RoHS

Ensures no use of restricted hazardous materials in products such as lead, mercury, cadmium, PBB, PBDE, and Phthalate.

#### DOT



US Department of Transportation certified for on road use.

#### UL



UL Certification is recognized around the world as a way to ensure standards.

## ATEX 94 (94/9/EC)



The ATEX 94 certification is given to electronic equipment that is resistant to flame and explosion.



# ADR



Products which are in compliance with the Australian Design Rules (ADR).

# **IP RATING**

IP-69K

Ingress Protection rates protection against outside elements. First number is solids, second is liquids.

#### CE




CE is a mandatory conformity mark for products in the European Economic



EMC and EMI certifies that a product does not interfere with other electrical products. This includes CISPR 25 Certifications


# VISION X LIGHTING ENGINEERED SOLUTION PROCESS

#### **2D BLUEPRINT**



Vision X begins a project by requesting the list of machines that will needed to be retrofitted. Then gathering the technical information for those machines.

#### SIMULATION RENDER




Prior to implementing a lighting solution, Vision X creates a simulation rendering of the intended result to help envision if the final product will meet lighting requirements.

#### **3D MODEL**



A 3D Model is then built to match the customers exact specifications. This model is then carried over into the rendering.


#### SOLUTION



Vision X creates a complete breakdown of what the customer needs to meet their specific requirements for safety.

#### **CONTINUOUS IMPROVEMENT HAZCOM** Certified HAZCOM ISO Program Vision X Meets ISO 9001, ISO 14001 Standards 140 20 Vision X Lighting is Years of Experience Currently Active in 140 with Finding Lighting Countries Worldwide Solutions **Photo ECOPROFIT Biological Award Winning Factory** All Lights are Photo Biologically for Environmental Tested Safe for Human Skin and Eyes Responsibility

# **ENGINEERED PRODUCT DEVELOPMENT**



Vision X works with our customers around the world, our sponsorship partners and the world's leading LED manufacturers continuously to imagine new products for use in many applications. We strive to be the solution provider for any lighting need by continuously improving existing product and imagining new product.

# PATENTED PRODUCT PROTECTION




Vision X ensures the protection of our products by acquiring patents and trademarks worldwide. This gives us the ability to fight "knock-off" products worldwide so that our customers can be assured they are buying Vision X Genuine products.

# **VISION X LIGHTING**

**TECHNOLOGY EXPLAINED** 

LED



Vision X LED Lighting runs at a 6000K temperature for intense, bright white light for maximum visibility and safety. LED Lights do not use a bulb, making them much more durable than other options.

INTENSITY AMP DRAW **LUMENS** PER WATT LIGHT COLOR

HID

HALOGEN



Vision X HID Lighting runs at a 5000k temperature for a super white beam color. HID lights require a bulb, starter and ballast to operate. They have a higher output per wattage than Halogen bulbs.

•••• INTENSITY ●●●● AMP DRAW **LUMENS** PER WATT LIGHT COLOR



Vision X offers a number of different Halogen Lighting options. The Tungsten-Halogen series uses an oversized globe and specially engineered filament to enhance light output. Vision X offers many headlight replacements.

INTENSITY AMP DRAW **LUMENS** PER WATT LIGHT COLOR

# WHAT MAKES VISION X LED DIFFERENT

Not all LEDs are created equal. Each run of LEDs by the manufacturer is binned to classify the quality within that batch. Vision X uses only top-binned LEDs to ensure the highest quality.

#### WEATHERPROOF DEUTSCH CONNECTORS

Each Vision X product features a weatherproof deutsch connector, ensuring the functionality of the light in harsh conditions. Vision X tests each batch of lights to make sure its resistant to weather.

Vision X products are engineered for the highest possible luminus efficacy - the ratio of lumens per watt.

#### **PULSE WIDTH MODULATION**

When enabled, Pulse Width Modulation integrated circuitry flashes the LED faster than the human eye can see for reduced heat, prolonged LED life and dimming capabilities.

#### **ELECTRONIC THERMAL MANAGEMENT**

Integrated Electronic Thermal Management automatically regulates heat levels by engaging ETM to prolong each LEDs lifespan to 50,000 hours.

#### **DIMMING CAPABILITY**

Prime Drive includes dimming capability. Dimming works by engaging PWM to reduce power while maintaining steady output. Vision X offers push button and dial dimmer units.

#### LED TYPES

#### 90 WATT LED

The Light Cannon 8.7" housing features a 90 Watt LED. Combined with IRIS Reflector Technology, this allows for 3,280 feet of usable light.

#### 10 WATT LED

The benefits of the 10 watt LED are great intensity and bulk lighting. The 10 watt LED provides the greatest bulk lighting on the market.

#### 3 WATT LED

The benefits of the 3 watt LED are great output and beam precision. The tight footprint allows for precision optical control.

#### **50 WATT LED**

The Light Cannon 6.7" housing features a 50 Watt LED. Combined with IRIS Reflector Technology, this allows 2,500 feet of usable light from a single LED.

#### 7 AND 6 WATT LED

Utilizing the same footprint as the 5 watt. 7 and 6 Watt LED Lights from Vision X have an increased luminus efficacy over 5-watt LEDs. Producing up to 50% more light than 5 watt.

The Surface Mounted Diode (SMD) is used in the Shockwave fixture and UF32 to create an even, ultra-wide beam pattern for area lighting

The 4.5" Light Cannon housing features a 25 Watt LED. Combined with IRIS Reflector Technology, this allows 1,000 feet of usable light from a single LED.

Utilizing the same footprint as the 3 watt LED, but at twice the output, the 5 watt LED combines the advantages of a tight LED footprint with the ultimate output.


CUBE LEDs from Vision X are ideal for structural applications because of the 117 lumen per watt ratio. We're able to get more light output for a lower cost than standard LEDs

#### **USABLE LIGHT**



Usable light is defined as the light that is actually converted for use in forward projection lighting. Vision X measures this by accounting for effective, rather than raw, lumens in our calculations. We also provide the measurement of distance at which a light achieves one lux. One lux is the level of light needed to read a newspaper. Vision X provides lumen ratings in effective lumens, which factors in the levels of optical, electrical and heat loss. This states the true output of the light as a whole, not just a single component such as the LED.


#### **ISOLUX CHART**



#### Measuring Lux

On Vision X lux charts, the different colors within a light's beam on the lux chart correlates to a different lux level at that distance from the source, according to the colors above.

## TOTAL LIGHT OUTPUT = LUMENS





Light source placed into lumen sphere to measure the complete output of a source

# 10% Electrical Loss 10% Optical Loss


#### **Raw Lumen Output**

Lumens are a common standard for measuring light output at the source. It is important to know that the lighting source manufacturer rating is only for the light source and does not account for losses due to optical inefficiencies, electrical inefficiencies or heat.

#### **Effective Lumen Output**

The sheer output of the light source is not enough to capture the whole story. When rating the effective output of a light source, the light lost as heat, in optical light spray and electrical inefficiency must also be accounted for, as each of these reduce the total


# LIGHT AT A SPECIFIC POINT = LUX AND FOOT CANDLES



Lux measures the amount of light per square meter. Unlike lumens which measures light at the source, lux is measured at a specific area. This helps better determine whether those effective lumens are lighting up the environment with the necessary light.

Foot Candle measures the amount of light per square foot, as opposed to square meter as with lux. Foot-Candle and lux are interchangable, with 100 lux = 10.42 foot-candles.

#### **BEAM PATTERNS ILLUSTRATED**





# **ROOF LIGHT BARS**





**HEADLIGHT UPGRADES** 





**BUMPER LIGHTS** 







# **ROOF MOUNTED LIGHT BARS**

#### THE XPR-S IS THE ULTIMATE RACE LIGHT BAR

All New IRIS Reflectors | XPR-21S Shines 3,281' of Useable Light | Available 5" to 51" Lengths





ITEM #: XPR-21S PART #: 9897424

ITEM#	PART#	APPLICATION
XPR-15S	9897400	Stock cages 30"
XPR-21S	9897424	Aftermarket Cages 40"

See Page 47 for Complete XPR-S Details

#### XPR FEATURES TILTED REFLECTORS FOR A MIXED BEAM

Multiple Mounting Options Included | Highest Quality 10-Watt LED | Available 5" to 51" Lengths



ITEM #: XPR-21M PART #: 9891668

ITEM#	PART#	FITS
XPR-15M	9891644	Stock cages 30"
XPR-21M	9891668	Aftermarket Cages 40"

See Page 48 for Complete XPR Details

## **HEADLIGHT UPGRADES**



ITEM #: XIL-OEHL14RZROPR PART #: 9897516

#### **POLARIS RZR HEADLIGHT KIT**

For Select 2008+ Models | Available in Black, Chrome, White and Halo Models | Plug and Play Installation

ITEM#	PART#	FITS	KIT INCLUDES
XIL-OEHL14RZROPR	9897516	2014+ RZR	Brackets, 4 Optimus Lights
XIL-OEHL08RZR900OP	9898582	2008+ RZR	Brackets, 4 Optimus Lights

See Page 64 for Complete RZR Headlight Details

#### YAMAHA YXZ HEADLIGHT KIT

For Select 2015+ Models | 1 Kit for Low Beam 2nd Kit Optional for High Beam | Plug and Play Installation

ITEM#	PART#	FITS	KIT INCLUDES
XIL-OEHL15YXZCPZ1	9899114	2015+ YXZ	Brackets, 2 Cannon Lights

View our website for complete application information

# **BUMPER LIGHTS**



ITEM #: DURA-410KIT Shown



ITEM #: XIL-LP610A Shown

#### **DURA SERIES BUMPER LIGHT FOR UTVS**

Add 4,244 Raw Lumens to Your UTV | Simple Single Stud Mounting | Adjustable Bracket for Easy Aiming

ITEM#	PART#	APPLICATION	KIT INCLUDES
DURA-410KIT	9891187	Spot Beam Kit	2 Lights and Harness
			See Page 99 for Complete DURA Details

#### **BUMPER LIGHT BARS FOR UTVS**

Available in Flood or Spot Beams | Also Available with Amber LEDs | Add Light to Your Front Bumper

ITEM#	PART#	APPLICATION	INCLUDES
XIL-LPX610	9118758	9" Spot Beam	Light Bar and Harness
XIL-LPX640	9120737	9" Flood Beam	Light Bar and Harness
XIL-LP610A	9888071	9" Amber Spot	Light Bar and Harness
			See Page 49 for Complete Lo Pro Details

# **CHASER REAR LED SYSTEM**



ITEM #: XIL-CBSR27 Shown PART #: 9897202

#### **RECREATIONAL CHASER BAR**

Low Profile Design | Running & Brake Lights In Single Bar | Red/Amber/White/Amber/Red Configuration

ITEM#	PART#	APPLICATION
XIL-CBSR21	9897196	Recreational 28"
XIL-CBSR27	9897202	Recreational 28"

See Page 51 for Complete Chaser Details

#### **RACER CHASER BAR**

Low Profile Design | Running & Brake Lights In Single Bar | Feature Blue Warning Light



ITEM #: XIL-CBSX27 Shown PART #: 9897196

ITEM#	PART#	APPLICATION
XIL-CBSX21	9897219	Racer Xtreme 28"
XIL-CBSX27	9897226	Racer Xtreme 35"

See Page 51 for Complete Chaser Details

# **A-PILLAR LIGHTING**



ITEM #: CTL-CPZ110KIT Shown PART #: 9151069



#### 4.5" LED LIGHT CANNON

Multiple Mounting Options | Lightweight Hybrid Housing | Plug and Play Installation

ITEM#	PART#	KIT INCLUDES
CTL-CPZ110KIT	9151069	2 x 25-Watt LED Light Cannons and Harness
CTL-CPZ110XPKIT	9893365	2 x 40-Watt LED Light Cannons and Harness

See Page 33 for Complete Cannon Details

#### SNAP-ON COVERS FOR CANNONS CHANGE BEAM AND COLOR

Clear Covers to Protect | Red Covers for Sand | Amber Covers for Fog and Debris

ITEM#	PART#	APPLICATION
PCV-CP1RCB	9893235	Red Combo Beam
PCV-CP1BL	9157450	Black Protective

See Page 72 for Complete Polycarbonate Cover Details

# **ACCESSORIES**



ITEM #: XIL-PDW Shown PART #: 9136127

SECURITY HARDWARE



#### PRO POD UNDER GLOW LIGHTING

Add Color to Your UTV | Extremely Low Power Consumption | Add Light to Your Front Bumper

ITEM#	PART#	COLOR
XIL-PDA	9136219	Amber
XIL-PDB	9136301	Blue
XIL-PDG	9136394	Green

**DURA MINI** 2.75" Universal Flood Light



ITEM#	PART#	COLOR
XIL-PDR	9136486	Red
XIL-PDW	9136127	White

See Page 74 for Complete Pro Pod Details

MINI SOLO 1.7" Pod Available in Colors



View our Website for Complete Range of Accessories



# **HEADLIGHT UPGRADES**



# FOG LIGHT UPGRADES



WINDSHIELD LIGHT BAR



**HOOD MOUNT** 



A-PILLAR



ACCESSORIES



# **HEADLIGHT UPGRADES**



ITEM #: XIL-7RDKITJK PART #: 9892733

#### PLUG AND PLAY HEADLIGHT UPGRADE FOR JEEP HEADLIGHTS

Works With Canbus | Multiple LEDs Fill in Roadway | Long Range High Beams

ITEM#	PART#	APPLICATION
XIL-7RDKITJK	9892733	Jeep Headlight Chrome Finish
XIL-7RDBKITJK	9892825	Jeep Headlight Black Chrome Finish

See Page 56 for Complete Vortex Details



# **WINDSHIELD LIGHT BARS**

#### XMITTER PRIME XTREME MAX LIGHT OUTPUT LIGHT BAR

Mixed Beam for Wide Pattern | Mount Using End Caps Or Feet | Wiring Included

INCLUDES




ITEM #: XIL-PX90M PART #: 9132792

ITEM #: XPR-27M Shown



#### XPR LONG DISTANCE LIGHT BAR

Tilted Reflectors for Wide Pattern | Mount Using End Caps Or Feet | Wiring Included



See Page 48 for Complete XPR Details

See Page 61 for Complete Vx Spec Details

# **A-PILLAR LIGHTING**



ITEM #: XIL-OEA0713JKCPZ1 Shown PART #: 9888415



#### JEEP A-PILLAR BRACKETS AND 4.5" LED LIGHT CANNON KITS

Multiple Mounting Options | Lightweight Hybrid Housing | Plug and Play Installation

ITEM#	PART#	KIT INCLUDES
XIL-OEA0713JKCPZ1	9888415	Brackets for Jeep JK and 2x 4.5" Light Cannon
XIL-OEA9706TJCPZ1	9892795	Brackets for Jeep TJ and 2x 4.5" Light Cannon

#### SNAP-ON COVERS FOR CANNONS CHANGE BEAM AND COLOR

Clear Covers to Protect | Red Covers for Sand | Amber Covers for Fog and Debris

ITEM#	PART#	APPLICATION
PCV-CP1RCB	9893235	4.5" Red Combo Beam Cover
PCV-CP1BL	9157450	4.5" Black Protective Cover

See Page 72 for Complete Polycarbonate Cover Details

# **FOG LIGHT UPGRADES**



ITEM #: XIL-OE1012JKOPR Shown PART #: 9154756



ITEM #: XIL-OE13JKXOPRH Shown PART #: 9892474

2007 AND UP JEEP JK FOG LIGHTS

No Drilling Required | Direct Plug-And-Play With Factory Wiring | Dramatically Increased Visibility

ITEM#	PART#	APPLICATION
XIL-OE0709JKV2OPR	9145754	07-09 Jeep JK Fog Light Upgrade
XIL-OE0709JKV2OPRH	9891811	07-09 Jeep JK Fog Light Upgrade Lights with Halo
XIL-OE1012JKV2OPR	9154756	2010+ Jeep JK Fog Light Upgrade
XIL-OE1012JKV2OPRH	9891828	2010+ Jeep JK Fog Light Upgrade with Halo

#### JEEP JK X FOG LIGHTS

No Drilling Required | Direct Plug-And-Play With Factory Wiring | Dramatically Increased Visibility

ITEM#	PART#	APPLICATION
XIL-OE13JKXOPR	9891088	2013+ Jeep JK X Fog Light Upgrade
XIL-OE13JKXOPRH	9892474	2013+ Jeep JK X Fog Light Upgrade with Halo

See Page 60 for Complete VxSpec Details

**VISION X LIGHTING - 2017 CATALOG** 

# **HOOD MOUNT**



ITEM #: XIL-OEH0713JKPX36 Shown

#### HOOD MOUNT KITS FOR JEEP JK

No Drill Installation | Bracket Holds up to 24" Light Bar | Adds Up to 19,008 lm

ITEM#	PART#	APPLICATION
XIL-OEH0713JKPX36	9891002	Bracket with 21" XIL-PX3610 Light Bar For Max Light Output
XIL-OEH0713JKXPI12	9891019	Bracket with 24" XPI-12M Light Bar For Long Distance

See Page 60 for Complete VxSpec Details



#### **ACCESSORIES**



ITEM #: HIL-STW Shown PART #: 4005419

SECURITY HARDWARE
Secure Your Lights and Accessories

# TANTRUM 8 POD UNDERCARRIAGE LIGHTING KITS

Add Color to Your Jeep | Includes Wireless Remote | 4 Pods with 10' Cords 4 Pods with 20' Cords

ITEM#	PART#	COLOR
HIL-STA	4005662	Amber
HIL-STB	4005372	Blue
HIL-STG	4005396	Green

**DURA MINI** 2.75" Universal Flood Light




ITEM#	PART#	COLOR
HIL-STM	4005679	Multi
HIL-STR	4005389	Red
HIL-STW	4005419	White

See Page 75 for Complete Tantrum Details

PRO POD
Available in Multiple Colors



View our Website for Complete Range of Accessories



# **FOG LIGHT UPGRADES**







A-PILLAR LIGHTS



**DRIVING LIGHTS** 



**ROOF LIGHT BARS** 



ACCESSORIES



#### **VISION X LIGHTING - 2017 CATALOG**

# **FOG LIGHT UPGRADES**



ITEM #: XIL-OE9913FSDDURA PART #: 9891200



ITEM #: XIL-OE0711GSUMX PART #: 9133157

#### FORD TRUCKS PLUG AND PLAY LED FOG LIGHT UPGRADE KITS

ITEM#	PART#	APPLICATION
XIL-OE9913FSDDURA	9891200	99-16 Ford Superduty Fog Light Using 2 x DURA-410 Lights
XIL-OE10FROP	9133515	10-14 Ford Raptor Fog Light Using 4 x XIL-OP110 Lights
XIL-OE10FROPH	9892450	10-14 Ford Raptor Fog Light Using 4 x Halo XIL-OPH115 Lights

#### DODGE\RAM TRUCKS PLUG AND PLAY LED FOG LIGHT UPGRADE KITS

ITEM#	PART#	APPLICATION
XIL-OE0913DROP	9888552	10-16 Dodge Ram Fog Light Using 2 x XIL-OP110 Lights
XIL-OE0913DROP1MX2	9890685	10-16 Dodge Ram Fog Light Using 4 x Optimus Lights
XIL-OE0210DRUMX	9133065	02-10 Dodge Ram Fog Light Using 2 x XIL-UMX4010 Lights

#### GM TRUCKS PLUG AND PLAY LED FOG LIGHT UPGRADE KITS

ITEM#	PART#	APPLICATION
XIL-OE0711GSUMX	9133157	07-13 GMC Sierra Fog Light Using 2 x XIL-UMX4010 Lights
XIL-OE0711CSS1100	9120829	07-13 Chevrolet Silverado Fog Light Using 4 x XIL-S1100 Lights

#### TOYOTA TRUCKS PLUG AND PLAY LED FOG LIGHT UPGRADE KITS

ITEM#	PART#	APPLICATION
XIL-OE0711TTUMX	9133249	07-14 Toyota Tundra Fog Light Using 2 x XIL-UMX4010 Lights

View our website for complete application information

# **A-PILLAR LIGHTS**



ITEM #: CTL-CPZ110KIT Shown



#### 4.5" LED LIGHT CANNON

Multiple Mounting Options | Lightweight Hybrid Housing | Plug and Play Installation

ITEM#	PART#	KIT INCLUDES
CTL-CPZ110KIT	9151069	2 x 4.5" 25-Watt LED Light Cannons and Harness
CTL-CPZ110XPKIT	9893365	2 x 4.5" 40-Watt LED Light Cannons and Harness

See Page 33 for Complete Cannon Details

#### SNAP-ON COVERS FOR CANNONS CHANGE BEAM AND COLOR

Clear Covers to Protect | Red Covers for Sand | Amber Covers for Fog and Debris

ITEM#	PART#	APPLICATION
PCV-CP1RCB	9893235	Red Combo Beam for 4.5" Cannon
PCV-CP1BL	9157450	Black Protective for 4.5" Cannon

See Page 72 for Complete Polycarbonate Cover Details

# **ROOF LIGHT BARS**



ITEM #: XPR-27M Shown

#### 50" XPR LONG DISTANCE LIGHT BAR WITH TILTED REFLECTORS

Tilted Reflectors for Wide Pattern | Mount Using End Caps Or Feet | Wiring Included

ITEM#	PART#	APPLICATION
XPR-27M	9891682	50" Tilted Reflector XPR Light Bar

See Page 48 for Complete XPR Details

#### 50" XMITTER PRIME XTREME MAX LIGHT OUTPUT LIGHT BAR

Mixed Beam for Wide Pattern | Mount Using End Caps Or Feet | Wiring Included

ITEM#	PART#	FITS
XIL-PX90M	9132792	50" Mixed Beam PX Light Bar

See Page 46 for Complete PX Details

# **BUMPER LIGHT BARS**



ITEM #: XIL-OEB09F150PX36 Shown PART #: 9891156



ITEM #: XIL-OEB0913DRPX3610 Shown PART #: 9889245

#### FORD TRUCKS PLUG AND PLAY LED FOG LIGHT UPGRADE KITS

ITEM #         PART #         APPLICATION           XIL-OEB09F150PX36         9891156         09-14 Ford F150 Using 1 x XIL-PX3610 Light Bar           XIL-OEB09F150ECO         9891170         09-14 Ford F150 Eco-Boost Using 2 x XIL-PX610 Light Bar           XIL-OEB10FRPX3610         9887357         10-14 Ford Raptor Using 1 x XIL-PX3610 Light Bar
XIL-OEB09F150ECO 9891170 09-14 Ford F150 Eco-Boost Using 2 x XIL-PX610 Light Bar
XIIOEB10ERPX3610 9887357 10-14 Ford Rantor Using 1 x XIIPX3610 Light Bar
ALE GEBTOTAL AGOTO
XIL-OEB0810FSDPX3610 9891842 08-10 Ford Superduty Using 1 x XIL-PX3610 Light Bar
XIL-OEB0810FSDXPI12M 9892306 08-10 Ford Superduty Using 1 x XPI-12M Light Bar
XIL-OEB1114FSDPX3610 9891873 11-16 Ford Superduty Using 1 x XIL-PX3610 Light Bar
XIL-OEB1114FSDXPI12M 9892290 11-16 Ford Superduty Using 1 x XPI-12M Light Bar

#### DODGE\RAM TRUCKS PLUG AND PLAY LED FOG LIGHT UPGRADE KITS

ITEM#	PART#	APPLICATION
XIL-OEB0913DRPX3610	9889245	10-16 Dodge Ram Using 1 x XIL-PX3610

View our website for complete application information

## **DRIVING LIGHTS**



ITEM #: CTL-CPZ610KIT Shown PART #: 9888545



ITEM #: CTL-TPX1810 Shown PART #: 9111018

#### 6.7" LED LIGHT CANNON

Multiple Mounting Options | 25 Lights in 1 With Snap on Covers | Wiring Included

ITEM#	PART#	APPLICATION
CTL-CPZ610KIT	9888545	Two 50-Watt Single Source LED Long Distance 6.7" Lights

See Page 33 for Complete Cannon Details

#### 6.7" TRANSPORTER 18 LED DRIVING LIGHT

Smooth Beam Pattern to Fill Roadway | Color Changing Covers | Wiring Included

ITEM#	PART#	APPLICATION
CTL-TPX1810	9111018	90 Watt 6.7" Light with 10° Spot Beam Pattern
CTL-TPX1840	9111193	90 Watt 6.7" Light with 40° Flood Beam Pattern

See Page 34 for Complete Transporter Details

# **ACCESSORIES**



ITEM #: XIL-SRECEIVERDURAMX2 Shown PART #: 9899121

WINCH MOUNT Light Bar Mount Plate for Winch



#### RECEIVER TOW MOUNT KIT FOR REVERSE FLOOD LIGHTS

Wire to Reverse or Separate Switch | Weatherproof Lights For Boat Launching | Multiple Lights Available

ITEM#	PART#	APPLICATION
XIL-SRECEIVERDURAMX2	9899121	Receiver Light Kit with Bracket, 2 x DURA-M460, Harness
XIL-SRECEIVERS1101X2	4008595	Receiver Light Kit with Bracket, 2 x XIL-S1101, Harness

See Page 78 for Complete Mounting Solutions Details

#### FLUSH MOUNT LIGHTS DURA FLUSH



BORG MODULE
Bluetooth Controller for Prime Drive



View our Website for Complete Range of Accessories

PART #: 9132792

ITEM #: XIL-PX90M Shown



# **HEADLIGHT UPGRADES**



# **BUMPER LIGHTS**



# **BUMPER LIGHT BARS**



CAB-OVER



LOAD LIGHTS



# ACCESSORIES



#### **VISION X LIGHTING - 2017 CATALOG**

# **HEADLIGHT UPGRADES**



ITEM #: XIL-46DBKIT PART #: 9897837

ITEM #: XIL-7RDKIT

PART #: 9891224

#### 4X6" DUAL BEAM HEADLIGHT LED UPGRADE KIT

High and Low Beam in Single Housing | IRIS Reflectors for Long Distance High Beams | Bright Halo

ITEM#	PART#	APPLICATION
XIL-46DKIT	9897820	Pair of Polished Chrome Face 4x6" LED Headlights
XIL-46DBKIT	9897837	Pair of Black Chrome Face 4x6" LED Headlights

See Page 56 for Complete Headlight Details

#### 7" HEADLIGHT LED UPGRADE KIT

Additional LEDs To Fill in Roadway | IRIS Reflectors for Long Distance High Beams | Bright Halo

ITEM#	PART#	APPLICATION
XIL-7RDKIT	9891224	Pair of Polished Chrome Face 7" LED Headlights
XIL-7RDBKIT	9892443	Pair of Black Chrome Face 7" LED Headlights

See Page 56 for Complete Headlight Details

# **BUMPER LIGHT BARS**



ITFM #: XII -PX3610 PART #: 9117041



ITEM #: XPR-12S Shown

#### XMITTER PRIME XTREME MAXIMUM LIGHT OUTPUT LIGHT BAR

Full Range Fills in Road Way | Multiple Mounting Options | Wiring Included

ITEM#	PART#	APPLICATION
XIL-PX3610	9117041	20" Spot Beam LED Light Bar
XIL-PX5410	9117225	30" Spot Beam LED Light Bar

See Page 46 for Complete PX Details

#### XPR-S XTREME LONG DISTANCE LIGHT BAR

IRIS Reflector for Long Range Light | Dual Mounting Options Included | Wiring Included

ITEM#	PART#	INCLUDES
XPR-12S	9897394	24" XPR-S Light Bar Producing 2,461 ft of Usable Light
XPR-15S	9897400	29" XPR-S Light Bar Production 2,784 ft of Usable Light

See Page 47 for Complete XPR-S Details

# **LOAD LIGHTS**



ITEM #: XIL-UMX4060 Shown



ITEM #: DURA-660 Shown PART #: 9888385

#### **UTILITY MARKET SERIES 35-WATT LED WORK LIGHT**

Single Stud Mounting | Available in Round or Square Housing | Durable Polycarbonate Lens

ITEM#	PART#	APPLICATION
XIL-UMX4060	9118307	4" Round LED Work Light 60° Flood Beam
XIL-UMX4460	9118482	4" Square LED Work Light 60° Flood Beam

#### See Page 97 for Complete UMX Details

#### **DURA SERIES 30 AND 20 WATT LED WORK LIGHTS**

Single Stud Mounting | Two Sizes Available | Durable Polycarbonate Lens

ITEM#	PART#	APPLICATION
DURA-460	9141527	4" Square 20-Watt Work Light 60° Flood Beam
DURA-660	9888385	5" Rectangular 30-Watt Work Light 60° Flood Beam

See Page 99 for Complete DURA Details

# **BUMPER LIGHTS**



ITEM #: CTL-CPZ610KIT Shown



ITEM #: CTL-TPX1810 Shown PART #: 9111018

#### 6.7" LED LIGHT CANNON

Multiple Mounting Options | 25 Lights in 1 With Snap on Covers | Wiring Included

ITEM#	PART#	APPLICATION
CTL-CPZ610KIT	9888545	Two 50-Watt Single Source LED Long Distance 6.7" Lights

See Page 33 for Complete Cannon Details

#### 6.7" TRANSPORTER 18 LED DRIVING LIGHT

Smooth Beam Pattern to Fill Roadway | Color Changing Covers | Wiring Included

ITEM#	PART#	APPLICATION
CTL-TPX1810	9111018	90 Watt 6.7" Light with 10° Spot Beam Pattern
CTL-TPX1840	9111193	90 Watt 6.7" Light with 40° Flood Beam Pattern

See Page 34 for Complete Transporter Details

# **CAB-OVER**



ITEM #: CTL-CPZ810KIT Shown

Multiple Mounting Options | 25 Lights in 1 With Snap on Covers | Lights Up 3,280 ft of Usable Light

8.7" LED LIGHT CANNON

ITEM#	PART#	APPLICATION
CTL-CPZ810KIT	9890074	Two 90-Watt Single Source LED Long Distance 8.7" Lights

See Page 33 for Complete Cannon Details

#### SNAP-ON COVERS FOR 8.7" CANNONS CHANGE BEAM AND COLOR

Black Street Legal Cover | Amber Covers for Snow | Combo Cover for Best of Both Beams

ITEM#	PART#	APPLICATION
PCV-8500YCB	9893211	8.7" Amber Combo Beam Cover
PCV-8500Y	4002791	8.7" Amber Spot Cover
PCV-8500BL	9890876	8.7" Black Protective Cover

See Page 72 for Complete Polycarbonate Cover Details

# **ACCESSORIES**



ITEM #: XIL-PDW Shown PART #: 9136127

SECURITY HARDWARE Secure Your Lights and Accessories



#### PRO POD UNDER GLOW LIGHTING

Add Color to Your UTV | Durable PC Lens for Any Application | Add Accent Light Anywhere

ITEM#	PART#	COLOR
XIL-PDA	9136219	Amber
XIL-PDB	9136301	Blue
XIL-PDG	9136394	Green

DUDA MINI
DURA MINI
2.75" Universal Flood Lig



PART# COLOR ITEM# XIL-PDR 9136486 Red XIL-PDW 9136127 White See Page 74 for Complete Pro Pod Details



View our Website for Complete Range of Accessories















# 7" ROUND LED HEADLIGHT




ITEM #: XMC-7RD Shown PART #: 9892061

#### DOT APPROVED LED HEADLIGHT WITH BRIGHT LED HALO RING

Multiple LEDs Fill In Roadway | Polycarbonate Lens | Dramatically Improves Safety

<b>BEAM MODES</b> Halo, Low, High	<b>WEIGHT</b> 2.20 lb / 1.00 kg	<b>DIMENSIONS</b> 6.96" x 3.86"
<b>RAW LUMENS</b> 4,210 lm (ea)	REFLECTOR FINISH Polished Chrome, Black Chrome	<b>METRIC</b> 177mm x 177mm x 97.8mm



Replaces OEM 68342-05A, 67700032, 67700243

View Our Website For Complete Application Chart



ITEM #: XMC-5750DKIT Shown PART #: 9895673

# 5.75" OVAL ROAD GLIDE KIT

#### 2004-2013 HARLEY-DAVIDSON ROAD GLIDE DIRECT REPLACEMENT

Multiple LEDs Fill In Roadway | Polycarbonate Lens | Dramatically Improves Safety

**WEIGHT** 

2.20 lb / 1.00 kg

REFLECTOR FINISH

Polished Chrome, Black Chrome



XMC-575ODKIT

XMC-575ODBKIT





9895673

9895697








Replaces OEM 67700109, 67775-01C

View Our Website For Complete Application Chart



**DIMENSIONS** 

6.96" x 6.96" x 3.85"

METRIC

177mm x 177mm x 97.8mm

# 5.75" ROUND LED HEADLIGHT




ITEM #: XMC-575RD Shown

#### DOT APPROVED LED HEADLIGHT WITH BRIGHT LED HALO RING

Multiple LEDs Fill In Roadway | Polycarbonate Lens | Dramatically Improves Safety


BEAM MODES Halo, Low, High	<b>WEIGHT</b> 1.95 lb / 0.88 kg	<b>DIMENSIONS</b> 5.65" x 5.65" x 2.88"	
<b>RAW LUMENS</b>	REFLECTOR FINISH	<b>METRIC</b>	
4,210 lm (ea)	Polished Chrome, Black Chrome	146mm x 146mm x 73mm	





Replaces OEM 68297-05A, 67700144A

View Our Website For Complete Application Chart





**DIMENSIONS** 

2.7" x 2.7" x 0.87"

**METRIC** 

68.5mm x 68.5mm x 21mm

# **BAG LIGHTS**

ITEM #: XMC-BKW2 Shown PART #: 9895246

# LOW CONSUMPTION COMPARTMENT LIGHTING FOR TRUNKS, BAGS, SADDLES

WARRANTY

Extended

WEIGHT

0.20 lb / 0.09 kg (ea)

Two Light Kit | 40 Inch Power Cord With Flush Switch Included | Water & Dust Proof





**BEAM MODES** 

Frosted Lens

**RAW LUMENS** 







ITEM#	PART#	WIRING	QTY
XMC-BKW2	9895246	40" Cord With Switch	Two Pods

ITEM #: XMC-45RDKIT Shown

# FIVE TIMES BRIGHTER THAN HALOGEN PASSING LAMPS

Multisurface Reflector | Polycarbonate Lens | Dramatically Improves Safety

**WEIGHT** 

2.20 lb / 1.00 kg

REFLECTOR FINISH

Polished Chrome, Black Chrome



**MOTORCYCLE PASSING LAMP** 




**BEAM MODES** 


Driving

**RAW LUMENS** 

2,104 lm (kit)







**DIMENSIONS** 

4.49" x 4.49" x 2.24"

**METRIC** 

114mm x 114mm x 57mm

# **ACCESSORIES**



ITEM #: XIL-OPRH115KIT Shown PART #: 9891729

**BILLET CLAMPS** Universal 0.75" - 3.00" Tube Mounting



#### OPTIMUS ROUND LED DRIVING LIGHT

Single Bolt Mounting | Capable of 883 ft of Usable Light | Available In Halo and Non-Halo Models

ITEM#	PART #	FINISH	QTY
XIL-OPRH115KIT	9891729	Black, Halo	Kit (2)
XIL-OPR110KIT	9141251	Black, Non-Halo	Kit (2)

See Page 36 for Complete Optimus Details

WIRING



**PRO POD** Available in Multiple Colors



When we released the 25 watt 4.5" LED Light Cannon, no one expected us to double the size shortly after being on the market for one year. Enter the 8.7" LED Light Cannon. This massive single source LED excels at long range distances, shining up to 3,280 feet of usable light all from a 90 watt Luminus Premium LED. With the addition of the 50 watt 6.7" Cannon, that boasts a respectable 2,500 feet of usable light, there's a Light Cannon option for everyone. With the available snap-on covers, you can easily turn any Cannon into 25 different lights.

# UNIMATCHED DISTANCE + VERSATILITY + VALUE



8.7" 3280' 6.7" 2500'

4.5 1115' USABLE LIGHT NEW! 40-WATT

**1000'** USABLE LIGHT

# **LED**LIGHTS

Vision X Automotive/Offroad LED lighting runs at a 6000K temperature for intense, bright white light for increased visibility and safety. LED technology has many advantages over traditional lighting options, including low power consumption, no voltage spike at start-up, 50,000 hour life span, and increased durability with the absence of a bulb.

25 LIGHTS IN ONE!



With Snap-On Covers

#### AUTOMOTIVE/OFFROAD

# LED LIGHT CANNONS

#### ABOUT THE CANNON SERIES

The LED Light Cannon Series from Vision X is unmatched by any other fixture on the market. By utilizing Vision X's IRIS Reflector Technology and top binned Single-Source Luminus LEDs, the Cannon Series can produce up to 3,280 feet of usable light.

Each Light Cannon is 25 Lights In One with the help of the available polycarbonate snap-on covers that can alter the beam pattern and change the color of the Cannon. Tackle any weather condition with the proper color cover, or quickly change your spot cover to a flood cover for a wider beam when necessary

The Light Cannon Series is sold as a single fixture, or as a complete Light Kit consisting of two lights and a dual wiring harness with lighted rocker switch.



#### BIG-CHIP SINGLE SOURCE LEDS



#### **Luminus LEDs**

Most LEDs on the market today are composed of smaller LEDs combined together to make one large unit. With the LED Light Cannon Series, Vision X uses larger Single Source LEDs that are one diode, capable of producing more light and a brighter

#### **Light Kits Available**

Each size of LED Light Cannon is available in a two light kit that includes a dual wiring harness and a lighted rocker switch.





FLOOD WIDE FLOOD

25 LIGHTS IN ONE

CLEAR COVERS

color

Unbreakable, dust resistant

protection to protect the light

from debris and particulates.

Recommended for users who

wish to maintain original light

RED COVERS

Reduces light temperature and glare back in order to enhance penetration in dust and air particulates. Ideal for vehicles in extreme dust conditions.



EURO ELLIPTICAL

#### **BLUE COVERS**

Increases lighting distance when used in snow conditions by reflecting the blue light off the snow. Recommended for vehicles in heavy winter conditions.



#### AMBER COVERS

Battles fog conditions by reducing the amount of blue light. Mimics classic Halogen color temperature. Great for driving in dust at high speeds



#### **BLACKOUT COVERS**

Covers the fixture with a solid black protective cover with a high contrast "X" logo. Required in select states for on-road use.



# 4.5" 40-WATT LIGHT CANNON XP



PART #: 9893259 \*Lights Available with Black Bezels

ITEM #: CTL-CPZ110XP Shown

#### XTREME PERFORMANCE 40-WATT SINGLE SOURCE LED PRODUCES 1,100' OF USEABLE LIGHT 10° Beam Pattern | Polycarbonate Covers Available (Round) | Two Light Kits Available





\*Additional Part Numbers & Technical Information On Page 40





# 8.7" 90-WATT LIGHT CANNON



ITEM #: CTL-CPZ810 Shown

ITEM #: CTL-CPZ610 Shown

# 90-WATT SINGLE SOURCE LED PRODUCES 3,280' OF USABLE LIGHT

Lightweight Hybrid Housing | Long Range IRIS Reflectors | Snap-On Covers Change Beam Pattern

BEAM PATTERNS 10°	<b>WEIGHT</b> 10.36 lb / 4.7 kg	<b>DIMENSIONS</b> 8.71" x 10.58" x 4.57"
<b>RAW LUMENS</b> 5,800 lm (ea)	DISTANCE TO 1 LUX 3,280'	<b>METRIC</b> 221mm x 269mm x 116mm

L.E.D.S	WARRANTY	DC INPUT	HOUSING	WATERPROOF	KATED	OPERATION TEMP	LIFESPAN
ITEM			PART	#	QTY	В	EAM
CTL-C	CPZ810		98908	352	1		10°
CTL-C	CPZ810KI	Т	98900	)74	2		10°





# 6.7" 50-WATT LIGHT CANNON

#### 50-WATT SINGLE SOURCE LED PRODUCES 2,500' OF USABLE LIGHT

Lightweight Hybrid Housing | Long Range IRIS Reflectors | Snap-On Covers Change Beam Pattern

BEAM PATTERNS 10°, 20°	<b>WEIGHT</b> 5.51 lb / 2.5 kg	<b>DIMENSIONS</b> 6.69" x 8.82" x 6.31"	
RAW LUMENS	DISTANCE TO 1 LUX	<b>METRIC</b>	
3,200 lm (ea)	2,500'	170mm x 224mm x 160mm	



















ITEM# CTL-CPZ610 10° 9888538 CTL-CPZ610KIT 9888545 10° CTL-CPZ620 9891736 20° CTL-CPZ620KIT 9891743 2 20°

# 4.5" 25-WATT LIGHT CANNON

#### 25-WATT SINGLE SOURCE LED PRODUCES 1,000' OF USABLE LIGHT

Lightweight Hybrid Housing | Long Range IRIS Reflectors | Snap-On Covers Change Beam Pattern



ITEM #: CTL-CPZ110 Shown PART #: 9150970

BEAM PATTERNS 10°	<b>WEIGHT</b> 2.02 lb / 0.92 kg	<b>DIMENSIONS</b> 4.72" x 5.75" x 4.35"	
RAW LUMENS	DISTANCE TO 1 LUX	<b>METRIC</b>	
2,500 lm (ea)	1,000'	120mm x 147mm x 110mm	



ITEM#

CTL-CPZ110

CTL-CPZ110KIT









PART #

9150970

9151069





QTY



10°

10°





<sup>\*</sup>Additional Part Numbers & Technical Information On Page 40

<sup>\*</sup>Additional Part Numbers & Technical Information On Page 40

<sup>\*</sup>Additional Part Numbers & Technical Information On Page 40

#### AUTOMOTIVE/OFFROAD

# TRANSPORTER SERIES

#### ABOUT THE TRANSPORTER SERIES

The Transporter Series utilizes high powered 5-watt LEDs to provide intense light output for commercial applications. The Transporter Series is ideal for long-haul Trucking and Transport applications because the 50,000 hour lifespan takes away from unscheduled fleet maintenance like bulb replacement, etc.

Additionally, brighter driving conditions for operators ensures greater safety and reliability for drivers on the road. Proper lighting can reduce the amount of time it takes for a load to be delivered and can also reduce the chances for an accident on roadways affected by harsh conditions.





#### **KNURLED AIMING KNOBS**

The Transporter Series can be precisely adjusted to any angle within 15° thanks to the knurled adjustment knobs located at the

#### LIGHTED ROCKER HARNESS



#### **INCLUDED HARNESS**

The Transporter Series comes packaged with a single light wiring harness with lighted rocker switch for activation and a weatherproof deutsch connector, ensuring the longevity of the light. Mounting and wiring is a breeze so you'll be out on the

#### **RECESSED OPTICS**



#### SMOOTH BEAM PATTERN

Each Transporter produces a smooth and even beam pattern due to the recessed reflectors that are precisely angled to achieve an effective beam pattern for on-road driving.



# **TRANSPORTER 18 LED**



ITEM #: CTL-TPX1810 Shown PART #: 9111018

#### 90-WATT LED LIGHT FOR LONG-HAUL TRUCK AND TRANSPORT

Eighteen 5-Watt LEDs | Protective Polycarbanate Covers Available | Truck and Transport Ready

BEAM PATTERNS 10°, 40°	<b>WEIGHT</b> 6.17 lb / 2.8 kg	<b>DIMENSIONS</b> 6.42" x 7.19" x 4.57"
RAW LUMENS	DISTANCE TO 1 LUX	<b>METRIC</b>
9,504 lm (ea)	840'	171mm x 183mm x 116mm

40°



CTL-TPX1840 9111193 \*Additional Part Numbers & Technical Information On Page 40





# **TRANSPORTER 12 LED**



ITEM #: CTL-TPX1210 Shown

#### 60-WATT LED LIGHT FOR LONG-HAUL TRUCK AND TRANSPORT

Twelve 5-Watt LEDs | Protective Polycarbonate Covers Available | Truck and Transport Ready

BEAM PATTERNS 10°, 40°	<b>WEIGHT</b> 5.95 lb / 2.7 kg	<b>DIMENSIONS</b> 6.42" x 7.19" x 4.57"
<b>RAW LUMENS</b>	DISTANCE TO 1 LUX	<b>METRIC</b>
6,336 lm (ea)	778'	171mm x 183mm x 116mm











# TRANSPORTER 9 LED



ITEM #: CTL-TPX910 Shown PART #: 9110110

#### LED LIGHT FOR LONG-HAUL TRUCK AND TRANSPORT

Nine 5-Watt LEDs | Protective Polycarbonate Covers Available | E-Mark Approved Fixture

BEAM PATTERNS 10°, 40°	<b>WEIGHT</b> 5.95 lb / 2.7 kg	<b>DIMENSIONS</b> 6.42" x 7.19" x 4.57"
RAW LUMENS	DISTANCE TO 1 LUX	<b>METRIC</b>
4,752 lm (ea)	656'	163mm x 183mm x 116mm



<sup>\*</sup>Additional Part Numbers & Technical Information On Page 40





#### AUTOMOTIVE/OFFROAD

# **OPTIMUS SERIES**

#### ABOUT THE OPTIMUS SERIES

By combining Single-Source LEDs with Vision X's IRIS Reflector Technology, the Optimus Series is capable of reaching powerful distances from a small housing. The Optimus is available in three different beam patterns, allowing users to choose between distance or spread.

Kits consisting of two lights and a wiring harness are available for each member of the Optimus family, and each is also available in Black, Chrome or White housing colors.

The Optimus Series is often used in Vision X Vehicle Specific Kits, to see the available options and to learn more please see page 60.

COVERS AVAILABLE

#### TWO LIGHT KIT



#### **COMPLETE KIT**

Each model in the Optimus Series can be purchased in a complete lighting kit consisting of two fixtures, a dual-wiring harness, and necessary mounting. Everything you need to explore the night.



# **OPTIMUS HALO**

#### LONG-RANGE 10-WATT LED WITH BRIGHT LED HALO RING

15° Beam Pattern | Polycarbonate Covers Available (Round) | Two Light Kits Available

**WEIGHT** 

1.37 lb / 0.62 kg

DISTANCE TO 1 LUX



ITEM #: XIL-OPRH115 Shown PART #: 9891712

ITEM #: XIL-OPH115 Shown PART #: 9891699

AVAILABLE	WARRANTT	DC INFO	HOUSING WATERFRO
ITEM#	PART #	QTY	HOUSING
XIL-OPRH115	9891712	1	Round
XIL-OPH115	9891699	1	Square

	QTY	HOUSING	ITEN
2	1	Round	XIL-C
9	1	Square	XIL-C

OPRH115KIT 9891729 Round OPH115KIT 9891705 Square

**ROUND DIMENSIONS** 

3.62 x 3.62 x 3.79"/92 x 92 x 96mm

**SQUARE DIMENSIONS** 

2.99 x 2.99 x 3.79"/76 x 76 x 97mm

**BEAM PATTERNS** 

15°

**RAW LUMENS** 

# **OPTIMUS SINGLE**




ITEM #: XIL-OP110 Shown PART #: 9123882

#### 10-WATT UNIVERSAL LED DRIVING LIGHT PRODUCES ULTIMATE DISTANCE

Compact 3.0" Housing | High-Strength Adjustable Trunnion Mount | Two Light Kits Available

<b>BEAM PATTERNS</b> 10°, 20°, 60°	<b>WEIGHT</b> 1.37 lb / 0.62 kg	<b>DIMENSIONS</b> 2.99" x 2.99" x 3.82"
RAW LUMENS 1,052 lm (ea)	DISTANCE TO 1 LUX 883'	<b>METRIC</b> 76mm x 80.5mm x 97mm



<sup>\*</sup>Additional Part Numbers & Technical Information On Page 41

		6 6TF	
ITEM#	PART #	QTY	BEAM
XIL-OP110KIT	9124421	2	10°
XIL-OP120KIT	9138015	2	20°
XIL-OP160KIT	9137926	2	60°

# **OPTIMUS ROUND**




ITEM #: XIL-OPR110 Shown



# 10-WATT UNIVERSAL LED DRIVING LIGHT PRODUCES ULTIMATE DISTANCE

Compact 3.0" Housing | Snap-On Color & Beam Changing Covers | Two Light Kits Available

Е	BEAM PATTERNS 10°, 20°, 60°	<b>WEIGHT</b> 1.53 lb / 0.69 kg	<b>DIMENSIONS</b> 3.62" x 3.62" x 3.82"
	RAW LUMENS 1,052 lm (ea)	DISTANCE TO 1 LUX 883'	METRIC 92mm x 92mm x 97mm



XIL-OPR110	9140896	1	10°	XII
XIL-OPR120	9141077	1	20°	XII
XIL-OPR160	9141169	1	60°	XII

*Additional Part Numbers &	Technical	I Information	On Page 41

#### L-OPR110KIT 9141251 10° 9141343 IL-OPR120KIT 20° IL-OPR160KIT 9141435 60°

# **OPTIMUS DUAL**

#### 20-WATT UNIVERSAL LED DRIVING LIGHT PRODUCES ULTIMATE DISTANCE Power Of Two Optimus In One | Available In Kits | High-Strength Adjustable Trunnion Mount



ITEM #: XIL-OP210 Shown PART #: 9123882

BEAM PATTERNS	WEIGHT	DIMENSIONS
10°, 20°, 60°	2.25 lb / 1.02 kg	5.83" x 3.82" x 4.80"





1	ITEM#	PART #	QTY	BEAM
	XIL-OP210KIT	9125053	2	10°
	XIL-OP220KIT	9137834	2	20°
	XIL-OP260KIT	9137742	2	60°

<sup>\*</sup>Additional Part Numbers & Technical Information On Page 41

<sup>\*</sup>Additional Part Numbers & Technical Information On Page 41

#### AUTOMOTIVE/OFFROAD

# **SOLO POD SERIES**

#### ABOUT THE SOLO SERIES

Compact yet powerful, the Solo Pod Series from Vision X provides intense light output from a small housing. Each Solo produces the equal light output of a pair of headlights from a modern vehicle.

The Solstice Solo excels at multiple applications thanks to the wide selection of different beam patterns. Perfect for dirt bikes, reverse lights, marine lights, or rock lights - the applications are endless.

Additionally, there are multiple accessories that can further extend the versatility of the Solstice Solo.

#### FLEXIBLE MOUNTING



#### SINGLE-BOLT MOUNTING SYSTEM

The Solstice Solo uses a single-bolt mounting system with an adjustable aiming system allowing for precision aiming in hard to



#### **ENDLESS CONFIGURATIONS**

With the Omni-Link Connector, simply connect Solstice Solo Pods together to create unique lengths and configurations, as well as add numerous accessories for various applications.

**FLUSH MOUNT** 3" Flush Mount Adapter



**HANDLE** 

HANDLE BAR CLAMP 0.75"- 1.25" Mounting



See page 80 for complete accessory details.

# **SOLO PRIME POD**




#### **ULTIMATE 10-WATT LED POD FOR UNIVERSAL APPLICATIONS**

Omni-Link Interlocking System | Electronic Thermal Management | Flush Mount Bracket Available

<b>BEAM PATTERNS</b> 10°, 20°, 40°	<b>WEIGHT</b> 0.70 lb / 0.32 kg	<b>DIMENSIONS</b> 2.17" x 3.35" x 2.36"
RAW LUMENS	DISTANCE TO 1 LUX	METRIC





<sup>\*</sup>Additional Part Numbers & Technical Information On Page 42



# **SOLSTICE SOLO**



ITEM #: XIL-S1110 Shown PART #: 9888156

#### **COMPACT 10-WATT LED FOR UNIVERSAL APPLICATIONS**

Omni-Link Interlocking System | Small 2" Die-Cast Housing | Flush Mount Bracket Available

<b>BEAM PATTERNS</b> 10°, 30°, 60°, 30°x65°	<b>WEIGHT</b> 0.76 lb / 0.34 kg	<b>DIMENSIONS</b> 2.05" x 3.24" x 2.44"
<b>RAW LUMENS</b>	DISTANCE TO 1 LUX	<b>METRIC</b>
1,052 lm (ea)	255'	52mm x 82mm x 62mm



















XIL-S1110 9888156 10° 30° XIL-S1130 9888163 XIL-S1160 9888170 60°


# MINI SOLO POD



ITEM #: XIL-MX110 Shown PART #: 9113531

#### COMPACT 5-WATT LED PERFECT FOR TIGHT SPOTS

Omni-Link Interlocking System | Ultra Compact Housing | Mounting Accessories



ITEM#	PART #	BEAM
XIL-MX110	9113531	10°
XIL-MX140	9113715	40°
XIL-MX160	9113807	60°

<sup>\*</sup>Additional Part Numbers & Technical Information On Page 42








<sup>\*</sup>Additional Part Numbers & Technical Information On Page 42


# LED LIGHT CANNON

ITEM#	PART#	QTY	BEAM	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
CTL-CPZ110 CTL-CPZ110KIT	9150970 9151069	1 2	10°	2.02 lb 4.04 lb	2,500 lm 5,000 lm	1,750 lm 3,500 lm	9-32V	25	2.08A 4.17A
CTL-CPZ110XP CTL-CPZ110XPKIT	9893259 9893365	1 2	10°	2.02 lb 4.04 lb	3,000 lm 6,000 lm	2,100 lm 4,200 lm	9-32V	40	3.33A 6.66A
CTL-CPZ610 CTL-CPZ610KIT	9888538 9888545	1 2	10°	5.51 lb 11.02 lb	3,200 lm 6,400 lm	2,240 lm 4,480 lm	9-32V	50	4.17A 8.34A
CTL-CPZ620 CTL-CPZ620KIT	9891736 9891743	1 2	20°	5.51 lb 11.02 lb	3,200 lm 6,400 lm	2,240 lm 4,480 lm	9-32V	50	4.17A 8.34A
CTL-CPZ810 CTL-CPZ810KIT	9890852 9890074	1 2	10°	10.36 lb 20.72 lb	5,800 lm 11,600 lm	4,060 lm 8,120 lm	9-32V	90	7.5A 15A











# TRANSPORTER


ITEM#	PART#	# OF LEDS	BEAM	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
CTL-TPX910	9110110	9	10°	5.95 lb	4,752 lm	3,330 lm	9-32V	45	3.75A
CTL-TPX940	9110295	9	40°	5.95 lb	4,752 lm	3,330 lm	9-32V	45	3.75A
CTL-TPX1210	9110561	12	10°	6.17 lb	6,336 lm	4,440 lm	9-32V	60	5A
CTL-TPX1240	9110745	12	40°	6.17 lb	6,336 lm	4,440 lm	9-32V	60	5A
CTL-TPX1810	9111018	18	10°	6.61 lb	9,504 lm	6,660 lm	9-32V	90	7.5A
CTL-TPX1840	9111193	18	40°	6.61 lb	9,504 lm	6,660 lm	9-32V	90	7.5A







# OPTIMUS

ITEM#	PART#	QTY	HOUSING	BEAM	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
XIL-OPH115 XIL-OPH115KIT	9891699 9891705	1 2	Black	10°	1.37 lb 2.74 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OPRH115 XIL-OPRH115KIT	9891712 9891729	1 2	Black	10°	1.53 lb 3.06 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OP110 XIL-OP110KIT	9123882 9124421	1 2	Black	20°	1.37 lb 2.74 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OP120 XIL-OP120KIT	9130002 9138015	1 2	Black	10°	1.37 lb 2.74 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OP160 XIL-OP160KIT	9124063 9137926	1 2	Black	10°	1.37 lb 2.74 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OP110W XIL-OP110C	9124513 9124247	1 1	White Chrome	10°	1.37 lb 2.74 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OP120W XIL-OP120C	9139005 9139098	1	White Chrome	20°	1.37 lb 2.74 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OP160W XIL-OP160C	9139364 9139272	1	White Chrome	60°	1.37 lb 2.74 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OPR110 XIL-OPR110KIT	9140896 9141251	1 2	Black	10°	1.53 lb 3.06 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OPR120 XIL-OPR120KIT	9141077 9141343	1 2	Black	10°	1.53 lb 3.06 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OPR160 XIL-OPR160KIT	9141169 9141435	1 2	Black	10°	1.53 lb 3.06 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OPR110W XIL-OPR110C	9149172 9149080	1	White Chrome	10°	1.53 lb 3.06 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OPR120W XIL-OPR120C	9149356 9149264	1	White Chrome	20°	1.53 lb 3.06 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OPR160W XIL-OPR160C	9149530 9149448	1	White Chrome	60°	1.53 lb 3.06 lb	1,052 lm 2,104 lm	736 lm 1,473 lm	9-32V	10	0.83A 1.67A
XIL-OP210 XIL-OP210KIT	9124605 9125053	1 2	Black	10°	2.25 lb 4.5 lb	2,104 lm 4,208 lm	1,473 lm 2,946 lm	9-32V	20	1.67A 3.3A
XIL-OP220 XIL-OP220KIT	9139548 9137834	1 2	Black	20°	2.25 lb 4.5 lb	2,104 lm 4,208 lm	1,473 lm 2,946 lm	9-32V	20	1.67A 3.3A
XIL-OP260 XIL-OP260KIT	9136660 9137742	1 2	Black	60°	2.25 lb 4.5 lb	2,104 lm 4,208 lm	1,473 lm 2,946 lm	9-32V	20	1.67A 3.3A
XIL-OP210W XIL-OP210C	9124964 9124698	1	White Chrome	10°	2.25 lb 4.5 lb	2,104 lm 4,208 lm	1,473 lm 2,946 lm	9-32V	20	1.67A 3.3A
XIL-OP220W XIL-OP220C	9139630 9166636	1	White Chrome	20°	2.25 lb 4.5 lb	2,104 lm 4,208 lm	1,473 lm 2,946 lm	9-32V	20	1.67A 3.3A
XIL-OP260W XIL-OP260C	9139722 9159348	1 1	White Chrome	60°	2.25 lb 4.5 lb	2,104 lm 4,208 lm	1,473 lm 2,946 lm	9-32V	20	1.67A 3.3A












# SOLO PRIME

ITEM#	PART#	HOUSING	BEAM	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
XIL-SP110	4008830	Black	10°	0.70 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-SP110W	4008847	White	10°	0.70 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-SP120	4009882	Black	20°	0.70 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-SP120W	4008854	White	20°	0.70 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-SP140	4009899	Black	40°	0.70 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-SP140W	4008861	White	40°	0.70 lb	1,052 lm	736 lm	9-32V	10	0.83A










# SOLSTICE SOLO

ITEM#	PART#	HOUSING	BEAM	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
XIL-S1110	9888156	Black	10°	0.76 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-S1110W	9888194	White	10°	0.76 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-S1130	9888163	Black	30°	0.76 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-S1130W	9888200	White	30°	0.76 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-S1160	9888170	Black	60°	0.76 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-S1160W	9888217	White	60°	0.76 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-S11e3065	9888187	Black	30°x65°	0.76 lb	1,052 lm	736 lm	9-32V	10	0.83A
XIL-S11e3065W	9888224	White	30°x65°	0.76 lb	1,052 lm	736 lm	9-32V	10	0.83A









# MINI SOLO

ITEM#	PART#	HOUSING	BEAM	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
XIL-MX110	9113531	Black	10°	0.40 lb	528 lm	368 lm	9-32V	5	0.42A
XIL-MX140	9113715	Black	40°	0.40 lb	528 lm	368 lm	9-32V	5	0.42A
XIL-MX160	9113807	Black	60°	0.40 lb	528 lm	368 lm	9-32V	5	0.42A











# **XMITTER PRIME XTREME**















BEAM PATTERNS	WARRANTY
10°, 40°, Mixed	Extended
<b>HEIGHT</b> 3.75" / 95mm	<b>WIDTH</b> 3.31" / 84mm

#### **BRIGHTEST LIGHT BAR ON THE MARKET**

- Full Range Fills In Road Way
- Plug And Play Harness Included
- PWM Integrated Dimming Circuitry
   90% Efficiency Next Generation LED
- Electronic Thermal Management & Dimming

#### **END CAP MOUNTS**



ITEM #: XIL-PECM Shown PART #: 9889191







VAILABLE IN AMBER



















ITEM#	PART #	BEAM
XIL-PX640	9117492	40° Flood
XIL-PX1240	9115696	40° Flood
XIL-PX1840	9115870	40° Flood
XIL-PX3040	9116952	40° Flood
XIL-PX3640	9117133	40° Flood
XIL-PX5440	9117317	40° Flood
XIL-PX7240	9117676	40° Flood
XIL-PX9040	9887043	40° Flood

ITEM#	PART#	BEAM
XIL-PX6M	9894850	Mixed
XIL-PX12M	9894751	Mixed
XIL-PX18M	9887890	Mixed
XIL-PX30M	9123431	Mixed
XIL-PX36M	9894836	Mixed
XIL-PX54M	9153223	Mixed
XIL-PX72M	9153490	Mixed
XIL-PX90M	9132792	Mixed

30" 54 LED 28,512 lm

72 LED 38.016 lm

50" 90 LED 47,520 lm

\*Additional Part Numbers & Technical Information On Page 52

# XPR-S





**BEAM PATTERNS** 

Straight (6.5°)

HEIGHT









WARRANTY

Extended

WIDTH







#### **UPGRADED FOR UNSURPASSED DISTANCE**

- Halo Models Available
- Dual Mounting Standard

- Plug And Play Harness Included
   40-95% More Distance than XPR Series
   Upgraded IRIS Reflector Technology With 10 Watt LED


#### 3.75" / 95mm 3.19" / 81mm




ITEM #: XPI-EM Shown PART #: 9892917

**END CAP MOUNTS** 









ITEM#	PART #	LENGTH	BEAM
XPR-3S	9897462	6.14" / 156 mm	Straight
XPR-6S	9897479	11.46"/291mm	Straight
XPR-9S	9897455	18.80"/476mm	Straight
XPR-12S	9897394	24.06"/611mm	Straight
XPR-15S	9897400	29.37"/746mm	Straight
XPR-18S	9897417	34.69"/881mm	Straight
XPR-21S	9897424	40.00"/1,016mm	Straight
XPR-27S	9897448	50.63"/1,286mm	Straight

\*Additional Part Numbers & Technical Information On Page 51



#### **DUAL MOUNTING INCLUDED**

Each XPR comes packaged with dual side-wing mounts as well as patented feet mounts. Amount of feet mounts vary by length of the light bar.

# XPR





**BEAM PATTERNS** 

Straight, Tilted











WARRANTY

Extended



#### IRIS REFLECTORS FOR ULTIMATE DISTANCE

- Dual Mounting Standard
- 5-Watt XPI Light Bar Available


- Plug And Play Harness Included
   IRIS Reflector Technology With 10 Watt LED
   New Lifespan-Boosting Heat Sink Technology


#### **HEIGHT WIDTH** 3.75" / 95mm 3.19" / 81mm

#### **END CAP MOUNTS**



ITEM #: XPI-EM Shown PART #: 9892917









ITEM#	PART #	LENGTH	BEAM
XPR-3	9891606	6.05" / 153.7mm	Straight
XPR-6	9891613	11.46"/291mm	Straight
XPR-9M	9891620	18.80"/476mm	Tilted
XPR-12M	9891637	24.06"/611mm	Tilted
XPR-15M	9891644	29.37"/746mm	Tilted
XPR-18M	9891651	34.69"/881mm	Tilted
XPR-21M	9891668	40.00"/1,016mm	Tilted
XPR-27M	9891682	50.63"/1,286mm	Tilted

\*Additional Part Numbers & Technical Information On Page 51

#### ING MOUNTS INCLUDED



#### **DUAL MOUNTING INCLUDED**

Each XPR comes packaged with dual side-wing mounts as well as patented feet mounts. Amount of feet mounts vary by length of the light bar.

# XMITTER LOW PRO XTREME













BEAM PATTERNS	WARRANTY
10°, 40°, Mixed	Extended
<b>HEIGHT</b> 2.06" / 52mm	<b>WIDTH</b> 2.45" 62mm


#### XTREME OUTPUT IN A COMPACT LIGHT BAR

- Sleek Low Profile Design
   90% Efficiency Next Gen LED
   Plug And Play Harness Included
   PMW Integrated Dimming Circuitry
   Electronic Thermal Management & Dimming

#### **END CAP MOUNTS**



ITEM #: XIL-LPECM Shown PART #: 9888811

























RT# BEAM

10° Spot

10° Spot

10° Spot 10° Spot

10° Spot

10° Spot

10° Spot

10° Spot

LENGTH	ITEM#	PART#
4.65" / 118mm	XIL-LPX310	4000759
8.43" / 214mm	XIL-LPX610	9118758
12.21" / 310mm	XIL-LPX910	4000773
19.77" / 502mm	XIL-LPX1510	9114613
31.11" / 790mm	XIL-LPX2410	9121901
34.89" / 886mm	XIL-LPX2710	9114972
42.44" / 1,078mm	XIL-LPX3310	9115153
50.00" / 1,270mm	XIL-LPX3910	9128115

ITEM#	PART #	BEAM
XIL-LPX340	4000766	40° Flood
XIL-LPX640	9120737	40° Flood
XIL-LPX940	4000780	40° Flood
XIL-LPX1540	9114705	40° Flood
XIL-LPX2440	9132884	40° Flood
XIL-LPX2740	9115061	40° Flood
XIL-LPX3340	9115245	40° Flood
XIL-LPX3940	9132976	40° Flood
*Δ	dditional Part Nu	mhere & Techn

PART#	BEAM
9153407	Mixed
9897042	Mixed
9889351	Mixed
9892252	Mixed
	9153407 9897042 9889351

# **XMITTER**















BEAM PATTERNS	WARRANTY
Euro, Flood	Extended
<b>HEIGHT</b> 2.76" / 69mm	<b>WIDTH</b> 3.00" / 76mm

#### ORIGINAL LIGHT BAR WITH SEAMLESS BEAM

- Seamless Beam Pattern
- Plug and Play Harness Included
- Weatherproof Deutsch Connector
- Used by NASA, Border Patrol, and Pro Racers
- Infrared, Amber, Red Blue, and Green Available

#### **END CAP MOUNTS**



ITEM #: XIL-ECM Shown PART #: 9888781



XIL-1000


50











51.80" / 1,316mm

Euro

4006355

ITEM#	PART#	LENGTH	BEAM
XIL-41	4007529	4.00" / 101.6mm	Flood
XIL-81	4007581	5.80" / 147.6mm	Flood
XIL-121	4007369	7.80" / 198.4mm	Flood
XIL-201	4007468	11.80" / 300mm	Flood
XIL-321	4007482	17.60" / 446mm	Flood
XIL-401	4007505	21.70" / 550mm	Flood
XIL-601	4007543	31.80" / 808mm	Flood
XIL-801	4007567	41.80" / 1,062mm	Flood
XIL-1001	4007345	51.80" / 1.316mm	Flood

<sup>\*</sup>Additional Part Numbers & Technical Information On Page 53

# **CHASER BARS**









BEAM PATTERNS	WARRANTY
60°	Extended
<b>HEIGHT</b> 2.06" / 52mm	<b>WIDTH</b> 2.45" / 62mm

# **END CAP MOUNTS**



ITEM #: XIL-LPECM Shown PART #: 9888811

#### LOW PROFILE REAR LED CHASER BAR SYSTEM

- Sleek Low Profile Design
- High Output Color LEDs
   Racer Models Include Blue LEDs
- Running and Brake Lights in Single Bar
   Red, Amber, and White LEDs in Single Housing

MED AMBER WHITE AMBER MED /







34.89" / 886mm

9897226


Race

ITEM#	PART#	LENGTH	USE
XIL-CBSR21	9897196	27.33" / 694mm	Recreation
XIL-CBSR27	9897202	34.89" / 886mm	Recreation

# **XPR-S TECHNICAL DATA**


ITEM#	PART#	LEDS	BEAM	LENGTH	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
XPR-3S	9897462	3	Straight	6.14"/156mm	1.80lb/0.82kg	3,237 lm	2,266 lm	11-32V	30	2.5A
XPR-6S	9897479	6	Straight	11.46"/291mm	3.40lb/1.54kg	6,474 lm	4,531 lm	11-32V	60	5A
XPR-9S	9897455	9	Straight	18.80"/476mm	5.10lb/2.31kg	9,711 lm	6,798 lm	11-32V	60	5A
XPR-12S	9897394	12	Straight	24.06"/611mm	6.90lb/3.13kg	12,948 lm	9,064 lm	11-32V	90	10A
XPR-15S	9897400	15	Straight	29.37"/746mm	8.70lb/3.95kg	16,185 lm	11,330 lm	11-32V	150	12.5A
XPR-18S	9897417	18	Straight	34.69"/881mm	9.80lb/4.45kg	19,422 lm	13,595 lm	11-32V	180	15A
XPR-21S	9897424	21	Straight	40.00"/1,016mm	11.60lb/5.26kg	22,659 lm	15,861 lm	11-32V	210	17.5A
XPR-27S	9897448	27	Straight	50.63"/1,286mm	15.22lb/6.90kg	29,133 lm	20,393 lm	11-32V	270	22.5A


XIL-CBSX27



# XMITTER PRIME XTREME


ITEM#	PART#	LEDS	BEAM	LENGTH	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP
XIL-PX610 XIL-PX640 XIL-PX6M	9117409 9117492 9894850	6	10° 40° Mixed	4.70"/120mm	2.65lb/1.2kg	3,168 lm	2,220 lm	9-32V	30	2.5A
XIL-PX1210 XIL-PX1240 XIL-PX12M	9115603 9115696 9894751	12	10° 40° Mixed	7.90"/201mm	5.29lb/2.4kg	6,336 lm	4,440 lm	9-32V	60	5A
XIL-PX1810 XIL-PX1840 XIL-PX18M	9115788 9115870 9887890	18	10° 40° Mixed	11.10"/282mm	6.61lb/3.0kg	9,504 lm	6,660 lm	9-32V	90	7.5A
XIL-PX3010 XIL-PX3040 XIL-PX30M	9116860 9116952 9123431	30	10° 40° Mixed	17.50"/444mm	9.25lb/4.5kg	15,840 lm	11,100 lm	9-32V	150	12.5A
XIL-PX3610 XIL-PX3640 XIL-PX36M	9117041 9117133 9894836	36	10° 40° Mixed	20.60"/525mm	10.58lb/4.8kg	19,008 lm	13,320 lm	9-32V	180	15A
XIL-PX5410 XIL-PX5440 XIL-PX54M	9117225 9117317 9153223	54	10° 40° Mixed	30.20"/768mm	14.55lb/6.6kg	28,512 lm	19,980 lm	9-32V	270	22.5A
XIL-PX7210 XIL-PX7240 XIL-PX72M	9117584 9117676 9153490	72	10° 40° Mixed	39.80"/1,011mm	18.51lb/8.4kg	38,016 lm	26,640 lm	9-32V	360	30A
XIL-PX9010 XIL-PX9040 XIL-PX90M	9887036 9887043 9132792	90	10° 40° Mixed	49.37"/1,254mm	22.49lb/10.2kg	47,520 lm	33,300 lm	9-32V	450	37.5A






# XPR


ITEM#	PART#	LEDS	BEAM	LENGTH	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
XPR-3	9891606	3	Straight	6.14"/156mm	1.80lb/0.82kg	3,237 lm	2,266 lm	11-32V	30	2.5A
XPR-6	9891613	6	Straight	11.46"/291mm	3.40lb/1.54kg	6,474 lm	4,531 lm	11-32V	60	5A
XPR-9M	9891620	9	Tilted	18.80"/476mm	5.10lb/2.31kg	9,711 lm	6,798 lm	11-32V	60	5A
XPR-12M	9891637	12	Tilted	24.06"/611mm	6.90lb/3.13kg	12,948 lm	9,064 lm	11-32V	90	7.5A
XPR-15M	9891644	15	Tilted	29.37"/746mm	8.70lb/3.95kg	16,185 lm	11,330 lm	11-32V	150	12.5A
XPR-18M	9891651	18	Tilted	34.69"/881mm	9.80lb/4.45kg	19,422 lm	13,595 lm	11-32V	180	15A
XPR-21M	9891668	21	Tilted	40.00"/1,016mm	11.60lb/5.26kg	22,659 lm	15,861 lm	11-32V	210	17.5A
XPR-27M	9891682	27	Tilted	50.63"/1,286mm	15.22lb/6.90kg	29,133 lm	20,393 lm	11-32V	270	22.5A



# XMITTER LOW PROFILE XTREME


ITEM#	PART#	LEDS	BEAM	LENGTH	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
XIL-LPX310 XIL-LPX340	4000759 4000766	3	10° 40°	4.65"/118mm	1.21lb/0.5kg	1,584 lm	1,110 lm	9-32V	15	1.25A
XIL-LPX610 XIL-LPX640 XIL-LPX6M	9118758 9120737 9153407	6	10° 40° Mixed	8.43"/214mm	2.00lb/0.9kg	3,168 lm	2,220 lm	9-32V	30	2.5A
XIL-LPX910 XIL-LPX940	4000773 4000780	9	10° 40°	12.21"/310mm	2.84lb/1.3kg	4,752 lm	3,330 lm	9-32V	45	3.75A
XIL-LPX1510 XIL-LPX1540 XIL-LPX15M	9114613 9114705 9897042	15	10° 40° Mixed	19.77"/502mm	4.45lb/2.0kg	7,920 lm	5,550 lm	9-32V	75	6.25A
XIL-LPX2410 XIL-LPX2440 XIL-LPX24M	9121901 9132884 9889351	24	10° 40° Mixed	31.11"/790mm	6.05lb/2.7kg	12,672 lm	8,880 lm	9-32V	120	10A
XIL-LPX2710 XIL-LPX2740	9114972 9115061	27	10° 40°	34.89"/886mm	7.67lb/3.5kg	14,256 lm	9,990 lm	9-32V	135	11.25A
XIL-LPX3310 XIL-LPX3340	9115153 9115245	33	10° 40°	42.44"/1,078mm	9.26lb/4.2kg	17,424 lm	12,210 lm	9-32V	165	13.75A
XIL-LPX3910 XIL-LPX3940 XIL-LPX39M	9128115 9132976 9892252	39	10° 40° Mixed	50.00"/1,270mm	10.9lb/4.9kg	20,592 lm	14,430 lm	9-32V	195	16.25A






# **XMITTER**

ITEM#	PART#	LEDS	BEAM	LENGTH	WEIGHT	RAW LUMENS	EFFECTIVE LUMENS	INPUT VOLTS	WATTS	AMP DRAW
XIL-40 XIL-41	4006270 4007529	4	Euro Flood	4.00"/101.6mm	1.26lb/0.57kg	720 lm	396 lm	9-42V	12	1.25A
XIL-80 XIL-81	4006287 4007581	8	Euro Flood	5.80"/147.6mm	2.09lb/0.95kg	1,440 lm	792 lm	9-42V	24	2.5A
XIL-120 XIL-121	4006294 4007369	12	Euro Flood	7.80"/198.4mm	2.65lb/1.2kg	2,160 lm	1,188 lm	9-42V	36	3.75A
XIL-200 XIL-201	4006300 4007468	20	Euro Flood	11.80"/300mm	3.64lb/1.65kg	3,600 lm	1,980 lm	9-42V	60	6.25A
XIL-320 XIL-321	4006317 4007482	32	Euro Flood	17.60"/446mm	5.51lb/2.5kg	5,760 lm	3,168 lm	9-42V	96	10A
XIL-400 XIL-401	4006324 4007505	40	Euro Flood	21.70"/550mm	6.61lb/3.0kg	7,200 lm	3,960 lm	9-42V	120	11.25A
XIL-600 XIL-601	4006331 4007543	60	Euro Flood	31.80"/808mm	9.59lb/4.35kg	10,800 lm	5,940 lm	9-42V	180	13.75A
XIL-800 XIL-801	4006348 4007567	80	Euro Flood	41.80"/1,062mm	12.46lb/5.65kg	14,400 lm	7,920 lm	9-42V	240	16.25A
XIL-1000 XIL-1001	4006355 4007345	100	Euro Flood	51.80"/1,316mm	14.55lb/6.60kg	18,000 lm	9,900 lm	9-42V	300	16.25A





# NEXTLEVEL STYLE+OUTPUT+RELIABILITY



# **LED**HEADLIGHTS

Take your desire for high powered LEDs to the streets with the DOT Approved Vortex LED Headlight. The Vortex boasts halo, low, and high beam modes and a robust aluminum polycarbonate hybrid housing. E-Mark and ADR approved models also available.







BLACK CHROME

E-MARK & ADR MODELS AVAILABLE

#### AUTOMOTIVE/OFFROAD

# **VORTEX LED HEADLIGHTS**

#### ABOUT THE VORTEX

The DOT Approved Vortex LED Headlight leads the LED Headlight industry in both style and performance. With an integrated LED Halo Ring, the Vortex is sure to turn heads while also delivering a dramatically improved night driving experience over factory headlights. The Vortex is currently available in 7" Round and 5.75" Round with more models on the way, each available with a Polished Chrome finish or a Black Chrome finish.

ADR and E-MARK Approved models are available for those who live in Australia and Europe. We spent the time to get the certification and pass all regulations so that you can enjoy your Vortex LED Headlight regardless of

Multiple direct plug-and-play accessories are available that help give you the most out of your Vortex LED Headlight.

#### 7" E-MARK APPROVED MODELS



#### XIL-7RELKIT

Special models for Left-hand and Right-hand driving regulations are available with E-Mark Approval in the 7" Round housing..



#### **MULTIPLE LEDS FILL IN ROADWAY**

Vision X integrated two LEDs with flood optics into the sides of the fixture in order to provide ample peripheral lighting by filling in the sides of the roadway in between the vehicle and the low beam.







#### HALO / LOW / HIGH

The Vortex has three beam modes that each serve a different purpose. The Halo works as a daytime running light while the Low and High beams handle the job of providing you with light output.



# **ACCESSORIES**



PART #: 9895475 For Offroad Vehicles Only



PART #: 9892757

#### IMPROVE PERFORMANCE

For those looking to take their Vortex LED Headlight to the next level we recommend the following accessories.

ITEM#	PART#	PURPOSE	QTY
P-HLHI4	9895475	Engages all three beam modes simultaneously to dramatically increase visibility and light output	1
P-HLCBA	9892757	Levels electrical current to remove electrical interference from vehicle and eliminate flickering in the light	1

# 7" ROUND LED HEADLIGHT



ITEM #: XIL-7RD Shown PART #: 9891217

Replaces OEM Part # H6017/H6024


# DOT APPROVED LED HEADLIGHT WITH BRIGHT LED HALO RING

Multiple LEDs Fill In Roadway | Polycarbonate Lens | E-Mark & ADR Models Available

BEAM MODES Halo, Low, High	<b>WEIGHT</b> 2.20 lb / 1.00 kg	<b>DIMENSIONS</b> 6.96" x 6.96" x 3.86"
<b>RAW LUMENS</b>	REFLECTOR FINISH	<b>METRIC</b>
4,210 lm (ea)	Polished Chrome, Black Chrome	177mm x 177mm x 98mm



9892443



# 5.75" ROUND LED HEADLIGHT

XIL-7RDBKIT

ITEM #: XIL-575RD Shown


Replaces OEM Part # H5001/H5006


#### Multiple LEDs Fill In Roadway | Polycarbonate Lens | Perfect For Classic Cars **BEAM MODES WEIGHT** 1.95 lb / 0.88 kg Halo, Low, High

DOT APPROVED LED HEADLIGHT WITH BRIGHT LED HALO RING

Black Chrome







**DIMENSIONS** 

5.65" x 5.65" x 2.88"

METRIC

144mm x 144mm x 73mm

# **4X6" LED HEADLIGHT**

ITEM #: XIL-46D Shown PART #: 9897806

Replaces OEM Part # H4656/H4651

#### DOT APPROVED LED HEADLIGHT WITH BRIGHT LED HALO RING

Multiple LEDs Fill In Roadway | Dual All In One High and Low Beam | Perfect For Truck and Transport





ITEM#

XIL-46D

XIL-46DKIT

XIL-46DBKIT

XIL-46DB

E



PART #

9897806

9897820

9897813

9897837









Polished Chrome

Polished Chrome

Black Chrome

Black Chrome





2

2







# JEEP JK SPECIFIC KIT




ITEM #: XIL-7RDKITJK Shown PART #: 9892733

Replaces OEM Part # H6017/H6024

#### DIRECT REPLACEMENT LED HEADLIGHT KIT FOR JEEP JK

Works with Canbus | Simple Installation | Multiple LEDs Fill In Roadway

<b>BEAM MODES</b> Halo, Low, High	<b>WEIGHT</b> 4.40 lb / 2.00 kg	<b>DIMENSIONS</b> 6.96" x 6.96" x 3.86"
RAW LUMENS 8,420 lm (kit)	REFLECTOR FINISH Polished Chrome, Black Chrome	<b>METRIC</b> 177mm x 177mm x 98mm



Replaces Chrysler OEM Part # 55078148AB, 55078149AB, 55078148AC, 55078149AC

View Our Website For Complete Application Chart

# **XMC 7" ROUND LED HEADLIGHT**



ITEM #: XMC-7RD Shown PART #: 9892061

#### DOT APPROVED LED HEADLIGHT WITH BRIGHT LED HALO RING

Multiple LEDs Fill In Roadway | Polycarbonate Lens | Dramatically Improves Safety

BEAM MODES Halo, Low, High	<b>WEIGHT</b> 2.20 lb / 1.00 kg	<b>DIMENSIONS</b> 6.96" x 6.96" x 3.86"
RAW LUMENS	REFLECTOR FINISH	<b>METRIC</b>
4,210 lm (ea)	Polished Chrome, Black Chrome	177mm x 177mm x 98mm



XMC-7RD XMC-7RDB 9895291 Black Chrome

Replaces OEM Part # 68342-05A, 67700032, 67700243

View Our Website For Complete Application Chart



# XMC 5.75" ROUND LED HEADLIGHT




ITEM #: XMC-575RD Shown PART #: 9895628

#### DOT APPROVED LED HEADLIGHT WITH BRIGHT LED HALO RING

Multiple LEDs Fill In Roadway | Polycarbonate Lens | Dramatically Improves Safety





Replaces OEM Part # 68297-05A, 67700144A View Our Website For Complete Application Chart




# XMC 5.75" OVAL ROAD GLIDE

#### 2004-2013 HARLEY-DAVIDSON ROAD GLIDE DIRECT REPLACEMENT Multiple LEDs Fill In Roadway | Polycarbonate Lens | Dramatically Improves Safety



ITEM #: XMC-5750DKIT Shown PART #: 9895673

<b>BEAM MODES</b> Halo, Low, High	<b>WEIGHT</b> 2.20 lb / 1.00 kg	<b>DIMENSIONS</b> 6.52" x 5.96" x 4.29"
RAW LUMENS	REFLECTOR FINISH	<b>METRIC</b>
8,420 lm (kit)	Polished Chrome, Black Chrome	165mm x 151mm x 109mm



XMC-575ODBKIT 9895697 Kit Black Chrome

Replaces OEM Part # 67700109, 67775-01C

View Our Website For Complete Application Chart

# **XMC PASSING LAMP**



ITEM #: XMC-45RDKIT Shown PART #: 9897844


## FIVE TIME BRIGHTER THAN HALOGEN PASSING LAMPS


Multisurface Reflector | Polycarbonate Lens | Dramatically Improves Safety





ITEM#	PART#	FINISH	QTY
XMC-45RDKIT	9897844	Polished Chrome	1
XMC-45RDBKIT	9897851	Black Chrome	1





# **VEHICLE** SPECIFIC KITS

Vision X offers vehicle specific lighting application and mounting options for most truck makes and models, allowing for effortless installation with our direct replacement fitting.



# JEEP KITS

#### ABOUT JEEP JK KITS

Adding custom lighting takes any Jeep to the next level. Vision X makes easy to install custom kits for Jeep JK vehicles. All kits feature no-drilling installation, and are easily installed in a matter of minutes.



# **VORTEX 7" LED HEADLIGHT**

Check out the Vortex 7" LED Headlight featuring an intense halo ring on page 56 and 58. This powerful headlight is the perfect addition to any Jeep. Exclusive Jeep JK LED headlight kit includes 2 canbus adapters to eliminate electrical interference between vehicle and light.



#### AVAILABLE JEEP LED KITS



- Factory Fog Light Upgrade Kit 883' Of Usable Light per Light 7x Brighter Than Factory
- Direct Replacement

ITEM #: XIL-OE1012JKV2OPR Shown PART #: 9154756



# Windshield Mount for Light Bars Mount 50" LED Light Bars Easy Installation No Drilling

ITEM #: XIL-OEW0713JKV2 Shown PART #: 9888422



# **Hood Mount for Light Bars**

- Maintains Factory Appearance For Up To 20" LED Light Bar Adds Up To 19,008 Lumens

ITEM #: XIL-OEH0713JKPX36 Shown PART #: 9891002



VORTEX HEADLIGHT UPGRADE
DOT Approved Lighting Fixture | Bright LED Halo Ring | Multiple LEDs Fill In Roadway

ITEM#	PART#	REPLACES	KIT INCLUDES	REFERENCE
XIL-7RDKITJK	9892733	7" ROUND HEADLIGHT	Chrome LED Headlights (2), Canbus Adapter (2)	PAGE 58
XIL-7RDBKITJK	9892825	7" ROUND HEADLIGHTS	Black Chrome LED Headlights (2), Canbus Adapter (2)	PAGE 58

#### **DIRECT REPLACEMENT LED UPGRADES**

No Drilling Necessary | Direct Plug-And-Play With Factory Wiring | Dramatically Increase Visibility

ITEM#	PART#	APPLICATION	YEAR FITS	KIT INCLUDES	REFERENCE
XIL-OE0709JKV2	9145662	LED FOG LIGHTS	07-09 JEEP JK	Brackets, Connectors	-
XIL-OE1012JKV2	9154664	LED FOG LIGHTS	10-17 JEEP JK	Brackets, Connectors	-
XIL-OE0709JKV2OPR	9145754	LED FOG LIGHTS	07-09 JEEP JK	Brackets, (2) XIL-OPR110, Connectors	PAGE 37
XIL-OE1012JKV2OPR	9154756	LED FOG LIGHTS	10-17 JEEP JK	Brackets, (2) XIL-OPR110, Connectors	PAGE 37
XIL-OE13JKX	9891064	LED FOG LIGHTS	13-17 JEEP JK-X	Brackets, Connectors	-
XIL-OEW0713JKV2	9888422	WINDSHIELD MOUNT	07-17 JEEP JK	Brackets	-
XIL-OEH0713PX36	9891002	HOOD LIGHT BAR	07-17 JEEP JK	Brackets, (1) XIL-PX3610, Harness	PAGE 46
XIL-OEH0713JKXPI12	9891019	HOOD LIGHT BAR	07-17 JEEP JK	Brackets, (1) XPI-12M	PAGE 48
XIL-OEA0713JK	9888392	A-PILLAR FOG LIGHT	07-17 JEEP JK	Brackets	-
XIL-OEA0713JKOP1	9888408	A-PILLAR FOG LIGHT	07-17 JEEP JK	Brackets, (2) XIL-OP110, Harness	PAGE 37
XIL-OEA0713JKCPZ1	9888415	A-PILLAR FOG LIGHT	07-17 JEEP JK	Brackets, (2) CTL-CPZ110, Harness	PAGE 33
XIL-OEA9706TJCPZ1	9892795	A-PILLAR FOG LIGHT	97-06 JEEP TJ	Brackets, (2) CTL-CPZ110, Harness	PAGE 33
XIL-OEA9706TJOPH	9892818	A-PILLAR FOG LIGHT	97-06 JEEP TJ	Brackets, (2) XIL-OPH115, Harness	PAGE 36



A-Pillar Light Mount

- Perfect For Cannon Or Optimus
- Long Range Projection
- No Drilling Required

ITEM #: XIL-OEA0713JKCPZ1 Shown PART #: 9888415

# FORD RAPTOR KITS









Factory Fog Light Upgrade Kit ITEM #: XIL-OE10FROP Shown PART #: 9133515

**Bumper Mount for Light Bars** ITEM #: XIL-OEB10FRPX3610 Shown PART #: 9887357

FACTORY FOG LIGHT UPGRADE KIT
Lights, Mounts, Wiring | 7x Brighter Than Headlight | Direct Fit In Factory Opening

Lighter, Mounter, Whiting   17 Brighter Thair Floating Photol R III Floating					
ITEM#	PART#	FITS	KIT INCLUDES	REFERENCE	
XIL-OE10FR	9160870	10-14 FORD RAPTOR	BRACKET, FACTORY INTEGRATION HARNESS	-	
XIL-OE10FROP	9133515	10-14 FORD RAPTOR	BRACKETS, (4) XIL-OP110, INTEGRATED HARNESS	PAGE 37	
XIL-OE10FROPH	9892450	10-14 FORD RAPTOR	BRACKETS, (4) XIL-OPH115, INTEGRATED HARNESS	PAGE 37	

#### **BUMPER MOUNT FOR LIGHT BARS**

Lights, Mounts, Wiring | Fits Directly into Factory Bumper | Add Up to 19,008 Lumens

J , J		7 1 1 -1 -7-		
ITEM#	PART#	FITS	KIT INCLUDES	REFERENCE
XIL-OEB10FR	9887340	10-14 FORD RAPTOR	BRACKETS, FACTORY INTEGRATION HARNESS	-
XIL-OEB10FRPX3610	9887357	10-14 FORD RAPTOR	BRACKETS, (1) XIL-PX3610, INTEGRATED HARNESS	PAGE 46

# **FORD F SERIES KITS**







Factory Fog Light Upgrade Kit ITEM #: XIL-0E9913FSDDURA Shown PART #: 9891200

**Bumper Mount for Light Bars** ITEM #: XIL-OEB09F150PX36 Shown PART #: 9891156

#### **FACTORY FOG LIGHT UPGRADE KIT**

Drastically Increase Light Output | 99-16 Ford Super Duty Models | Direct Fit In Factory Bumper

ITEM#	PART#	FITS	KIT INCLUDES	REFERENCE
XIL-OE9913FSD	9891194	99-16 FORD SUPER DUTY	BRACKET, CONNECTORS	-
XIL-OE9913FSDDURA	9891200	99-16 FORD SUPER DUTY	BRACKETS, (2) DURA-410, CONNECTORS	PAGE 99

BUMPER MOUNT FOR LIGHT BARS
EcoBoost Edition Available | Add Up To 19,008 Lumens | Direct Fit In Factory Bumper

ITEM#	PART#	FITS	KIT INCLUDES	REFERENCE
XIL-OEB09F150	9891057	09-14 FORD F150	BRACKET	-
XIL-OEB09F150PX36	9891156	09-14 FORD F150	BRACKET, XIL-PX3610, WIRING HARNESS	PAGE 46
XIL-OEB09F150LPX15	9891163	09-14 FORD F150	BRACKET, XIL-LPX1510, WIRING HARNESS	PAGE 49
XIL-OEB09F150ECO	9891170	09-14 FORD F150	BRACKET, (2) XIL-PX610, WIRING HARNESS	PAGE 46

# DODGE RAM KITS



ITEM #: XIL-OE0913DROP1MX2 Shown PART #:9890685

#### **FACTORY FOG LIGHT UPGRADE KIT**

Lights, Mounts, Wiring | Available for 02-14 Dodge Ram Models | Direct Fog Light Replacement

ITEM#	PART#	FITS	KIT INCLUDES
XIL-OE0210DR	4002333	02-08 DODGE RAM	BRACKETS, PLUG & PLAY CONNECTORS
XIL-OE0210DRUMX	9133065	02-08 DODGE RAM	BRACKETS, (2) XIL-UMX4010, CONNECTORS
XIL-OE0913DR	9889221	09-14 DODGE RAM	BRACKETS, CONNECTORS
XIL-OE0913DROP	9888552	09-14 DODGE RAM	BRACKETS, (2) XIL-OP110, CONNECTORS
XIL-OE0913DROP1MX2	9890685	09-14 DODGE RAM	BRACKETS, (2) XIL-OP110, (2)XIL-OP120 CONNECTORS



ITEM #: XIL-OEB0913DRPX3610 Shown PART #: 9889245

#### **BUMPER MOUNT FOR LIGHT BARS**

Lights, Mounts, Wiring | Add Up to 19,008 Lumens | Direct Fit In Factory Bumper

ITEM#	PART#	FITS	KIT INCLUDES
XIL-OEB0913DR	9889238	10-14 DODGE RAM	BRACKETS, CONNECTORS
XIL-OEB0913DRPX3610	9889245	10-14 DODGE RAM	BRACKETS, XIL-PX3610, WIRING HARNESS

# **TOYOTA TUNDRA KITS**



ITEM #: XIL-OE0711TTUMX Shown PART #: 9133249

#### **FACTORY FOG LIGHT UPGRADE KIT**

Lights, Mounts, Wiring | 7x Brighter Than Headlight | Direct Fog Light Replacement

ITEM#	PART#	FITS	KIT INCLUDES
XIL-OE0711TT	4002296	07-13 TUNDRA	BRACKET, CONNECTORS
XIL-OE0711TTUMX	9133249	07-13 TUNDRA	BRACKETS, (2) XIL-UMX4010, CONNECTORS

# **GMC SIERRA KITS**



ITEM #: XIL-OE0111GSUMX Shown

#### **FACTORY FOG LIGHT UPGRADE KIT**

Lights, Mounts, Wiring | Bolts Directly To Factory Mounting | 7x Brighter Than Headlight

ITEM#	PART#	FITS	KIT INCLUDES
XIL-OE0711GS	4002388	07-13 GMC SIERRA	BRACKET
XIL-OE0711GSUMX	9133157	07-13 GMC SIERRA	BRACKETS, (2) XIL-UMX4010, T-TAP CONNECTORS

# **CHEVROLET SILVERADO KITS**



ITEM #: XIL-OE0711CSS1100 Shown PART #: 9120829

#### **FACTORY FOG LIGHT UPGRADE KIT**

Lights, Mounts, Wiring | Bolts Directly To Factory Mounting | 7x Brighter Than Headlight

ITEM#	PART#	FITS	KIT INCLUDES	
XIL-OE0711CS	4002340	07-13 SILVERADO	BRACKETS*, T-TAP CONNECTORS	
XIL-OE0711CSS1100	9120829	07-13 SILVERADO	BRACKETS, (4) XIL-S1100, T-TAP CONNECTORS	

# **POLARIS RZR KITS**





Twin LED Headlight System
ITEM #: XIL-OEHL08RZR900OP Shown
PART #: 9898582



A Pillar Mounting Brackets
ITEM #: XIL-OEAD08RZROPR Shown PART #: 9898940



D Pillar Mounting Brackets
ITEM #: XIL-OED08RZROPR Shown

TWIN LED HEADLIGHT SYSTEM FOR POLARIS RZR
08+ Models | Halo Models Available | Plug and Play Wiring Included | Maintains Separate High / Low Beam Operation

		, ,	
ITEM#	PART#	LIGHTS INCLUDED	KIT INCLUDES
XIL-OEHL08RZR900	9898643	No	Left and Right Brackets, 2 Wiring Adapters
XIL-OEHL08RZR900OP	9898582	Yes, Black Housing	4x XIL-OP110 Lights, Left and Right Brackets, 2 Wiring Adapters
XIL-OEHL08RZR900OPC	9898599	Yes, Chrome Housing	4x XIL-OP110C Lights, Left and Right Brackets, 2 Wiring Adapters
XIL-OEHL08RZR900OPW	9898629	Yes, White Housing	4x XIL-OP110W Lights, Left and Right Brackets, 2 Wiring Adapters
XIL-OEHL08RZR900OPH	9898605	Yes, Black with Halo	4x XIL-OPH115 Lights, Left and Right Brackets, 2 Wiring Adapters

TWIN LED HEADLIGHT SYSTEM FOR POLARIS RZR 1000

14+ Models | Halo Models Available | Plug and Play Wiring Included | Maintains Separate High / Low Beam Operation

ITEM#	PART#	LIGHTS INCLUDED	KIT INCLUDES	
XIL-OEHL14RZR	9897509	No	Left and Right Brackets, 2 Wiring Adapters	
XIL-OEHL14RZROPR	9897516	Yes, Black Housing	4x XIL-OPR110 Lights, Left and Right Brackets, 2 Wiring Adapters	
XIL-OEHL14RZROPRC	9898490	Yes, Chrome Housing	4x XIL-OPR110C Lights, Left and Right Brackets, 2 Wiring Adapters	
XIL-OEHL14RZROPRW	9898513	Yes, White Housing	4x XIL-OPR110W Lights, Left and Right Brackets, 2 Wiring Adapters	
XIL-OEHL14RZROPRH	9898520	Yes, Black with Halo	4x XIL-OPRH115 Lights, Left and Right Brackets, 2 Wiring Adapters	

A-PILLAR LIGHT MOUNTS FOR OPTIMUS 2008+ POLARIS RZR 08+ Models | Single and Dual Light Brackets Available | Harness Included with Lights

The state of the s				
ITEM#	PART #	LIGHTS INCLUDED	KIT INCLUDES	
XIL-OEAS08RZR	9898957	No	Left and Right Brackets	
XIL-OEAS08RZROPR	9898964	Yes, Black Housing	2x XIL-OPR110 Lights, Left and Right Single Light Brackets, Harness	
XIL-OEAD08RZR	9898933	No	Left and Right Brackets	
XIL-OEAD08RZROPR	9898940	Yes, Black Housing	4x XIL-OPR110 Lights, Left and Right Dual Light Brackets, 2x Harness	

**D-PILLAR LIGHT MOUNTS FOR OPTIMUS 2008+ POLARIS RZR** 08+ Models | Light is Adjustable Once Mounted | Harness Included with Lights

ITEM#	PART#	LIGHTS INCLUDED	KIT INCLUDES
XIL-OED08RZR	9898971	No	Left and Right Brackets
XIL-OED08RZROPR	9898988	Yes, Black Housing	2x XIL-OPR110 Lights, Left and Right Single Light Brackets, Harness


# YAMAHA YXZ

#### YAMAHA YXZ HEADLIGHT KIT

For Select 2015+ Models | 1 Kit for Low Beam 2nd Kit Optional for High Beam | Plug and Play Installation

ITEM#	PART#	LIGHTS INCLUDED	KIT INCLUDES
XIL-OEHL15YXZCPZ1	9899114	Yes, Black Housing	Brackets, 2 Cannon Lights

# VIEW OUR WEBSITE FOR COMPLETE APPLICATION GUIDE AND THE NEWEST PRODUCTS





# LIGHTING

Vision X continues to offer high quality HID lighting solutions, providing over 2,500 hours of intense illumination and a die-cast 6061 aluminum housing for a reliable and durable lighting solution.

#### ABOUT THE XP SERIES

The Xtreme Performance HID was engineered with input from Baja 1000 winning racers to further enhance the race proven Vision X HID series. Each light includes a weatherproof Deutsch Connector with Plug-and-Play Harness and features a durable lightweight polycarbonate lens.

The HID XP Series is currently trusted by professional rally teams in the United States and Canada.

Internal Ballast & Starter
The ballast takes the standard 12V input power and increases this to the 32,000V that the bulb operates at and the starter is used to ignite the bulb. Vision X uses all internal components for an all-in-one package

#### LONG RANGE PROJECTION

The XP Series is capable of producing long range distances of up to 1,200 meters of usable light from the 8.7" model and 1,000 meters from the 6.7" housing.



# 8.7" HID XP



ITEM #: HID-8550XP Shown PART #: 9119922

#### 1200 METERS OF LIGHT FOR UNMATCHED DISTANCE

Polycarbonate Lens | Die-Cast Aluminum Housing | Internal Ballast & Starter

BEAM PATTERNS Spot, Euro	WARRANTY Extended	<b>DIMENSIONS</b> 8.70" x 9.09" x 5.55"	
RAW LUMENS 5,000 lm (ea)	EFFECTIVE LUMENS 3,500 lm	<b>METRIC</b> 221mm x 231mm x 141mm	
WATTAGE / AMPS 50W / 4.17A	VIBRATION RATING 8.6 Grms	<b>WEIGHT</b> 6.20 lb / 2.81 kg	



HID-8550XP

HID-8552XP





9119922

4000490



Euro

Spot





# 6.7" HID XP



ITEM #: HID-6552XP Shown PART #: 4000483

#### 1000 METERS OF USABLE LIGHT

Polycarbonate Lens | Die-Cast Aluminum Housing | Internal Ballast & Starter

BEAM PATTERNS Spot	WARRANTY Extended	<b>DIMENSIONS</b> 6.7" x 7.00" x 6.30"
RAW LUMENS	EFFECTIVE LUMENS	<b>METRIC</b>
5,000 lm (ea)	3,500 lm (ea)	170mm x 178mm x 160mm
WATTAGE / AMPS	VIBRATION RATING	<b>WEIGHT</b>
50W / 4.17A	8.6 Grms	4.00 lb / 1.81 kg








ITEM#	PART#	BEAM
HID-6552XP	4000483	Spot







# HALOGEN LIGHTING

With various bulbs and headlight products, Vision X caters to your needs when upgrading or replacing your bulbs or headlights.

### AUTOMOTIVE/OFFROAD

# **HALOGEN HEADLIGHT BULBS**

#### DIRECT REPLACEMENT

Increase brightness by up to 50% with the Vision X headlight bulbs. Vision X headlight bulbs provide a super white, more natural light for increased visibility and safety. With three lines to choose from, we offer the perfect mix of cost and performance for any driver.

#### DOT APPROVED

Unlike other Halogen Bulbs on the market, Vision X D Series bulbs are DOT Approved. Enhance your night time driving experience while cooperating with all laws and regulations.

#### LIFETIME WARRANTY

Vision X D Series bulbs feature a Lifetime Limited Warranty. Meaning you never have to buy another set of bulbs.

# VISION X FACTORY

# D SERIES HALOGEN BULBS







**VX-D9005** 4001534



**VX-D9006** 4001558



**VX-D9007** 4001572



**VX-DH1** 4001589



**VX-DH3**4001596



**VX-DH4** 4001602



**VX-DH7** 4001619



**VX-DH10** 4001633



**VX-DH11** 4001657



**VX-DH13** 4001664



ITEM#	PART#	REPLACES	WATTS	FILAMENT
VX-D9004	4001527	9004	65/45	DUAL
VX-D9005	4001534	9005	65	SINGLE
VX-D9006	4001558	9006	55	SINGLE
VX-D9007	4001572	9007	65/55	DUAL
VX-DH1	4001589	H1	55	SINGLE
VX-DH3	4001596	H3	66	SINGLE
VX-DH4	4001602	H4	60/55	DUAL
VX-DH7	4001619	H7	55	SINGLE
VX-DH10	4001633	H10	42	SINGLE
VX-DH11	4001657	H11	55	SINGLE
VX-DH13	4001664	H13	55/60	DUAL

#### **VISION X LIGHTING - 2017 CATALOG**

# 7" SEALED BEAM



ITEM #: VX-7RD Shown PART #: 4004047

**OEM REPLACEMENT HEADLIGHT** 

Hardened Borosilicate Glass Lens | High/Low Beam | DOT Approved

**BULB TYPE** H4 (Not Included) WARRANTY Standard

VISION X BULB AVAILABLE VX-DH4 / VX-LH4 / VX-HH4

**OEM CROSS REFERENCE METRIC** H6017 / H6024

127mm x 178mm x 114mm

**DIMENSIONS** 

**DIMENSIONS** 5.00" x 7.00" x 4.50"

**CERTIFICATION** DOT Approved

WEIGHT 3.40 lb / 1.54 kg

ITEM#	PART#	QUANTITY
VX-7RD	4004047	2

**BEAM MODE** 

High/Low

# 5.75" SEALED BEAM



ITFM #: VX-575 Shown PART #: 4004030

**OEM REPLACEMENT HEADLIGHT** 

Hardened Borosilicate Glass Lens | High/Low Beam | DOT Approved

**BULB TYPE** 9007 (Not Included) **WARRANTY** 

**VISION X BULB AVAILABLE** VX-D9007/VX-L9007/VX-H9007

DOT Approved

5.75" x 5.75" x 3.13" Standard **OEM CROSS REFERENCE** METRIC

**CERTIFICATION** 

146mm x 146mm x 80mm H5001 / H5006 **BEAM MODE** WEIGHT

1.50 lb / 0.68 kg High/Low

ITEM#	PART#	QUANTITY
VX-575	4004030	2

# 5" X 7" SEALED BEAM



ITEM #: VX-57 Shown PART #: 4004023

ITEM #: VX-46 Shown

**OEM REPLACEMENT HEADLIGHT** 

Hardened Borosilicate Glass Lens | High/Low Beam | DOT Approved

**BULB TYPE** H4 (Not Included) WARRANTY Standard

**DIMENSIONS** 5.00" x 7.00" x 4.50"

VISION X BULB AVAILABLE VX-DH4 / VX-LH4 / VX-HH4

**CERTIFICATION** 

**DOT** Approved

**OEM CROSS REFERENCE** H6054

METRIC 127mm x 178mm x 114mm

**BEAM MODE** High/Low

WEIGHT 3.40 lb / 1.54 kg

ITEM#	PART#	QUANTITY
VX-57	4004023	2

# 4" X 6" SEALED BEAM



Hardened Borosilicate Glass Lens | High/Low Beam | DOT Approved

VISION X BULB AVAILABLE VX-D9007/VX-L9007/VX-H9007 **CERTIFICATION** 

DOT Approved

**BULB TYPE** 

9007 (Not Included)

**WARRANTY** Standard **OEM CROSS REFERENCE** 

**DIMENSIONS** 4.00" x 6.00" x 4.25" **METRIC** 

H4656 / H4651

102mm x 152mm x 108mm **WEIGHT** 

**BEAM MODE** 2.00 lb / 0.91 kg High/Low

ITEM# VX-46 4004016 2



# **AUTOMOTIVE ACCESSORIES**

Vision X provides an assortment of automotive accessories including accent lights, mounting solutions, and light covers for that extra detail you've been looking for.

### POLYCARBONATE LIGHT COVERS

### ABOUT POLYCARBONATE LIGHT COVERS

Vision X polycarbonate translucent covers not only protect your light, but they also improving vision in dust, fog, or snow. Another benefit of adding a cover is the capability to change your beam pattern. All covers are made with a UV Protective Coating to prevent fading. Each cover is finished with a glow in the dark printed "X" for a unique look at night when the lights are off.

### COVER COLORS



### **CLEAR**

Unbreakable, dust resistant protection to protect the light from debris and particulate. Without changing light color or performance.



### **BLACKOUT**

Covers the fixture with a solid black protective cover with a high contrast "X" logo. Required in select states for on-road use.



### **AMBER**

Battles fog conditions by reducing the amount of blue light. Mimics classic Halogen color temperature. Great for driving in dust at high speeds.



### **BLUE**

Increases lighting distance when used in snow conditions by reflecting the blue light off the snow. Recommended for vehicles in heavy winter conditions.



### RE

Reduces light temperature and glare back in order to enhance penetration in dust and air particulate. Ideal for vehicles in extreme dust conditions.



### COVED BEAMS



### SPOT

Spot covers maintain original lighting beam pattern while protecting the lens from harmful debris.



### COMBO

Combo covers combine the distance of a spot cover with the peripheral illumination of a euro cover.



### **EURO \*ELLIPTICAL**

Euro covers illuminate peripherals while losing some distance effectiveness.


\*Reduces left peripheral illumination for oncoming traffic.



### FLOOD \*WIDE FLOOD

Wide Flood covers illuminate a wide field of view in exchange for distance effectiveness.

\* Flood covers is the vertical beam equivalent to flood covers.





### OPTIMUS ROUND & OPTIMUS HALO ROUND ITEM# PART# COLOR BEAM PCV-OPR1 CLEAR SPOT 9889528 PCV-OPR1B SPOT 9889559 BLUE PCV-OPR1Y 9889740 **AMBER** SPOT PCV-OPR1R 9889719 RED PCV-OPR1EU CLEAR EURO 9889535 PCV-OPR1BEU 9889566 BLUE **EURO** PCV-OPR1YEU 9889757 **AMBER** EURO PCV-OPR1REU 9889726 RED **EURO** PCV-OPR1FL CLEAR FLOOD PCV-OPR1BFL 9889573 FLOOD **BLUE** PCV-OPR1YFL **AMBER FLOOD** PCV-OPR1RFL 9889733 RED FLOOD WIDE FLOOD PCV-OPR1WF 9890944 CLEAR PCV-OPR1BWF WIDE FLOOD 9890906 **BLUE** PCV-OPR1YWF 9890968 AMBER WIDE FLOOD PCV-OPR1RWF 9890937 RED WIDE FLOOD PCV-OPR1EL CLEAR ELLIPTICAL 9890913 PCV-OPR1BEL 9890890 **BLUE** ELLIPTICAL PCV-OPR1YEL 9890951 AMBER ELLIPTICAL 9890920 PCV-OPR1REL RED ELLIPTICAL **PROTECTIVE**

6.7 LED LIGHT CANNON			
ITEM#	PART#	COLOR	BEAM
PCV-6500	4003248	CLEAR	SPOT
PCV-6500B	4003569	BLUE	SPOT
PCV-6500Y	4002784	AMBER	SPOT
PCV-6500R	4004689	RED	SPOT
PCV-6500CB	9895703	CLEAR	COMBO
PCV-6500BCB	9895710	BLUE	COMBO
PCV-6500YCB	9895734	AMBER	COMBO
PCV-6500RCB	9893198	RED	COMBO
PCV-6500EU	9888453	CLEAR	EURO
PCV-6500BEU	9888460	BLUE	EURO
PCV-6500YEU	9888484	AMBER	EURO
PCV-6500REU	9888477	RED	EURO
PCV-6500FL	9888491	CLEAR	FLOOD
PCV-6500BFL	9888507	BLUE	FLOOD
PCV-6500YFL	9888521	AMBER	FLOOD
PCV-6500RFL	9888514	RED	FLOOD
PCV-6500WF	9888771	CLEAR	WIDE FLOOD
PCV-6500BWF	9889788	BLUE	WIDE FLOOD
PCV-6500YWF	9889801	AMBER	WIDE FLOOD
PCV-6500RWF	9889795	RED	WIDE FLOOD
PCV-6500EL	9890616	CLEAR	ELLIPTICAL
PCV-6500BEL	9890609	BLUE	ELLIPTICAL
PCV-6500YEL	9890630	AMBER	ELLIPTICAL
PCV-6500REL	9890623	RED	ELLIPTICAL
PCV-6500BL * Also compatible with Tra	9160245	BLACK	PROTECTIVE

### LOW PROFILE XTREME

ITEM#	PART#	FITS	COLOR	BEAM
PCV-LP3BL	9155296	XIL-LPX3*	BLACK	<b>PROTECTIVE</b>
PCV-LP6BL	9155388	XIL-LPX6*	BLACK	<b>PROTECTIVE</b>
PCV-LP9BL	9135946	XIL-LPX9*	BLACK	<b>PROTECTIVE</b>
PCV-LP15BL	9155470	XIL-LPX15*	BLACK	<b>PROTECTIVE</b>
PCV-LP18BL	9135762	XIL-LPX18*	BLACK	<b>PROTECTIVE</b>
PCV-LP24BL	9155654	XIL-LPX24*	BLACK	PROTECTIVE
PCV-LP33BL	9155838	XIL-LPX33*	BLACK	<b>PROTECTIVE</b>
PCV-LP36BL	9155920	XIL-LPX36*	BLACK	<b>PROTECTIVE</b>
PCV-LP3Y	9165103	XIL-LPX3*	AMBER	SPOT
PCV-LP6Y	9165196	XIL-LPX6*	AMBER	SPOT
PCV-LP9Y	9136035	XIL-LPX9*	AMBER	SPOT
PCV-LP15Y	9164564	XIL-LPX15*	AMBER	SPOT
PCV-LP18Y	9135854	XIL-LPX18*	AMBER	SPOT
PCV-LP24Y	9164748	XIL-LPX24*	AMBER	SPOT
PCV-LP33Y	9164922	XIL-LPX33*	AMBER	SPOT
PCV-LP36Y	9165011	XIL-LPX36*	AMBER	SPOT
* Compatible with all b	eam patterns			

PCV-CP1	4.5 LED LIGHT CANNON			
PCV-CP1B         9157184         BLUE         SPOT           PCV-CP1Y         9157726         AMBER         SPOT           PCV-CP1R         9162492         RED         SPOT           PCV-CP1CB         9893228         CLEAR         COMBO           PCV-CP1BCB         9893222         BLUE         COMBO           PCV-CP1YCB         9893235         RED         COMBO           PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1EU         9157276         BLUE         EURO           PCV-CP1BEU         91577818         AMBER         EURO           PCV-CP1FEU         9157818         AMBER         EURO           PCV-CP1FL         9157335         CLEAR         FLOOD           PCV-CP1FL         9157368         BLUE         FLOOD           PCV-CP1FL         9157368         BLUE         FLOOD           PCV-CP1FL         9157634         RED         FLOOD           PCV-CP1FL         9157634         RED         FLOOD           PCV-CP1BWF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890684	ITEM#	PART#	COLOR	BEAM
PCV-CP1Y         9157726         AMBER         SPOT           PCV-CP1R         9162492         RED         SPOT           PCV-CP1CB         9893228         CLEAR         COMBO           PCV-CP1BCB         9893242         BLUE         COMBO           PCV-CP1YCB         9893259         AMBER         COMBO           PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1EU         9157276         BLUE         EURO           PCV-CP1BEU         91577818         AMBER         EURO           PCV-CP1FEU         9157542         RED         EURO           PCV-CP1FL         9157358         BLUE         FLOOD           PCV-CP1FL         9157368         BLUE         FLOOD           PCV-CP1FL         9157634         RED         FLOOD           PCV-CP1FL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1FL         9890661 </td <td>PCV-CP1</td> <td>9151151</td> <td>CLEAR</td> <td>SPOT</td>	PCV-CP1	9151151	CLEAR	SPOT
PCV-CP1R         9162492         RED         SPOT           PCV-CP1CB         9893228         CLEAR         COMBO           PCV-CP1BCB         9893242         BLUE         COMBO           PCV-CP1YCB         9893259         AMBER         COMBO           PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1EU         9151243         CLEAR         EURO           PCV-CP1BEU         9157276         BLUE         EURO           PCV-CP1YEU         9157318         AMBER         EURO           PCV-CP1REU         9157362         RED         EURO           PCV-CP1FL         9157368         BLUE         FLOOD           PCV-CP1BFL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157634         RED         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890564         BLUE         WIDE FLOOD           PCV-CP1YWF         9890883         RED         WIDE FLOOD           PCV-CP1RWF         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         <	PCV-CP1B	9157184	BLUE	SPOT
PCV-CP1CB         9893228         CLEAR         COMBO           PCV-CP1BCB         9893242         BLUE         COMBO           PCV-CP1YCB         9893259         AMBER         COMBO           PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1EU         9151243         CLEAR         EURO           PCV-CP1BEU         9157276         BLUE         EURO           PCV-CP1YEU         9157818         AMBER         EURO           PCV-CP1REU         9157342         RED         EURO           PCV-CP1REL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157634         RED         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890586         AMBER         WIDE FLOOD           PCV-CP1YWF         9890883         RED         WIDE FLOOD           PCV-CP1RWF         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890677         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1Y	9157726	AMBER	SPOT
PCV-CP1BCB         9893242         BLUE         COMBO           PCV-CP1YCB         9893259         AMBER         COMBO           PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1EU         9151243         CLEAR         EURO           PCV-CP1BEU         9157276         BLUE         EURO           PCV-CP1YEU         9157818         AMBER         EURO           PCV-CP1REU         9157542         RED         EURO           PCV-CP1FL         9157335         CLEAR         FLOOD           PCV-CP18FL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157634         RED         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890883         RED         WIDE FLOOD           PCV-CP1RWF         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1RE	PCV-CP1R	9162492	RED	SPOT
PCV-CP1YCB         9893259         AMBER         COMBO           PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1EU         9151243         CLEAR         EURO           PCV-CP1BEU         9157276         BLUE         EURO           PCV-CP1YEU         9157818         AMBER         EURO           PCV-CP1REU         9157542         RED         EURO           PCV-CP1FL         9157368         BLUE         FLOOD           PCV-CP18FL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1CB	9893228	CLEAR	COMBO
PCV-CP1RCB         9893235         RED         COMBO           PCV-CP1EU         9151243         CLEAR         EURO           PCV-CP1BEU         9157276         BLUE         EURO           PCV-CP1YEU         9157818         AMBER         EURO           PCV-CP1REU         9157542         RED         EURO           PCV-CP1FL         9157335         CLEAR         FLOOD           PCV-CP1BFL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157900         AMBER         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1RWF         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890677         BLUE         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1BCB	9893242	BLUE	COMBO
PCV-CP1EU         9151243         CLEAR         EURO           PCV-CP1BEU         9157276         BLUE         EURO           PCV-CP1YEU         9157818         AMBER         EURO           PCV-CP1REU         9157542         RED         EURO           PCV-CP1FL         9157335         CLEAR         FLOOD           PCV-CP1BFL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157900         AMBER         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1RWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890681         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890661         CLEAR         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1YCB	9893259	AMBER	COMBO
PCV-CP1BEU         9157276         BLUE         EURO           PCV-CP1YEU         9157818         AMBER         EURO           PCV-CP1REU         9157542         RED         EURO           PCV-CP1FL         9157335         CLEAR         FLOOD           PCV-CP1BFL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157900         AMBER         FLOOD           PCV-CP1KFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890681         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1RCB	9893235	RED	COMBO
PCV-CP1YEU         9157818         AMBER         EURO           PCV-CP1REU         9157542         RED         EURO           PCV-CP1FL         9151335         CLEAR         FLOOD           PCV-CP1BFL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1YEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1EU	9151243	CLEAR	EURO
PCV-CP1REU         9157542         RED         EURO           PCV-CP1FL         9151335         CLEAR         FLOOD           PCV-CP1BFL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157900         AMBER         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1BEU	9157276	BLUE	EURO
PCV-CP1FL         9151335         CLEAR         FLOOD           PCV-CP1BFL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157900         AMBER         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1YEU	9157818	AMBER	EURO
PCV-CP1BFL         9157368         BLUE         FLOOD           PCV-CP1YFL         9157900         AMBER         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1REU	9157542	RED	EURO
PCV-CP1YFL         9157900         AMBER         FLOOD           PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1FL	9151335	CLEAR	FLOOD
PCV-CP1RFL         9157634         RED         FLOOD           PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1BFL	9157368	BLUE	FLOOD
PCV-CP1WF         9890562         CLEAR         WIDE FLOOD           PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1YFL	9157900	AMBER	FLOOD
PCV-CP1BWF         9890654         BLUE         WIDE FLOOD           PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1RFL	9157634	RED	FLOOD
PCV-CP1YWF         9890586         AMBER         WIDE FLOOD           PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1WF	9890562	CLEAR	WIDE FLOOD
PCV-CP1RWF         9890883         RED         WIDE FLOOD           PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1BWF	9890654	BLUE	WIDE FLOOD
PCV-CP1EL         9890661         CLEAR         ELLIPTICAL           PCV-CP1BEL         9890647         BLUE         ELLIPTICAL           PCV-CP1YEL         9890579         AMBER         ELLIPTICAL           PCV-CP1REL         9890678         RED         ELLIPTICAL	PCV-CP1YWF	9890586	AMBER	WIDE FLOOD
PCV-CP1BEL 9890647 BLUE ELLIPTICAL PCV-CP1YEL 9890579 AMBER ELLIPTICAL PCV-CP1REL 9890678 RED ELLIPTICAL	PCV-CP1RWF	9890883	RED	WIDE FLOOD
PCV-CP1YEL 9890579 AMBER ELLIPTICAL PCV-CP1REL 9890678 RED ELLIPTICAL	PCV-CP1EL	9890661	CLEAR	ELLIPTICAL
PCV-CP1REL 9890678 RED ELLIPTICAL	PCV-CP1BEL	9890647	BLUE	ELLIPTICAL
. 0. 0	PCV-CP1YEL	9890579	AMBER	ELLIPTICAL
PCV-CP1BL 9157450 BLACK PROTECTIVE	PCV-CP1REL	9890678	RED	ELLIPTICAL
	PCV-CP1BL	9157450	BLACK	PROTECTIVE

8.7 LED LIGHT	CANNON		
ITEM#	PART#	COLOR	BEAM
PCV-8500	4003255	CLEAR	SPOT
PCV-8500B	4003583	BLUE	SPOT
PCV-8500Y	4002791	AMBER	SPOT
PCV-8500R	4003576	RED	SPOT
PCV-8500CB	9893182	CLEAR	COMBO
PCV-8500BCB	9893204	BLUE	COMBO
PCV-8500YCB	9893211	AMBER	COMBO
PCV-8500RCB	9893198	RED	COMBO
PCV-8500EU	9890128	CLEAR	EURO
PCV-8500BEU	9890098	BLUE	EURO
PCV-8500YEU	9890470	AMBER	EURO
PCV-8500REU	9890432	RED	EURO
PCV-8500FL	9890135	CLEAR	FLOOD
PCV-8500BFL	9890104	BLUE	FLOOD
PCV-8500YFL	9890487	AMBER	FLOOD
PCV-8500RFL	9890449	RED	FLOOD
PCV-8500WF	9890463	CLEAR	WIDE FLOOD
PCV-8500BWF	9890111	BLUE	WIDE FLOOD
PCV-8500YWF	9890142	AMBER	WIDE FLOOD
PCV-8500RWF	9890456	RED	WIDE FLOOD
PCV-8500EL	9890081	CLEAR	ELLIPTICAL
PCV-8500BEL	9890869	BLUE	ELLIPTICAL
PCV-8500YEL	9890159	AMBER	ELLIPTICAL
PCV-8500REL	9890425	RED	ELLIPTICAL
PCV-8500BL Also compatible with HID-8	9890876	BLACK	PROTECTIVE

### XMITTER PRIME XTREME

ITEM#	PART#	FITS	COLOR	BEAM
PCV-P6BL	9156019	XIL-PX6*	BLACK	PROTECTIVE
PCV-P12BL	9156101	XIL-PX12*	BLACK	PROTECTIVE
PCV-P18BL	9156194	XIL-PX18*	BLACK	PROTECTIVE
PCV-P30BL	9156378	XIL-PX30*	BLACK	PROTECTIVE
PCV-P36BL	9156460	XIL-PX36*	BLACK	PROTECTIVE
PCV-P54BL	9156736	XIL-PX54*	BLACK	PROTECTIVE
PCV-P72BL	9157009	XIL-PX72*	BLACK	PROTECTIVE
PCV-P90BL	9888064	XIL-PX90*	BLACK	PROTECTIVE
PCV-P6Y	9166186	XIL-PX6*	AMBER	SPOT
PCV-P12Y	9165288	XIL-PX12*	AMBER	SPOT
PCV-P18Y	9165370	XIL-PX18*	AMBER	SPOT
PCV-P30Y	9165554	XIL-PX30*	AMBER	SPOT
PCV-P36Y	9165646	XIL-PX36*	AMBER	SPOT
PCV-P54Y	9165912	XIL-PX54*	AMBER	SPOT
PCV-P72Y	9166278	XIL-PX72*	AMBER	SPOT
PCV-P90Y	9887883	XIL-PX90*	AMBER	SPOT

### LED ACCENT LIGHTING

Vision X offers a diverse line of accent pod lighting. Easily attract attention to your vehicle with the wide variety of colors. Each durable pod accepts 9-32 volt input and features a strong black housing. Ideal for professional grade applications and weekend enthusiasts alike.







**Reinforced Mounting** Vision X Pro Pod LEDs each feature four equally distant mounting holes, allowing the light to be securely fastened to a large variety of surfaces and letting you put the light where it needs to be.

### UNIVERSAL PRO PODS

### LED POD PERFECT FOR ROCK LIGHTING OR COMPARTMENT LIGHTING

Impact Resistant Lens | Weatherproof Housing for All Conditions | 3' Cord



ITEM #: XIL-PDW Shown PART #: 9136127

COLORS	WARRANTY	<b>DIMENSIONS</b>
Amber, Blue, Green, Red, White	Extended	1.76" Diameter
<b>RAW LUMENS</b>	<b>HOUSING</b>	<b>METRIC</b>
140 lm (ea)	Aluminum	45mm Diameter

ITEM#	PART#	COLOR
XIL-PDA	9136219	Amber
XIL-PDB	9136301	Blue
XIL-PDG	9136394	Green

ITEM#	PART#	COLOR
XIL-PDR	9136486	Red
XIL-PDW	9136127	White

### UNIVERSAL PODS

### **COLORED LED LIGHTING FOR ANY APPLICATION**

Impact Resistant Acrylic Lens | Weatherproof Housing for All Conditions | 10' Cord



ITEM #: HIL-DW Shown PART #: 4004054

COLORS	WARRANTY	<b>DIMENSIONS</b>
Amber, Blue, Green, Red, White	Standard	1.25" Diameter
<b>RAW LUMENS</b>	<b>HOUSING</b>	<b>METRIC</b>
70 lm (ea)	Aluminum	32mm Diameter

ITEM#	PART#	COLOR
HIL-DA	4004078	Amber
HIL-DB	4004139	Blue
HIL-DG	4004146	Green

ITEM#	PART#	COLOR
HIL-DR	4004061	Red
HIL-DW	4004054	White



### **TANTRUM**




ITEM #: HIL-STB Shown PART #: 4005372

### RUGGED LED STROBE OR ROCK LIGHT KIT

Wireless Remote | Multi-Speed Scanning and Flash Control | 4 Pods with 10' Cords 4 Pods with 20' Cords

COLORS Amber, Blue, Green, Multi, Red, White	WARRANTY Standard	<b>DIMENSIONS</b> 1.25" Diameter
<b>RAW LUMENS</b>	HOUSING	<b>METRIC</b>
560 lm (kit)	Aluminum	32mm Diameter





ITEM#	PART#	COLOR
HIL-STM	4005679	Multi
HIL-STR	4005389	Red
HIL-STW	4005419	White

### **STRIP LIGHT**



ITEM #: XIL-ST7.5 Shown PART #: 9167626



ITEM #: XIL-ST12 Shown PART #: 9141701

### TOUCH ACTIVATED OR STANDARD COMMERCIAL DESIGN

Universal Application | Touch Activated Model Available | Compact Design

ACTIVATION MODES Touch On/Off, Hard-wired	WARRANTY Standard	<b>HEIGHT</b> 0.92"/23mm
<b>RAW LUMENS</b> 141-328 lm (ea)	<b>LENGTH</b> 7.4", 11.9"	<b>DEPTH</b> 0.59"/15mm











ITEM#	PART#	MODE	LENGTH	ITEM#	PART#	MODE	LENGTH
XIL-ST7.5	9167626	Touch	7.4"/189 mm	XIL-SL7.5	9167534	Standard	7.4"/189 mm
XIL-ST12	9141701	Touch	11.9"/303 mm	XIL-SL12	9141794	Standard	11.9"/303 mm

# **LED BAGGER LIGHT KIT**



ITEM #: XMC-BKW2 Shown

### LOW CONSUMPTION COMPARTMENT LIGHTING FOR TRUNKS, BAGS, SADDLES

Two Light Kit | 40 Inch Power Cord With Flush Switch Included | Water & Dust Proof













### **XMC HEADLIGHT ACCESSORIES**



ITEM #: P-HLHI4 Shown PART #: 9895475



ITEM #: XMC-H42H9H11 Shown PART #: 9892900



ITEM #: XMC-H42DELPHI Shown PART #: 9892894

### **6 LED SUBAQUA**



ITEM #: XIL-U625W Shown PART #: 9897578

### UNDERWATER LED MODULE FOR OE TRANSOM INTEGRATION

Transom LED Light | New Model Produces Twice As Much Light | Multiple Colors Available

SUBMERSIBLE	WARRANTY	DIMENSIONS
100'/30m	Extended	4.13" x 4.13" x 1.25"
RAW LUMENS 1,366 lm (ea)	COLORS Amber, Blue, Green, Red, White	<b>METRIC</b> 105mm x 105mm x 33mm



9897554 Blue

9897561 Green

9897585 Red

9897578 White



G



# **BORG SMART LIGHTING APP**

### KEY FEATURES

- Take control of your Vision X Prime Drive Lights via bluetooth connection

XIL-U625A

XIL-U625B

XIL-U625G

XIL-U625R

XIL-U625W

- Monitor humidity, temperature, voltage, and other valuable data
- Remotely set strobing and power levels via mobile device
- Currently available for iOS and Android Devices
- Simple On-Off Power Function - Real Time Two-Way Data
- 32 Bit Processing

### ABOUT THE BORG

Vision X is constantly leading the LED Lighting industry by taking the "next-step" in technology and products. The Borg is just that. A simple adaption for any Vision X Light that is equipped with Prime Drive Technology can be transformed from a simple on/off product, to an experience in itself.

Everything from strobing intervals to light intensity can be controlled by your smartphone via bluetooth connection. Additionally, you'll have the power to see valuable data relayed from your LED Light such as humidity, temperature, voltage, RSSI, and elevation. Even further, you can track your g-force level and acceleration with only a few taps.

Unlock the full potential of your Vision X LED by equipping it with Borg!





ITEM #: XIL-PXB36M Shown

### **BLUETOOTH CONNECTION FOR PRIME DRIVE LIGHTS**

### **BORG CONTROL MODULE**



### CONTROL MODULE FOR ANY PRIME DRIVE LIGHT

Connects to Prime Drive Wire | Add Bluetooth Control | App Available in

- Take control of your Vision X Prime Drive Lights via bluetooth connection
- Monitor humidity, temperature, voltage, and other valuable data
   Remotely set strobing and power levels via mobile device
   Currently available for iOS and Android Devices

- Simple On-Off Power Function
- Real Time Two-Way Data
- 32 Bit Processing

ITEM#	PART#	WORKS WITH
XIL-BORGPC	9893273	Prime Drive

### PRIME DIMMER

### PUSH BUTTON OR DIAL DIMMER FOR PRIME LIGHTS

Push Button Dimmer | Designed for Prime Drive Lights | Dial Knob Dimmer



ITEM#	PART#	CONTROL	DIMMER RANGE	CORD LENGTH
XIL-PDIMMER	4009257	Dial Knob	50%-100%	5.50"/139.7mm
XIL-PDIMMERB	4009264	Button Knob	50% & 100%	5.50"/139.7mm

ITEM #: XIL-PDIMMERB Shown PART #: 4009264

### **BATTERY PACKS**

### RECHARGEABLE POWER SOURCE FOR VISION X LIGHTS

Long Life Battery | Compatible with 12V Lights | Compact & Lightweight



ITEM #: XPC-B30 Shown PART #: 9130095

MAX LOAD CAPACITY SOLO RUN TIME WEIGHT XPC-B22 4009080 5A 2.2Ah 3 Hours 1.15 lb XPC-B30 9130095 1.15 lb 5A 3.1Ah 5 Hours XPC-B65 4009097 6.5Ah 6 Hours 1.00 lb XPC-B86 4000339 10A 8.6Ah 13 Hours 2.00 lb

### **UNIVERSAL HARNESSES**

### **UNIVERSAL WIRING HARNESS**

30A 12V Relay Included | Lighted Rocker Switch | Weatherproof Deutsch Connectors



ITEM #: P-HARNESS.2XIL Shown PART #: 4006201

ITEM#	PART#	CONNECTORS	APPLICATION
P-HARNESS.2XIL	4006201	Terminals	2 Light Harness
P-HARNESS.XIL	4006195	Terminals	1 Light Harness
P-HARNESS.HO	9888354	Terminals	High Amp 1 Light Harness
P-DY2M1F	4006263	Deutsch DT Series	Y Adapter
P-UCA	4006218	Cigarette Adapter	Cigarette Power Cord

# **LED MOUNTING SOLUTIONS**

Vision X offers a variety of mounts and adapters to help you put light in more places. Each adapter allows you to add lights to spots that are normally out-of-bounds with these simple mounting solutions. Series includes extra mounting options for light bars.



### LICENSE PLATE MOUNT



LICENSE PLATE MOUNT

Holds Any LED Bar Up To 20" | Easily Installs Behind License Plate | Powder Coated

ITEM#	PART#	INCLUDED
XIL-LICENSEP	4000308	Bracket
XIL-LICENSEPLPX910	9887012	Bracket, XIL-LPX910 LED Bar & Harness

ITEM #: XIL-LICENSEPLPX910 Shown

### **TOW HITCH MOUNT**



### TOW HITCH MOUNT

Machined 6061 Aluminum | 2 Bolt Mount for Hitches | Use With Solo Pods Or Dura Mini

ITEM#	PART#	INCLUDED
XIL-SRECEIVER	4000322	Bracket
XIL-SRECEIVERDURAMX2	9899121	Bracket, 2 x DURA-M460
XIL-SRECEIVERS1101X2	4008595	Bracket, 2 x XIL-S1101

ITEM #: XIL-SRECEIVERS1101X2 Shown PART #: 4008595

View Website for Application Details





# **SOLO FLUSH MOUNT**



4" FLUSH MOUNT FOR SOLSTICE SOLO POD Install Flush Into A 2.75" Hole | Ideal for Ceiling Mounts | Black Anodized Finish

ITEM#	PART#	DIAMETER	APPLICATION
XIL-SFLUSH	4000315	3.68"/93.47 mm	Front Mount
XIL-SFLUSHV2	9887777	3.68"/93.47 mm	Light Mount
XIL-SFLUSH4	4008243	4.00"/101.6 mm	Front Mount

ITEM #: XIL-SFLUSHV2 Shown PART #: 9887777

# **MAGNETIC BASE**



ITEM #: P-UMB Shown
PART #: 4006225

### UNIVERSAL TEMPORARY LIGHT MOUNT

Secure Light Temporarily | Multiple to Support Large Lights | Protective Rubber Boot

ITEM#	PART#	PULL	INCLUDED
P-UMB.95	4009127	95 lb/43.09 kg	Magnet & Sleeve
P-UMB.65	4009110	65 lb/29.48 kg	Magnet & Sleeve
P-UMB	4006225	75 lb/34.02 kg	Magnet & Rubber Boot

# **DURA FLUSH MOUNTS**



ITEM #: DURA-460FLUSH Shown PART #: 9892993

### FLUSH MOUNT FOR DURA SERIES

Install Flush | Ideal for Bumpers | Black Powdercoat Finish

ITEM#	PART#	INCLUDES
DURA-M460FLUSH	9899138	Bracket, DURA Mini Flush Light
DURA-460FLUSH	9892993	Bracket, DURA 4 LED Flush Light
DURA-660FLUSH	9893006	Bracket, DURA 6 LED Flush Light

### **END CAP MOUNTS**



ITEM #: XIL-PECM Shown PART #: 9889191

### END CAP MOUNTS FOR LIGHT BARS

M10x1.5 20mm Thread | Sold In Pairs | Ideal For Roof Mounting

ITEM#	PART#	DESIGNED FOR
XIL-LPECM	9888811	Xmitter Low Profile
XIL-PECM	9889191	Xmitter Prime
XPI-EM	9892917	XPR & XPI
XIL-ECM	9888781	Xmitter

# **OPTIMUS HANDLE**



ITEM #: XIL-OP2HANDLE Shown PART #: 9887098

### **OPTIMUS HANDLE FOR PORTABLE APPLICATIONS**

Sure-Grip form | Convenient Handle for use with Optimus Series | Portable Application

ITEM#	PART#	FITS	COLOR
XIL-OP1HANDLE	9890173	Optimus Single & Optimus Round	Black
XIL-OP2HANDLE	9887098	Optimus Dual	Black

### **XIL-UM HANDLE**



ITEM #: P-UM40HANDLE Shown
PART #: 9144498

### UTILITY MARKET LIGHT ACCESSORY FOR ADDITIONAL APPLICATIONS

Sure-Grip form | Convenient Handle for use with UM Series | Portable Application

ITEM#	PART#	FITS
P-UM40HANDLE	9888361	UM40xx & UMX40xx
P-UMHANDLE	9887111	UM44xx & UMX44xx

### **SOLO MOUNTS**



Various Solo Mounts Shown

### SOLO MOUNTS

Combine with Vision X Battery Packs | Portable On-The-Go Lighting | Extends Applications

-	ITEM#	PART#	USE
	XIL-SHANDLE	4002685	Pistol Grip Handle
	XIL-SHELMET	4002753	Helmets
	XIL-SHANDLEBAR	4002746	Handlebars
	XIL-SCLAMP	9117942	Tube Mounting 0.75"-1.25"
	XIL-SCOMBO	4002739	Helmets + Handlebars

### MINI SOLO MOUNTS



MINI SOLO MOUNTS

Combine with Vision X Battery Packs | Portable On-The-Go Lighting | Extends Applications

ITEM#	PART#	USE
XIL-MXHANDLEBAR	9145570	Handlebars
XIL-MXHELMET	9145488	Helmets
XIL-MXCOMBO	9145396	Helmets + Handlebars
XIL-MXCLAMP	9119205	Tube Mounting 0.75"-1.25"

Various Mini Solo Mounts Shown

# TUBE CLAMP MOUNTS



ITEM #: XIL-C175 Shown PART #: 9897240

# 360° TUBE FRAME MOUNT SYSTEM FOR LIGHTS, LIGHT BARS, AND MORE Includes All Rubber Gasket and Hardware | Anodized Aluminum | Sold in Pairs

ITEM#	PART#	DIAMETER
XIL-C075	9897325	0.75"/19mm
XIL-C100	9897301	1.00"/25mm
XIL-C125	9897288	1.25"/32mm
XIL-C150	9897264	1.50"/38mm
XIL-C175	9897240	1.75"/45mm
XIL-C200	9893372	2.00"/50mm
XIL-C225	9893389	2.25"/57mm
XIL-C250	9893396	2.50"/64mm
XIL-C300	9893402	3.00"/76mm

### **SECURITY BOLTS**

### SECURITY HARDWARE REDUCES THEFT BY REQUIRING SPECIAL TOOL TO REMOVE

Fit Virtually Any Bolt | 304 Stainless Steel Construction | Sold as 2 Bolts with 1 Tool



ITEM#	PART#	SIZE	POPULAR APPLICATIONS
XIL-SB0615	9893440	M6 X 15	L Bracket Mounting Bolt to Side of Light for XPR – XPI Light Bars
XIL-SB0620	9893457	M6 X 20	Bracket to Light bolts Horizon Series
XIL-SB0815	9893419	M8 X 15	Bracket to Light bolts for Optimus Series, DURA Series
XIL-SB0820	9893426	M8 X 20	Bracket to Light on PitMaster Series
XIL-SB0825	9893433	M8 X 25	Any M8 x 25 Bolt

ITEM #: XIL-SB0820 Shown PART #: 9893426

# **SECURITY NUTS**

### SECURITY HARDWARE REDUCES THEFT BY REQUIRING SPECIAL TOOL TO REMOVE

Fit Virtually Any Nut | Carbon Steel Construction | Sold as 2 Nuts with 1 Tool




ITEM#	PART#	SIZE	POPULAR APPLICATIONS
XIL-SN06	9897349	M6	Fits to mounting bolts for UF32 – Solo Pods (SP100 - S1100 - MX Solo) - Dura Mini – Light Bar Mounting Feet (Xmitter, PX, LPX, XPI, XPR Series)
XIL-SN08	9893488	M8	Fits to mounting bolts for All Optimus, Dura Series. Fits to bracket to light bolts for 4.7" Cannon and UMX Series
XIL-SN10	9893471	M10	Fits to mounting bolts for 8.7"- 6.7" - 4.7" Cannon Series - Dual Optimus - TPX Series – UMX Series
XIL-SN12	9893464	M12	Any M12 Mounting Hardware

ITEM #: XIL-SN08 Shown PART #: 9893488








# HEAVY & MEDIUM DUTY SOLUTIONS

# **SOLUTION PROCESS**

Vision X offers complete lighting solutions tailored to the exact needs of your location. This allows you to know prior to purchasing exactly what each light package will do for you. Letting you know in confidence that the lights will meet all the OSHA/MSHA and any other requirements that you may need.



### **2D BLUEPRINT**

Vision X begins a project by requesting the list of machines that will needed to be retrofitted. Then gathering the technical information for those machines.

### **3D MODEL**

A 3D Model is then built to match the customer exact specifications. This model is then carried over into the rendering.

### **SIMULATION RENDER**

Prior to implementing a lighting solution, Vision X creates a simulation rendering of the intended result to help envision if the final product will meet lighting requirements.

### **SOLUTION**

Vision X creates a complete breakdown of what the customer needs to meet their specific requirements for safety.

# FIT OUT GUIDES AVAILABLE



### INDUSTRIAL/HEAVY DUTY

### PITMASTER SERIES

### ABOUT THE PITMASTER

### HARSH ENVIRONMENT 500 & 1000 WATT HPS REPLACEMENT

The PitMaster has earned it's reputation for being the ultimate Heavy Duty LED light from the combination of it's die-cast aluminum housing, unbreakable polycarbonate lens, integrated deutsch connector, reinforced gasketed bezel, and a strengthened trunnion mounting bracket.

Designed to outshine and outlast the competition, the PitMaster features advanced electronic technology like Pulse Width Modulation, Electronic Thermal Management, and a Redundant Circuit Design (60 LED) that allows the fixture to function even if half of the light should fail for unknown reasons. This is part of the effort by Vision X to ensure that the PitMaster exceeds half engine life on mining vehicles.

### FOR USE WITH

**UNDERGROUND JUMBOS & DRILL RIGS** HARSH ENVIRONMENT STRUCTURAL HYDRAULIC AND ROPE SHOVELS **WORKOVER DRILL RIGS** LIGHT PLANT RETROFIT **LIGHT POLES WASH BAYS** 

### REDUNDANT CIRCUIT DESIGN



### FAILSAFE FIXTURE

The PitMaster 30 & 60 each have five and ten internal circuits respectively for redundancy. If one circuit fails, other circuits continue to function allowing equipment to operate until preventive maintenance eliminating unscheduled maintenance and downtime

### NCREASED PERFORMANCE OVER HPS



Each PitMaster delivers 30% more light to effective work area over high-pressure sodium and metal-halide fixtures, while consuming only 30% of the energy.

### **PACKAGES & MOUNTS**

### **ADAPTIVE MOUNTING**

Multiple mounting options are available for the PitMaster 30 and PitMaster 60 such as hanging mounts, flush mounts, and application specific mounts crafted from hardened steel. Also, Vision X can create custom brackets or mounting for your specific needs. Give us a call for further information.



ITEM #: P-PMX30HANGINGMOUNT Shown PART #: 9131085

### COBRA HEAD POLE MOUNT



ITEM #: P-PMX30COBRAHEADMOUNT Shown



ITEM #: P-PMX30HANGINGMOUNT Shown

### **AC PACKAGES**

Packages are also available for purchase and include the fixture, a power supply, necessary mounting, and a junction box to protect the wiring from weather. The AC Power Inverter changes the PitMaster Input Voltage from 11-65V DC to 90-277V AC for a wider range.

ITEM #	PART#	APPLICATION	PACKAGE INCLUDES	VOLTAGE
CXA-PMX3060HPS	9887388	High Bay	MIL-PMX3060, XPC-PS150-24, P-PMX30HANGINGMOUNT, P-JBOXAC	90-277V AC
CXA-PMX3060FPS	9887395	Low Bay	MIL-PMX3060, XPC-PS150-24, P-PMX30FLUSHMOUNT, P-JBOXAC	90-277V AC
CXA-PMX3060CPS	9887401	Street Lighting	MIL-PMX3060, XPC-PS150-24, P-PMX30COBRAHEADMOUNT, P-JBOXAC	90-277V AC
CXA-PMX3060PS	9887418	Structural	MIL-PMX3060, XPC-PS150-24, P-JBOXAC	90-277V AC
CXA-PMX6060HPS	9887425	High Bay	MIL-PMX6060, [2] XPC-PS150-24, P-PMX60HPLATE, [2] P-JBOXAC	90-277V AC
CXA-PMX6060PS	9887432	Structural	MIL-PMX6060, [2] XPC-PS150-24, [2] P-JBOXAC	90-277V AC
CXA-PMX3090WPS	9893280	Wall Pack	MIL-PMX6090, [2] XPC-PS150-24, P-PMX30WALLPACK, [2] P-JBOXAC	90-277V AC

### **PITMASTER 60**



ITEM #: MIL-PMX6060 Shown PART #: 9113357

### 1000-WATT METAL HALIDE REPLACEMENT LIGHT

Increases Operator Safety | 360° Fully Adjustable Mounting System | Prime Drive Equipped

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 15.07" x 11.54" x 6.87"
<b>RAW LUMENS</b> 31,680 lm (ea)	EFFECTIVE LUMENS 22,200 lm (ea)	<b>METRIC</b> 383mm x 293mm x 175mm
<b>WATTAGE / AMPS</b> 300W / 25A @12V	VIBRATION RATING 60 Grms	<b>WEIGHT</b> 26.46 lb / 12.0 kg



















ITEM#	PART#	QTY	BEAM
MIL-PMX6010	9113081	1	10°
MIL-PMX6040	9113265	1	40°

ITEM#	PART #	QTY	BEAM
MIL-PMX6060	9113357	1	60°
MIL-PMX6090	9139906	1	90°

### BEAM PATTERN







**DIMENSIONS** 

11.96" x 7.52" x 4.94"

**METRIC** 

297mm x 191mm x 126mm

**WEIGHT** 

12.34 lb / 5.6 kg

### PITMASTER 30

### 400/500-WATT METAL HALIDE REPLACEMENT LIGHT

Increases Operator Safety | 360° Fully Adjustable Mounting System | Prime Drive Equipped

**WARRANTY** 

Extended

**EFFECTIVE LUMENS** 

11,100 lm (ea)

VIBRATION RATING

60 Grms



ITEM:	#: MIL-PMX3060 Show
PART	#: 9112909







**BEAM PATTERNS** 

10°, 25°, 40°, 60°, 90°, 30°x65°

**RAW LUMENS** 

15,840 lm (ea)

WATTAGE / AMPS

150W / 12.5A @12V















3060 Shown	ITEM#	PART#	QTY	BEAM
	MIL-PMX3010	9112633	1	10°
	MIL-PMX3040	9112817	1	40°

ITEM#	PART #	QTY	BEAM
MIL-PMX3060	9112909	1	60°
MIL-PMX3090	9138107	1	90°

### BEAM PATTERN

# MIL-PMX3060 | 9112909 - 60° Beam 73m/238ft Spread 180m/591ft 240m/787ft 300m/984ff 127m/417ft Distance at 1 lux





### INDUSTRIAL/HEAVY DUTY

### RIPPER SERIES

### ABOUT THE RIPPER

### DESIGNED SPECIFICALLY FOR TRACKED DOZERS, WILL LAST IN ANY APPLICATION.

Built to last. The Ripper Series from Vision X is the hardest working LED fixture you'll find on the market. Rated at 60Grms, the Ripper is capable of standing up to intense amounts of vibration and still perform like it is its first day on the job.

The Ripper is a direct replacement for HID and Halogen fixtures on heavy vibration commercial and industrial machinery. It features Prime Drive ETM (Electronic Thermal Management) that controls the LED temperature to ensure a prolonged LED lifespan. Additionally, the unique vertical and horizontal channeled heat sink increases heat dissipation and further prolongs the lifespan of the light.

### FOR USE WITH

HARSH ENVIRONMENT STRUCTURAL RUBBER TIRE & TRACK DOZERS STANCHION LIGHT POLES WORKOVER DRILL RIGS HYDRAULIC SHOVELS WASH BAYS

### RIPPER SERIES MOUNTING





### **DUAL MOUNTING**

Each Ripper comes packaged with a fully-adjustable Trunnion mount with isolated rubber shock absorbers. Combined with the standard Suspension mount, the Ripper can operate in intense vibration applications.

### **VARIETY OF OPTICS**



### **BEAM PATTERNS**

The Ripper 12 and 20 LED lights are available in a large variety of beam patterns, each excelling in specific applications. Currently, 10°, 25°, 40°, 60°, and 90° beam patterns are available.

### **RIPPER 20 LED**



ITEM #: MIL-RXP2060T Shown PART #: 9114439

### 60 Grms RATED FOR HIGH VIBRATION 100-WATT WORK LIGHT

Dual Mounting System | High Vibration Light | OE Upgrade

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 6.61" x 6.97" x 4.05"
RAW LUMENS 10,560 lm (ea)	<b>EFFECTIVE LUMENS</b> 7,400 lm (ea)	<b>METRIC</b> 168mm x 1177mm x 103m
<b>WATTAGE / AMPS</b> 100W / 8.34A @12V	VIBRATION RATING 60 Grms	<b>WEIGHT</b> 7.50 lb / 3.4 kg




9114347

MIL-RXP2040T


ITEM#	PART #	QTY	BEAM
MIL-RXP2060T	9114439	1	60°
MIL-RXP2090T	9138640	1	90°


### BEAM PATTERN

MIL-RXP2060T | 9114439 - 60° Beam



40°






### **RIPPER 12 LED**

ITEM #: MIL-RXP1260T Shown

### 60 Grms RATED FOR HIGH VIBRATION 60-WATT WORK LIGHT

Dual Mounting System | High Vibration Light | OE Upgrade


<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 4.72" x 6.93" x 4.05"
RAW LUMENS 6,336 lm (ea)	EFFECTIVE LUMENS 4,440 lm (ea)	<b>METRIC</b> 120mm x 6.93mm x 103mm
<b>WATTAGE / AMPS</b> 60W / 5.0A @12V	VIBRATION RATING 60 Grms	<b>WEIGHT</b> 5.51 lb / 2.5 kg





ITEM#	PART#	QTY	BEAM
MIL-RXP1260T	4009998	1	60°
MIL-RXP1290T	9138558	1	90°

### BEAM PATTERN

MIL-RXP1260T | 4009998 - 60° Beam







### INDUSTRIAL/HEAVY DUTY

# **SOLSTICE PRIME SERIES**

### ABOUT THE SOLSTICE PRIME

### DESIGNED FOR HEAVY DUTY FLEETS, OE FITMENT DESIGN

The Solstice Prime Series from Vision X combines traditional form factor and single-bolt mounting with the energy-efficient benefits of LED for the ultimate OE upgrade option for commercial and industrial vehicles that use HID and

The Solstice Prime Series is available in 5 LED or 7 LED models, and each feature Prime Drive ETM (Electronic Thermal Management) that controls the LED temperature to ensure a prolonged LED lifespan. Additionally, the unique vertical channeled heat sink increases heat dissipation and further prolongs the lifespan.

### FOR USE WITH

UNDERGROUND HAUL TRUCKS **OPEN PIT HAUL TRUCKS** MISC WHITE IRON WATER TRUCKS EXCAVATORS GRADERS **LOADERS** MUCKER


### SOLSTICE PRIME MOUNTING



### TRUNNION BRACKET

The Vision X Solstice Prime comes equipped with a fulladjustable 105° Trunnion Bracket that can be easily tuned with a 5mm allen wrench for the optical angle for the most direct and efficient light. Additionally, each bolt on the bracket uses isolated rubber shock absorbers to minimize vibration.

### **ETM & REDUNDANT CIRCUITRY**



### ETM & PRIME DRIVE

Integrated Electronic Thermal Management helps prolong the life of the LEDs by regulating heat levels. Redundant circuit design allows partial light operation until preventative



# **SOLSTICE PRIME 7 LED**



ITEM #: XIL-SP740 Shown PART #: 4009875

### OE UPGRADE FOR HEAVY DUTY COMMERCIAL & INDUSTRIAL APPLICATIONS

105° Adjustable Trunnion Bracket | PMW Integrated Dimming | Vertical Fins Maximize Heat Dissipation

BEAM PATTERNS 20°, 40°	WARRANTY Extended	<b>DIMENSIONS</b> 7.17" x 6.89" x 3.17"
RAW LUMENS	EFFECTIVE LUMENS	<b>METRIC</b>
7,364 lm (ea)	5,155 lm (ea)	182mm x 175mm x 81mm
<b>WATTAGE / AMPS</b>	VIBRATION RATING	<b>WEIGHT</b>
70W / 5.84A @12V	15.6 Grms	4.52 lb / 2.05 kg



ITEM#





PART# QTY BEAM



20°




XIL-SP740





4009875 1

# XIL-SP720 4009868





### **SOLSTICE PRIME 5 LED**

ITEM #: XIL-SP540 Shown

### OE UPGRADE FOR HEAVY DUTY COMMERCIAL & INDUSTRIAL APPLICATIONS

105° Adjustable Trunnion Bracket | PMW Integrated Dimming | Vertical Fins Maximize Heat Dissipation

BEAM PATTERNS 20°, 40°	WARRANTY Extended	<b>DIMENSIONS</b> 5.83" x 4.92" x 3.11"
<b>RAW LUMENS</b> 5,260 lm (ea)	EFFECTIVE LUMENS 3,682 lm (ea)	<b>METRIC</b> 148mm x 125mm x 79mm
<b>WATTAGE / AMPS</b> 50W / 4.17A @12V	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 3.09 lb / 1.4 kg

















ITEM#	PART#	QTY	BEAM
XIL-SP520	4009844	1	20°

ITEM #	PART #	QTY	BEAM
XIL-SP540	4009851	1	40°







### INDUSTRIAL/HEAVY DUTY

### DC CUBE SERIES

### ABOUT THE SHOCKWAVE

SHOCKWAVE SINGLE SERIES

### REPLACES FLUORESCENT FIXTURES IN HARSH ENVIRONMENTS

The Vision X Shockwave excels at being a durable fluorescent upgrade for flat mount applications. The Shockwave was designed to replace fluorescent tubes in heavy commercial and industrial work environments.

Each Shockwave has the option of using a Frosted lens that diffuse the light to help reduce shadow areas. Additionally, multiple mounting options are available, including a Flush, and standard brackets.

Fluorescent tubes often break and need replacement. With the Shockwave Series, you can save on unscheduled maintenance with 50,000 hours of LED life for a brighter, longer-lasting light.

The single panel LED Shockwave produces a 120° beam spread,

rugged industrial design, and universal mounting options.

### **FLUORESCENT REPLACEMENT**



### FOR HARSH CONDITION MACHINERY

We designed the Shockwave Series to replace ineffective fluorescent fixtures on heavy duty machinery. With the Shockwave, you get more output for much less power.



### **SHOCKWAVE DUAL SERIES**

The Dual Shockwave off axis panels produces a 150° beam spread with Integrated Electronic Thermal Management (ETM) and low power consumption.

### DC CUBE SHOCKWAVE



ITEM #: MIL-CSWD1296 (top) & MIL-CSWS2496 PART #: 9898995 & 9899046



# PREMIUM FLUORESCENT REPLACEMENT WITH 210° FULL-SPREAD BEAM PATTERN

High Efficacy CUBE LEDs | Power Supply Packages Available | Clear Bezel For Wider Dispersion

<b>BEAM PATTERNS</b> 180°, 210°	WARRANTY Extended	<b>DIMENSIONS</b> 12"   24"   36"   48"
TESTED LUMENS Up to 43,392 lm	INPUT VOLTAGE 9-32V DC	<b>METRIC</b> 304mm   608mm   912mm   1216mm
<b>WATTAGE / AMPS</b> Up to 384W / 32A @12V DC	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> Varies by Model





MIL-CSWS1248 9899039 Single 12" MIL-CSWS2496 9899046 Single 24" MIL-CSWS36144 9899053 Single 36" MIL-CSWS48192 9899060 Single 48"



PART# LENGTH LEDS RA









OFERATION TEMP			
W LUMENS	WATTS	AMP DRAW	WEIGHT
5,424 LM	48	4A	3.1 LB
10,848 LM	96	8A	6.2 LB
16 272 I M	144	12A	921B

16A

**DIMENSIONS** 

12" | 24" | 36" | 48"

METRIC

304mm | 608mm | 912mm | 1216mm

WEIGHT

3.1 - 22.6 lbs

12.2 LB

192

ITEM #	PART #	LENGTH	LENS	RAW LUMENS	WATTS	AMP DRAW	WEIGHT
MIL-CSWD1296	9898995	Dual 12"	Clear	10,848 lm	96	8A	5.80 LB
MIL-CSWD24192	9899008	Dual 24"	Clear	21,696 lm	192	16A	11.60 LB
MIL-CSWD36288	9899015	Dual 36"	Clear	32,544 LM	288	24A	17.00 LB
MIL-CSWD48384	9899022	Dual 48"	Clear	43,392 LM	384	32A	22.60 LB

MODULAR LED UPGRADE FOR FLUORESCENT LIGHTS Power Supply & Mounts Available | Frosted or Clear Lens | Direct Fluorescent Replacement

WARRANTY

Extended

**EFFECTIVE LUMENS** 

Up to 4,900 lm

VIBRATION RATING

15.6 Grms

21,696 LM

### DC SHOCKWAVE



ITEM #: MIL-SWD2440 (Top) & MIL-SWS1210 Shown PART #: 9126043 & 9150611







**BEAM PATTERNS** 

Ultra Wide 120°, 150°

**RAW LUMENS** 

Up to 7.000 lm

WATTAGE / AMPS

10-80W / 0.83-6.67A @12V









ITEM#	PART#	LENGTH	LENS	RAW LUMENS	WATTS	AMP DRAW	WEIGHT
MIL-SWD1220	9125954	Dual 12"	Clear	1,750 lm	20	1.67A	5.8 lb
MIL-SWD2440	9126043	Dual 24"	Clear	3,500 lm	40	3.34A	11.6 lb
MIL-SWD3660	9126135	Dual 36"	Clear	5,250 lm	60	5.0A	17.0 lb
MIL-SWD4880	9126227	Dual 48"	Clear	7,000 lm	80	6.67A	22.6 lb

ITEM#	PART#	LENGTH	LENS	RAW LUMENS	WATTS	AMP DRAW	WEIGHT
MIL-SWS1210	9125596	Single 12"	Clear	875 lm	10	0.83A	3.1 lb
MIL-SWS2420	9125688	Single 24"	Clear	1,750 lm	20	1.67A	6.2 lb
MIL-SWS3630	9125770	Single 36"	Clear	2,625 lm	30	2.50A	9.2 lb
MIL-SWS4840	9125862	Single 48"	Clear	3,500 lm	40	3.34A	12.2 lb

### INDUSTRIAL/HEAVY DUTY

### PROTEX LIGHT

### ABOUT THE PROTEX

### ATEX APPROVED FOR FLAMMABLE ENVIRONMENTS

The Protex Flameproof Light fixture from Vision X provides you with a powerful and energy efficient alternative to traditional hazardous lights. The Protex offers a compact design making it the perfect replacement for older fixtures that are too bulky or require high maintenance. The Protex is designed to be mounted on the interior or exterior for area illumination.

This fixture features 18 High Output 3-Watt LEDs for a total of forty watts, and has an integrated 85-264V AC input range. The Die-Cast Aluminum Housing combined with a soda-lime glass lens allow the light to operate in any environment.

### FOR USE WITH

FUEL DELIVERY SYSTEMS FRACKING DRILL RIGS OIL PLATFORMS **OIL REFINERIES** TANK FARMS

### ATEX 95 APPROVAL





### DIRECTIVE 94/9/EC

The Vision X Protex fixture has undergone extensive product testing and has earned the ATEX 94 certification to become a flameproof electrical equipment.

### FLAME/EXPLOSION CERTIFICATIONS



### €0575 EX II 2G Ex d II B T5 Gb

Zone 1 – Gases, Mists, Vapors. Occasional, Present Zone 2 – Gases, Mists, Vapors. Only present for a short period EX d – Prevents transmission of the explosion outside II B – For Complete list of explosion group examples see ATEX 94/9/EC



# PROTEX FLAMEPROOF LIGHT



ITEM #: MIL-EXP1860 Shown PART #: 9895956

### 40-WATT FLAMEPROOF ATEX 94/9/EC CERTIFIED LED FIXTURE

Soda-Lime Glass (15.0t) Lens | Integrated 85-264V AC Power Input | Single Stud Mounting System

<b>BEAM PATTERNS</b> 10°, 25°, 60°	WARRANTY Extended	<b>DIMENSIONS</b> 10.04" x 6.89" x 8.15"	
RAW LUMENS 3,500 lm (ea)	EFFECTIVE LUMENS 2,450 lm (ea)	<b>METRIC</b> 255mm x 175mm x 207mm	
<b>WATTAGE / AMPS @110V AC</b> 40W / 0.36A	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 21.16 lb / 9.16 kg	



MIL-EXP1810





9895925 1



PART # QTY BEAM














### BEAM PATTERN


25m/82ft



75m/246ft







### INDUSTRIAL/MEDIUM DUTY

### **UTILITY MARKET XTREME**

### ABOUT THE UMX SERIES

### **OEM/AFTERMARKET REPLACEMENT LIGHTING FOR HALOGEN/HID**

The UMX Series excels in a multitude of applications and is a premium OE upgrade for commercial and industrial applications. Both the UMX Round and the UMX Square are capable of delivering greatly increased output and a smoother beam pattern than comparable halogen fixtures.

The UMX is used everywhere from large-scale mining sites to commercial fog light applications that take advantage of the available 10° beam pattern.

Over 528 raw lumens come out of each LED inside the UMX, making it a leader in the 5-Watt LED field.

### FOR USE WITH

AGRICULTURAL EQUIPMENT AIRPORT EQUIPMENT GARBAGE TRUCKS **FLEET VEHICLES SERVICE BODIES EXCAVATORS SWEEPERS WRECKERS** 

### REDUCED ENERGY CONSUMPTION



### 3-WATT MODEL AVAILABLE

For those looking for less power draw, the less powerful UM Series is available in the same housings as the UMX. The UM Series utilizes 3-watt LEDs to draw only 21 watts.

### FACTORY REPLACEMENT FIXTURE



### **REPLACES OEM HALOGEN & HID**

The UMX Series features a single stud mount allowing it to replace OEM fixtures with ease, including integrated deutsch plug mated to factory wiring on most equipment manufacturers.

# ROUND UTILITY MARKET XTREME



ITEM #: XIL-UMX4060 Shown PART #: 9118307

### XTREME LIGHT OUTPUT OF UPGRADE FOR COMMERCIAL & INDUSTRIAL

Die-Cast Aluminum Housing | Reduced Energy Consumption | 3-Watt Model Available

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 4.49" x 5.47" x 2.99"
RAW LUMENS	EFFECTIVE LUMENS	<b>METRIC</b>
3,696 lm (ea)	2,590 lm (ea)	114mm x 139mm x 76mm
<b>WATTAGE / AMPS</b>	VIBRATION RATING	<b>WEIGHT</b>
70W / 3.8A @12V	15.6 Grms	2.43 lb / 1.1 kg



















TEM#	PART #	QTY	BEAM
XIL-UMX4010	4004719	1	10°
XIL-UMX4040	9118215	1	40°
XIL-UMX4060	9118307	1	60°

### BEAM PATTERN

### XIL-UMX4060 | 9118307 - 60° Beam







# SQUARE UTILITY MARKET XTREME

ITEM #: XIL-UMX4460 Shown

### XTREME LIGHT OUTPUT OF UPGRADE FOR COMMERCIAL & INDUSTRIAL

Die-Cast Aluminum Housing | Reduced Energy Consumption | 3-Watt Model Available

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 4.72" x 6.22" x 3.12"
RAW LUMENS 3,696 lm (ea)	EFFECTIVE LUMENS 2,590 lm (ea)	<b>METRIC</b> 120mm x 158mm x 79mm
<b>WATTAGE / AMPS</b> 70W / 3.8A @12V	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 2.63 lb / 1.2 kg




















ITEM#	PART #	QTY	BEAM
XIL-UMX4410	4004726	1	10°
XIL-UMX4440	9118390	1	40°
XIL-UMX4460	9118482	1	60°

### BEAM PATTERN

XIL-UMX4460 | 9118482 - 60° Beam 36m/119ft Spread 60m/197 ft Distance at 1 lux





### INDUSTRIAL/MEDIUM DUTY

### **DURALUX SERIES**

### ABOUT THE DURALUX SERIES

### **OEM/AFTERMARKET REPLACEMENT LIGHTING FOR HALOGEN/HID**

The Duralux Series gives more output than 100-Watt Halogen lights while drawing much less power and reducing wear on associated components.

Additionally, the Duralux was designed with fleet vehicles in mind, reducing cost, energy consumption, and boosting output at an attractive price.

Available in three different housing sizes and three different beam patterns, the Duralux Series is one of the most adaptive fixtures made by Vision X. The Die-Cast Aluminum housing combines durability with afford-ability for a wide variety of applications.

For those with limited space, the 12-Watt DURA Mini (DURA-M460) produces 2,000 raw lumens while only drawing 1.0 amperage at 12V.

### FOR USE WITH

AGRICULTURAL EQUIPMENT AIRPORT EQUIPMENT GARBAGE TRUCKS **FLEET VEHICLES SERVICE BODIES EXCAVATORS SWEEPERS WRECKERS** 

### TWO LIGHT KITS



### **AVAILABLE DURALUX KITS**

Currently, the Dura 6 LED and Dura 4 LED are available in two light kits with a dual wiring harness with 10°, 40°, or 60° optics at an affordable price.

### FLUSH BRACKETS AVAILABLE



PROFESSIONAL MOUNTING SOLUTION Extend the application range of the DURA with the addition of a

Flush Mounting Bracket. DURA-660FLÜSH | 9893006 DURA-460FLUSH 9892993

### **DURA MINI**



ITEM #: DURA-M460 Shown PART #: 9895499



### ULTIMATE COMPACT FIXTURE FOR UNIVERSAL APPLICATIONS


60° Flood Beam Pattern | IP-69K Waterproof/High Pressure Spray | 1.0 Amp Draw At 12V


BEA	M PATTERNS 60°	WARRANTY Extended	<b>DIMENSIONS</b> 2.75" x 3.62" x 1.94"
	<b>W LUMENS</b> 000 lm (ea)	EFFECTIVE LUMENS 950 lm (ea)	METRIC 70mm x 92mm x 49mm
	TAGE / AMPS 2W / 1.0A	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 0.88 lb / 0.40 kg

S E EX STENDED DIE CAST IP-68 IP-69K CISPR 25 40:- 40:0 50,000 HR

ITEM#	PART#	QTY	BEAM
DURA-M460	9895499	1	60°

### BEAM PATTERN







### **DURALUX 6 LED**



ITEM #: DURA-660 Shown PART #: 9888385


### 30-WATT HIGH PERFORMANCE UNIVERSAL LED LIGHT


Minimal Amperage Draw | 150-Watt Halogen Comparable Fixture | Durable Die-Cast Housing

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 5.38" x 4.19" x 2.72"
RAW LUMENS 3,696 lm (ea)	EFFECTIVE LUMENS 2,590 lm (ea)	<b>METRIC</b> 139mm x 107mm x 69mm
<b>WATTAGE / AMPS</b> 30W / 2.5A @12V	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 2.63 lb / 1.2 kg



ITEM#	PART#	QTY	BEAM
DURA-640	9888378	1	40°
DURA-660	9888385	1	60°







### **DURALUX 4 LED**

ITEM #: DURA-460 Shown

### 20-WATT HIGH PERFORMANCE UNIVERSAL LED LIGHT


Minimal Amperage Draw | 100-Watt Halogen Comparable Fixture | Durable Die-Cast Housing


<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 3.94" x 4.24" x 2.57"
RAW LUMENS 2,112 lm (ea)	EFFECTIVE LUMENS 1,480 lm (ea)	<b>METRIC</b> 100mm x 107mm x 65mm
<b>WATTAGE / AMPS</b> 20W / 1.6A @12V	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 1.50 lb / 0.68 kg



ITEM #	PART#	QTY	BEAM
DURA-440	9141619	1	40°
DURA-460	9141527	1	60°

BEAM PATTERN







# INDUSTRIAL SOLUTIONS

# Marine grade anti corrosive coating

BT Series lights polyester powder coating is designed for the exterior environment offering excellent long term light and weather resistance. Its marine grade anti-corrosive coating has passed multiple chemical and durability tests including:

Salt Spray AS3715 2.5.10 (1000 hours)

Exterior durability AS3715 (12 months continuous exposure)

# Long life - 50,000 hours

Using Pulse Width Modulation (PWM), the LEDs are being turned on and off at a frequency quicker than the human eye can detect. This technology allows the LEDs to be driven hard whilst still achieving a long life span of 50,000 hours.

### CISPR 25 -Class 1 rated

To limit the RF noise that your work light introduces into electronics/radios, enabling better communication.

### **Outstanding light output**

The latest LEDs provide a mass volume of light where you need it most. The color temperature of LED is closer to that of sunlight which reduces eye strain and enables excellent peripheral vision.



ABOUT THE BT HEAVY INDUSTRIAL SERIES

### UPGRADED STAINLESS STEEL TRUNNION BRACKET FOR MINING

The BT Heavy Industrial Series offers outstanding light output in a functional design utilizing a forward rake trunnion bracket, with integrated aiming markings on the sides and base of the bracket. Utilizing the aiming system in conjunction with 3d fit outs to ensure the correct light for any environment. As well as increasing safety, be keeping light out of other operators. High quality construction and components enable the BT Heavy Industrial Series to withstand vibration up to 60Grms. Built-in reverse polarity protection helps prevent accidental damage caused by incorrect installation. Electronic thermal management ensures that if the light is subjected to massive heat overload, that a self protection protocol is engaged to reduce the light output, until such time as the heat overload retreats to normal parameters.

### Moulded DT connectors

Any product is only as good as its components and Deutsch's moulded DT connectors are manufactured from high quality materials selected for their ability to withstand years of environmental exposure.

### Reverse polarity protection

BT Series lights will not sustain accidental damage if the polarity to the light is reversed by incorrect installation.

### IP69K rated

The IP69K rating ensures that the work lights are dust tight with no ingress of particulates and protected against high pressure, high temperature wash downs.

# Electronic thermal management

In an extraordinary situation where the light is subjected to massive heat overload, a self protection protocol is engaged to reduce the light output, until such time as the heat overload retreats to normal parameters.



ABOUT THE BT LIGHT INDUSTRIAL SERIES

### OEM/AFTERMARKET REPLACEMENT LIGHTING FOR HALOGEN/HID

The BT Light Industrial Series offers outstanding light output in a functional design which can be easily adjusted, with either of the supplied trunnion or single bolt bracket options. High quality construction and components enable the BT Light Industrial Series to withstand vibration up 21Grms. Built-in reverse polarity protection helps prevent accidental damage caused by incorrect installation. Electronic thermal management ensures that if the light in subjected to massive heat overload, that a self protection protocol is engaged to reduce the light output, until such time as the heat overload retreats to normal parameters.

### **BHB 20**



ITEM #: BHB072040 Shown PART #: 9898230

### 400 / 500-WATT METAL HALIDE REPLACEMENT FIXTURE

Forward Rake Trunnion Bracket | Aiming System on Bracket | Reverse Polarity Protection

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 9.42" x 6.81" x 4.92"
RAW LUMENS	EFFECTIVE LUMENS	<b>METRIC</b>
16,000 lm (ea)	11,270 lm (ea)	239mm x 173mm x 125mm
<b>WATTAGE / AMPS</b>	VIBRATION RATING	<b>WEIGHT</b>
140W / 11.66A @12V	60 Grms	9.25 lb / 4.20 kg

40°




9898230


BHB072040

ITEM #	PART#	QTY	BEAM
BHB072060	9898247	1	60°
BHB072090	9898254	1	90°

### BEAM PATTERN









### **BHB 12**



ITEM #: BLB071240L Shown PART #: 9898179

### 1000-WATT Halogen Equivalent

Forward Rake Trunnion Bracket | Aiming System on Bracket | Reverse Polarity Protection

WARRANTY Extended	<b>DIMENSIONS</b> 6.95" x 5.20" x 4.02"
<b>EFFECTIVE LUMENS</b> 6,697 lm (ea)	<b>METRIC</b> 177mm x 132mm x 102mm
VIBRATION RATING 60 Grms	<b>WEIGHT</b> 4.96 lb / 2.25 kg
	Extended  EFFECTIVE LUMENS 6,697 lm (ea)  VIBRATION RATING




9898179

BHB071240L


ITEM#	PART#	QTY	BEAM
BHB071260L	9898186	1	60°
BHB071290L	9898193	1	90°

### BEAM PATTERN



### 2D VIEW

40°





### BHB 9



ITEM #: BHB070940 Shown PART #: 9898056

### 700-WATT Halogen Equivalent

Forward Rake Trunnion Bracket | Aiming System on Bracket | Reverse Polarity Protection

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 6.08" x 5.20" x 3.33"
RAW LUMENS 7,200 lm (ea)	EFFECTIVE LUMENS 5,734 lm (ea)	<b>METRIC</b> 154mm x 132mm x 85mm
<b>WATTAGE / AMPS</b> 63W / 5.26A @12V	VIBRATION RATING 60 Grms	<b>WEIGHT</b> 3.96 lb / 1.80 kg

40°





9898056


BHB070940

ITEM#	PART#	QTY	BEAM
BHB070960	9898063	1	60°
BHB070990	9898070	1	90°









### BHB 5

# VISION X X NOISIA

ITEM #: BHB070540 Shown

### 400-WATT Halogen Equivalent

Forward Rake Trunnion Bracket | Aiming System on Bracket | Reverse Polarity Protection

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 4.86" x 4.41" x 3.98"
RAW LUMENS 4,000 lm (ea)	EFFECTIVE LUMENS 3,305 lm (ea)	<b>METRIC</b> 123mm x 112mm x 101mm
<b>WATTAGE / AMPS</b> 35W / 2.92A @12V	VIBRATION RATING 60 Grms	<b>WEIGHT</b> 2.20 lb / 1.00 kg




9897998

BHB070540


ITEM #	PART#	QTY	BEAM
BHB070560	9898001	1	60°
BHB070590	9898018	1	90°

### BEAM PATTERN



### 2D VIEV

40°





### **BLB 20**



ITEM #: BLB072040 Shown PART #: 9898230

### 400 / 500-WATT METAL HALIDE REPLACEMENT FIXTURE


Dual Mounting Brackets Included | Multiple Mounting Points on Light | Reverse Polarity Protection


<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 9.42" x 5.55" x 4.13"
RAW LUMENS 16,000 lm (ea)	EFFECTIVE LUMENS 11,270 lm (ea)	<b>METRIC</b> 239mm x 141mm x 105mm
<b>WATTAGE / AMPS</b> 140W / 11.66A @12V	VIBRATION RATING 21.2 Grms	<b>WEIGHT</b> 9.25 lb / 4.20 kg



ITEM#	PART#	QTY	BEAM
BLB072060	9898247	1	60°

### BEAM PATTERN







### **BLB 12**



ITEM #: BLB071240L Shown

### 1000-WATT Halogen Equivalent

Dual Mounting Brackets Included | Multiple Mounting Points on Light | Reverse Polarity Protection

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30/65°	WARRANTY Extended	<b>DIMENSIONS</b> 6.95" x 5.22" x 3.54"	
<b>RAW LUMENS</b>	EFFECTIVE LUMENS	<b>METRIC</b>	
9,600 lm (ea)	6,697 lm (ea)	177mm x 133mm x 90mm	
<b>WATTAGE / AMPS</b>	VIBRATION RATING	<b>WEIGHT</b>	
84W / 7.0A @12V	21.2 Grms	4.96 lb / 2.25 kg	



















ITEM #	PART#	QTY	BEAM
BLB071225L	9898162	1	25°
BLB071240L	9893877	2	40°

ITEM#	PART #	QTY	BEAM
BLB071260L	9898186	1	60°
BLB071290L	9898193	1	90°

### BEAM PATTERN







### BLB 9



ITEM #: BLB070940 Shown PART #: 9898056

### 700-WATT Halogen Equivalent

Dual Mounting Brackets Included | Multiple Mounting Points on Light | Reverse Polarity Protection

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 6.08" x 5.12" x 3.33"
<b>RAW LUMENS</b>	EFFECTIVE LUMENS	<b>METRIC</b>
7,200 lm (ea)	5,734 lm (ea)	155mm x 130mm x 85mm
<b>WATTAGE / AMPS</b>	VIBRATION RATING	<b>WEIGHT</b>
63W / 5.26A @12V	21.2 Grms	3.96 lb / 1.80 kg




















ITEM#	PART#	QTY	BEAM
BLB070960	9898063	1	60°
BLB070990	9898070	1	90°

### BEAM PATTERN







### BLB 5

ITEM #: BLB070540 Shown

### 400-WATT Halogen Equivalent

Dual Mounting Brackets Included | Multiple Mounting Points on Light | Reverse Polarity Protection

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 4.86" x 3.94" x 3.98"
RAW LUMENS 4,000 lm (ea)	EFFECTIVE LUMENS 3,305 lm (ea)	<b>METRIC</b> 123mm x 100mm x 101mm
<b>WATTAGE / AMPS</b> 35W / 2.92A @12V	VIBRATION RATING 21.2 Grms	<b>WEIGHT</b> 2.20 lb / 1.00 kg















	<b>A</b>	
BO'C	50,000 HR LIFESPAN	

ITEM #	PART#	QTY	BEAM
BLB070525	9897981	1	25°
BLB070540	9897998	2	40°


ITEM#	PART #	QTY	BEAM
BLB070560	9898001	1	60°
BLB070590	9898018	1	90°

### BEAM PATTERN










# **MARITIME** SOLUTIONS

Vision X Marine lighting is specially manufactured to prevent effects of corrosion caused by close proximity to saltwater, along with special electronics for use in or near saltwater.

### **SOLUTION PROCESS**

Vision X creates a solution for your ship or shore lighting needs while using a product specific range designed for the harsh environment of saltwater. This is done through above ground copper circuit boards, stainless steel brackets, and a marine grade coating. Using this environment specific range to create a complete proven solution.



### **2D BLUEPRINT**

Vision X begins a project by A 3D Model is then built gathering information from the customer and the exact areas of the boat that need to be illuminated to what Lux/FC requirements.

### **3D MODEL**

to match the requirements requested and dropped into a realistic aquatic or port environment to ensure the light is where you need it.

### **SIMULATION RENDER**

Prior to implementing a lighting solution, Vision X creates a simulation rendering of the intended result to help envision if the final product will resolve the on the ship. problem.

### **SOLUTION**

Vision X is able to create a solution that proves our lights are able to get you the spread and distance you need on the shore or

# CASE STUDIES / FIT OUT GUIDES AVAILABLE



### **INDUSTRIAL**

# **MARITIME SOLUTIONS**

### ABOUT THE MARITIME SERIES

The Vision X Marine line provides the ideal solution for watercraft of all sizes. From commercial freight ships to fishing vessels, we carry lighting designed specifically for the maritime market. Each electronics board used in the Maritime line is constructed from copper and are above ground to remove corrosion issues typically common in saltwater applications.

Additionally, the marine grade gloss coating reduces wear from constant barrage of saltwater while at sea, ensuring the light performs day in and day out. The heavy duty stainless steel bracket combines maximum strength with a bracket that won't deteriorate over time.

Maritime products operate at a 5000K color temperature, giving the light a

### **ABOVE GROUND MARITIM**





### **SALTWATER PROTECTION**

The unique gloss coating used on Maritime products from Vision X greatly reduces the dramatic impact that saltwater has on traditional lighting fixture housings.

### STAINLESS STEEL BRACKET



### **INCLUDED MOUNTING**

The each fixture in the MAR Series from Vision X comes equipped with a high-strength stainless steel bracket that gives the light extra protection against saltwater corrosion.



### **ANTI-CORROSION**

The Maritime products from Vision X feature an above ground copper electronic board to eliminate any chance of corrosion.

### **MARITIME PITMASTER 60**







**BEAM PATTERNS** 

10°, 25°, 40°, 60°, 90°, 30°x65°

**RAW LUMENS** 

31,680 lm (ea)

WATTAGE / AMPS

300W / 25A @12V





1000-WATT METAL HALIDE REPLACEMENT LIGHT FOR MARINE APPLICATIONS

Stainless Steel Bracket | AC Versions Available | Prime Drive Technology

**WARRANTY** 

Extended

**EFFECTIVE LUMENS** 

22,200 lm (ea)

**VIBRATION RATING** 









ITEM #	PART #	QTY	BEAM
MAR-PMX6040	9892382	1	40°
MAR-PMX6060	9892078	1	60°
MAR-PMX6090	9893013	1	90°


### BEAM PATTERN

ITEM #: MAR-PMX6060 Shown

PART #: 9892078







**DIMENSIONS** 

11.96" x 7.52" x 4.94"

**METRIC** 

297mm x 191mm x 126mm

**WEIGHT** 

16.1 lb / 7.3 kg

**DIMENSIONS** 

15.07" x 11.54" x 6.87"

METRIC

383mm x 293mm x 175mm

WEIGHT

32.4 lb / 14.7 kg

### **MARITIME PITMASTER 30**

### 400/500-WATT METAL HALIDE REPLACEMENT LIGHT FOR MARINE APPLICATIONS

Stainless Steel Bracket | AC Versions Available | Prime Drive Technology

WARRANTY

Extended

**EFFECTIVE LUMENS** 

11,100 lm (ea)

**VIBRATION RATING** 







**BEAM PATTERNS** 

10°, 25°, 40°, 60°, 90°, 30°x65°












ITEM#	PART #	QTY	BEAM
MAR-PMX3040	9892412	1	40°
MAR-PMX3060	9892085	1	60°
MAR-PMX3090	9892573	1	90°

### BEAM PATTERN

ITEM #: MAR-PMX3060 Shown





### **MARITIME RIPPER 20**



ITEM #: MAR-RXP2060 Shown PART #: 9892108

### STAINLESS STEEL BRACKET WITH UPGRADED ELECTRONICS FOR MARINE USE 60 Grms High Vibration Rating | Single Bolt Mounting | Stainless Steel Trunnion Bracket


<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 8.26" x 6.24" x 4.05"
RAW LUMENS 10,560 lm (ea)	<b>EFFECTIVE LUMENS</b> 7,400 lm (ea)	<b>METRIC</b> 210mm x 159mm x 103mm
<b>WATTAGE / AMPS</b> 100W / 8.34A @12V	VIBRATION RATING 60 Grms	<b>WEIGHT</b> 8.4 lb / 38 kg


5 ATT E.D.S	EX EXTENDED WARRANTY	11-65V	MARINE HOUSING	IP-68 WATERPROOF	IP69K SPRAY TESTED	GISPR 25	SO' - 180°C OPERATION TEMP	50,000 H

ITEM#	PART#	QTY	BEAM
MAR-RXP2040	9893020	1	40°
MAR-RXP2060	9892108	1	60°

### BEAM PATTERN

### MAR-RXP2060 | 9892108 - 60° Beam







# **MARITIME RIPPER 12**



ITEM #: MAR-RXP1260 Shown

### STAINLESS STEEL BRACKET WITH UPGRADED ELECTRONICS FOR MARINE USE

60 Grms High Vibration Rating | Single Bolt Mounting | Stainless Steel Trunnion Bracket

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 6.06" x 6.28" x 4.05"
RAW LUMENS 6,336 lm (ea)	EFFECTIVE LUMENS 4,440 lm (ea)	<b>METRIC</b> 154mm x 160mm x 103mm
<b>WATTAGE / AMPS</b> 60W / 5.0A @12V	VIBRATION RATING 60 Grms	<b>WEIGHT</b> 5.51 lb / 2.5 kg





ITEM #	PART #	QTY	BEAM
MAR-RXP1240	9893037	1	40°
MAR-RXP1260	9892092	1	60°

### BEAM PATTERN

### MAR-RXP1260 | 9892092 - 60° Beam







# **MARINE EXPLORER 7**



ITEM #: MIL-EPX760 Shown PART #: 9892115

### STAINLESS STEEL BRACKET WITH UPGRADED ELECTRONICS FOR MARINE USE Stainless Steel Trunnion Bracket | Single Bolt Mounting | CISPR 25 Rated For Marine Use

<b>BEAM PATTERNS</b> 10°, 25°, 40°, 60°, 90°, 30°x65°	WARRANTY Extended	<b>DIMENSIONS</b> 6.43" x 5.50" x 3.12"
RAW LUMENS	EFFECTIVE LUMENS	<b>METRIC</b>
3,696 lm (ea)	2,590 lm (ea)	163mm x 140mm x 79mm
<b>WATTAGE / AMPS</b>	VIBRATION RATING	<b>WEIGHT</b>
35W / 2.9A @12V	15.6 Grms	4.0 lb / 1.81 kg


















ITEM#	PART#	QTY	BEAM
MAR-EPX740	9893044	1	40°
MAR-EPX760	9892115	1	60°

### BEAM PATTERN


### MAR-EPX760 | 9892115 - 60° Beam












# LUCENT **ENGINEERED SOLUTIONS**

AC LED lighting solutions for harsh environments with greatly lower annual power consumption and increased efficiency to provide more light output for a more eco-friendly alternative to HPS and metal halide lighting.

### **SOLUTION PROCESS**

Vision X goes above the expectation to create a solution for the specific needs of its customers. A digital rendering of accurate light output can be requested for specific projects to help demonstrate the effectiveness of our products and help you visualize the solution before purchasing.



### **2D BLUEPRINT**

Vision X begins a project by A 3D Model is then built gathering information and details that will be used to digitally create the project in order to accurately portray the solution.

### **3D MODEL**

to-scale in order for lighting fixtures to be rendered and placed accordingly. This model is then carried over into the rendering.

### **SIMULATION RENDER**

Prior to implementing a lighting solution, Vision X creates a simulation rendering of the intended result to help envision if the final product will resolve the problem.

### **SOLUTION**

Vision X creates a cost effective solution that provides ample light output while saving energy and valuable time.

# **CASE STUDIES AVAILABLE**



### INDUSTRIAL

# **LUCENT ENGINEERED SOLUTIONS**

### ABOUT LUCENT AC TECHNOLOGY

Vision X is able to provide professional solutions due to the effectiveness of CUBE LED Technology. CUBE LEDs differ from standard diodes primarily in size and output pet watt. A CUBE LED has a larger surface area, allowing more light to be emitted per individual watt. Additionally, having a larger surface area gives the LED a much wider beam pattern, allowing more lux to illuminate a full 180° wide-spread area.

For larger applications, the PMX Series of AC lights have multiple beam patterns available, and currently produce 106 lumens per watt making them

### EASE OF INSTALLATION



### **BUILT IN CONNECTIONS**

The Lucent Range of AC products was designed with installation and mounting as key requirements. These products feature multiple mounting options and each features multiple 3/4" NPT threaded connections. So power can be supplied via conduit, or mounted easily as well as additional connections can be passed through the junction box.

### **JUNCTION BOX LIGHT 10W**

ITEM #: LSGSM40180 Shown PART #: LUC-40-1K-10-UD-LV-BL-5K

LSGSM40180 - 180° Beam












# LSGSM40180

### BEAM PATTERN

# 66 ft/20m Spread 16m/52 ft Distance at 1 lux

### HIGH EFFICACY



### **HIGH EFFICACY**

Lucent Engineered Solution AC products from Vision X are ideal for structural applications because of the 117 lumen per watt

### AC INTEGRATED




### **110-277V AC BUILT IN**

Structural solutions from Vision X are bundled with power supplies that allow for a 110V-277V AC Power input range, as well as junction boxes to protect the electrical connections.

### 10-WATT UL C CERTIFIED LED FLOOD LIGHT

Frosted Lens for Smooth Beam | Integrated 110-277V AC Power Input | Conduit or Flush Mounting System







# **JUNCTION BOX LIGHT 60W**



ITEM #: LSG0160180 Shown PART #: LUC-60-6k-60-UD-LV-BL-5K

# LOW MOUNT OR WALL PACK LED LIGHT FIXTURE

High Efficacy CUBE LEDs | Integrated 110-277V AC Power Input | Integrated NPT For Conduit Installation

BEAM PATTERNS 180°	WARRANTY Extended	<b>DIMENSIONS</b> 11.34" x 7.09" x 2.95"
TESTED LUMENS 5,294 lm	INPUT VOLTAGE 110-277V AC	<b>METRIC</b> 288mm x 180mm x 75mm
WATTAGE / AMPS @110V AC 60W / 0.55A	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 8.38 lb / 3.8 kg





















# BEAM PATTERN LSG0160180 - 180° Beam 37m/121ft Distance at 1 lux



### **HIGH BAY LIGHT**

ITEM #: LSG063060 Shown PART #: LUC-30-15K-150-FD-LV-BL-5K

### HARSH ENVIRONMENT 500-WATT AND 1000-WATT REPLACEMENT FIXTURES

Harsh Environment PC Lens | Integrated 90-264V AC Power Input | Multiple Mounting Options

<b>BEAM PATTERNS</b> 25°, 40°, 60°, 90°	WARRANTY Extended	<b>DIMENSIONS</b> 11.38" x 6.88" x 8.46"
<b>TESTED LUMENS</b>	INPUT VOLTAGE	<b>METRIC</b>
15,368 lm	110-277V AC	363mm x 297mm x 174.5mm
<b>WATTAGE / AMPS @110V AC</b>	VIBRATION RATING	<b>WEIGHT</b>
180W / 1.63A	15.6 Grms	29.17 lb / 13.23 kg


















ITEM#	LEDS	TESTED LUMENS	BEAM PATTERN
LSG063060	30	15,638 lm	60°
LSG066060	60	29,185 lm	60°

### **BEAM PATTERN**

# LSG063060 - 60° Beam







### **INDUSTRIAL**

### **CUBE SERIES**

### ABOUT CUBE LED TECHNOLOGY

Vision X is able to provide professional solutions due to the effectiveness of CUBE LED Technology. CUBE LEDs differ from standard diodes primarily in size and output pet watt. A CUBE LED has a larger surface area, allowing more light to be emitted per individual watt. Additionally, having a larger surface area gives the LED a much wider beam pattern, allowing more lux to illuminate a more wide-spread area.

Currently, Vision X CUBE LEDs output an impressive 117 lumens per watt, making them the ideal LED for structural applications.

### **HIGH TEMP GLASS**



### **HEAT RESISTANT**

The optional Soda-Lime Glass lens helps protect the LEDs, as well as internal components, from extreme heat. Vision X recommends Soda-Lime Glass for applications that require intense heat.



### **HIGH EFFICACY**

CUBE LEDs from Vision X are ideal for structural applications because of the 117 lumen per watt ratio. We're able to get more light output for a lower cost than standard LEDs.



### **INTEGRATED POWER SUPPLIES**

Structural solutions from Vision X are bundled with power supplies that allow for a 110V-277V AC Power input range, as well as junction boxes to protect the electrical connections.

# 116

### **CUBE PITMASTER 320 LED**



ITEM #: CPM320PE Shown PART #: 9893051

### 320 CUBE LEDS FOR 37,440 LUMENS & UNMATCHED BEAM SPREAD

High Efficacy CUBE LEDs | AC Power Supplies Included | High-Temp Glass Lens Option

BEAM PATTERNS	WARRANTY	<b>DIMENSIONS</b>
180°	Extended	14.21" x 11.54" x 8.40"
<b>TESTED LUMENS</b>	VIBRATION RATING	<b>METRIC</b>
37,440 lm (ea)	15.6 Grms	361mm x 293mm x 213mm
WATTAGE / AMPS @110V AC	INPUT VOLTAGE	<b>WEIGHT</b>
320W / 2.9A	110-277V AC	29.17 lb / 13.23 kg
























ITEM #	PART#	LEDS	LENS	WEIGHT
CPM320PE	9893051	320	Polycarbonate	26.46 lb / 12 kg
CPM320GPE	9893068	320	High-Temp Glass	26.46 lb / 12 kg

### BEAM PATTERN

CPM320PE | 9893051 - 180° Beam







**DIMENSIONS** 

11.96" x 7.52" x 6.46"

**METRIC** 

297mm x 191mm x 164mm

WEIGHT

15.05 lb / 6.82 kg

# **CUBE PITMASTER 160 LED**

### 160 CUBE LEDS FOR 18,720 LUMENS & UNMATCHED BEAM SPREAD

High Efficacy CUBE LEDs | AC Power Supplies Included | High-Temp Glass Lens Option

WARRANTY

Extended

**VIBRATION RATING** 

15.6 Grms

INPUT VOLTAGE

110-277V AC



53m/174ft Distance at 1 lux

ITEM #: CPM160PE Shown

# **TESTED LUMENS** 18,720 lm (ea) WATTAGE / AMPS @110V AC





**BEAM PATTERNS** 

180°












ITEM #	PART #	LEDS	LENS	WEIGHT
CPM160PE	9893075	160	Polycarbonate	12.34 lb / 5.6 kg
CPM160GPE	9893082	160	High-Temp Glass	12.34 lb / 5.6 kg

### BEAM PATTERN

# CPM160PE | 9893075 - 180° Beam 200m/656ft 300m/984ft 400m/1,312ft 500m/1,640ft





# **CUBE SHOCKWAVE DUAL**

ITEM #: CSWD192PE Shown PART #: 9893105

2D VIEW
11.97"/304mm~47.87"/1216mm
10.24"
0.24'786mm



### PREMIUM FLUORESCENT REPLACEMENT WITH 210° FULL-SPREAD BEAM PATTERN

High Efficacy CUBE LEDs | Power Supply Included | Clear Bezel For Wider Dispersion

BEAM PATTERNS 210°	WARRANTY Extended	<b>DIMENSIONS</b> 12"   24"
<b>TESTED LUMENS</b> 10,848 lm   21,696 lm	INPUT VOLTAGE 110-277V AC	METRIC 304mm   608mm
<b>WATTAGE / AMPS @110V AC</b> 96W / 0.87A   192W / 1.75A	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 5.8 lb   11.6 lb

















ITEM #	PART#	LENGTH	LEDS	RAW LUMENS	WATTS	AMP DRAW	WEIGHT
CSWD96PE	9893099	Dual 12"	96	10,848 lm	96	2A	5.80 lb
CSWD192PF	9893105	Dual 24"	192	21 696 lm	192	4A	11 60 lb

# **CUBE SHOCKWAVE SINGLE**



ITEM #: CSWS192 Shown PART #: 9893143





### PREMIUM FLUORESCENT REPLACEMENT WITH 180° FULL-SPREAD BEAM PATTERN

High Efficacy CUBE LEDs | Power Supply Included | Clear Bezel For Wider Dispersion

BEAM PATTERNS 180°	WARRANTY Extended	<b>DIMENSIONS</b> 12"   24"   36"   48"
<b>TESTED LUMENS</b> 5,424   10,848   16,272   21,696	INPUT VOLTAGE 110-277V AC	<b>METRIC</b> 304mm   608mm   912mm   1216mm
<b>WATTAGE / AMPS @110V AC</b> 92-371W / 0.84-3.37A	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 3.1 lb   6.2 lb   9.2 lb   12.2 lb



















ITEM#	PART#	LENGTH	LEDS	RAW LUMENS	WATTS	AMP DRAW	WEIGHT
CSWS48PE	9893112	Single 12"	48	5,424 lm	48	0.44A	3.1 lb
CSWS96PE	9893129	Single 24"	96	10,848 lm	96	0.87A	6.2 lb
CSWS144PE	9893136	Single 36"	144	16,272 lm	144	1.31A	9.2 lb
CSWS192PE	9893143	Single 48"	192	21,696 lm	192	1.75A	12.2 lb

# **MOUNTING SOLUTIONS**

Multiple mounting solutions have been created for a variety of applications in which the CUBE LED technology excels.

Additionally, Vision X can create custom mounting to suit your applications and help lower the cost of retrofitting a project with LED Lighting.














ITEM#	PART#	FITS	APPLICATION	MATERIAL
P-PMX30FLUSHMOUNT	9131085	PitMaster 30	For Use In Low Bay Applications	Steel
P-PMX30HANGINGMOUNT	9131177	PitMaster 30	For Hanging Mount Applications	Steel
P-PMX30COBRAHEADMOUNT	9130996	PitMaster 30	For Street Lighting Or Light Pole Applications	Steel
P-PMX60HPLATE	9893150	PitMaster 60	For Hangining Mount Applications	Steel





# INDUSTRIAL ACCESSORIES

Vision X offers various accessories including vehicle ID boards, LED reflector utility lights, and the new addition of our video extreme LED light.

# **CONSTRUCTION / ROADWORK AREA LIGHT**

### POLE-MOUNTED PORTABLE LED LIGHT SOLUTION

Includes 5' to 9' Extendable Pole | Flexible Ball Joints | Folds into Included Storage Case

BEAM PATTERN	WARRANTY	LIGHT DIMENSIONS
210°	Extended	11.81" x 4.65" x 1.89"
TESTED LUMENS 21,696 lm	INPUT VOLTAGE 110-277V AC	LIGHT METRIC 300mm x 118mm x 48mm
<b>WATTAGE / AMPS @110V AC</b>	VIBRATION RATING	MAXIMUM POLE EXTENSION
192W / 1.74A	15.6 Grms	9' / 2.4m



















ITEM #: PVR2CSWD96AC Shown







### **UTILITY FLOOD**



ITEM #: XIL-UF32 Shown PART #: 4001824

### LIGHTWEIGHT UTILITY LED LIGHT WITH 120° FLOOD PATTERN

0.5A Amp Draw At 12V | Available In White, Amber, Blue, Green, Red | Universal Applications

BEAM PATTERNS 120°	WARRANTY Extended	DIMENSIONS 3.4" x 1.9" x 0.9" METRIC 86mm x 48mm x 23mm	
RAW LUMENS 500 lm (ea)	EFFECTIVE LUMENS 456 lm (ea)		
WATTAGE / AMPS 6W / 0.5A	VIBRATION RATING 8.6 Grms	<b>WEIGHT</b> 0.41 lb / 0.19 kg	

















ITEM #	PART #	COLOR
XIL-UF32G	9121277	Green
XIL-UF32R	9121369	Red
XIL-UF32P	9135045	Purple

### **AVAILABLE COLORS**



### VIDEO EXTREME LIGHT

ITEM #: VEL-4460CA72SS Shown

### ILLUMINATES AREA WHILE SIMULTANEOUSLY PROVIDING LIVE VIDEO FEED

Kit Available With 7" Monitor (VEL-CAMMON7KIT) | Glare Blocking Shield | Infrared Model Available

BEAM PATTERNS 60°	WARRANTY Extended	<b>DIMENSIONS</b> 4.71" x 6.28" x 3.14"
RAW LUMENS 3,168 lm (ea)	<b>EFFECTIVE LUMENS</b> 2,590 lm (ea)	<b>METRIC</b> 119.6mm x 159.5mm x 79.7mm
WATTAGE / AMPS 30W / 2.5A	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 2.43 lb / 1.1 kg



ITEM#



VEL-4460CA72SS

VEL-CAMMON7KIT





9889856

9892863



White

White









ı	ITEM #	PART#	LED TYPE
	VEL-4460CA72SS.IR850	9889863	Infrared
	VEL-M7 (7" Monitor)	9889870	-

### BEAM PATTERN



### 2D VIEW



### **HEAVY DUTY LED BEACON**



PART #: 9895123

### 180 LED HEAVY DUTY STROBING SAFETY BEACON

360° Visibility | Rugged Die-Cast Aluminum Housing | Shatterproof Polycarbonate Lens

<b>LEDS</b> 180	WARRANTY Extended	<b>DIMENSIONS</b> 5.31" x 5.12" x 5.31"
AREA OF EFFECT Full 360° Visibility	<b>FLASH TYPE</b> Dual	<b>METRIC</b> 135mm x 130mm x 135mm
WATTAGE / AMPS 36W / 3.0A	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 2.96 lb / 1.34 kg



ITEM#	PART#	COLOR
MIL-HDBA	9895123	Amber
MIL-HDBB	9893167	Blue
MIL-HDBG	9895314	Green

ITEM#	PART#	COLOR
MIL-HDBR	9893174	Red
MIL-HDBW	9895130	White

# 36 LED STROBE BEACON (9V)



ITEM #: XIL-UBB36A Shown

### 3 TIMES THE OUTPUT OVER STANDARD LED BEACONS

Powered By 2x 9V Batteries | Magnetic Base | Available In Five Colors

LEDS 36	WARRANTY Extended	<b>DIMENSIONS</b> 5.25" x 3.81" x 2.86"
AREA OF EFFECT Full 360° Visibility	<b>FLASH TYPE</b> Dual	<b>METRIC</b> 133mm x 97mm x 73mm
<b>WATTAGE / AMPS</b> 7.2W / 0.8A @9V	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 0.44 lb / 0.2 kg



XIL-UBB36A

XIL-UBB36B

XIL-UBB36G







9895147

9895161

9895185













OR.	ITE
ber	XIL
ıe	XIL

DLOR		ITI
mber		XII
Blue		XII
Green	ľ	

ΓEM #	PART#	COLOR
IL-UBB36R	9895345	Red
IL-UBB36W	9895369	White

# **36 LED STROBE BEACON**

ITEM #: XIL-UB36A Shown PART #: 9895321

### 3 TIMES THE OUTPUT OVER STANDARD LED BEACONS

Weatherproof Deutsch Connector | Magnetic Base | Available In Five Colors

LEDS 36	WARRANTY Extended	<b>DIMENSIONS</b> 5.25" x 3.81" x 2.86"
AREA OF EFFECT Full 360° Visibility	<b>FLASH TYPE</b> Dual	<b>METRIC</b> 133mm x 97mm x 73mm
<b>WATTAGE / AMPS</b> 7.2W / 0.8A @9V	VIBRATION RATING 15.6 Grms	<b>WEIGHT</b> 0.44 lb / 0.2 kg

ITEM#	PART#	COLOR
XIL-UB36A	9895321	Amber
XIL-UB36B	9895154	Blue
XIL-UB36G	9895178	Green

ITEM #	PART #	COLOR
XIL-UB36R	9895338	Red
XIL-UB36W	9895352	White


# LED VEHICLE ID BOARD


ITEM #: MIL-ID03R & MIL-ID02A Shown PART #: 9892184 & 9892207

### ALLOWS FOR QUICK VEHICLE IDENTIFICATION IN ANY WEATHER CONDITION

195 Crisp LEDs Per Digit | Magnetic Sensor To Change Digits | Engineered For 24/7 Operation

ITEM#	PART#	DIGITS	COLOR	ITEM#	PART #	DIGITS	COLOR
MIL-ID03A	9892719	3	Amber	MIL-ID02A	9892207	2	Amber
MIL-ID03R	9892184	3	Red	MIL-ID02R	9892191	2	Red





# MINI INCIDENT RESPONSE CASE



ITEM #: XLS-M2DURA460BP Shown PART #: 9891026

### PORTABLE EMERGENCY SCENE LIGHTING

Deploys In 30 Seconds Without Tools | Self-Contained Power Cell | 12 Hour Run Time

<b>POLE LENGTH</b> 96" / 2.44m	WARRANTY Standard	<b>DIMENSIONS</b> 17.5" x 25" x 8"
<b>RUN TIME</b>	CHARGE TIME	<b>METRIC</b>
Up To 12 Hours	10 Hours	445mm x 635mm x 203mm

ITEM #	PART #	LIGHTS INCLUDED	RAW LUMENS	RUN TIME
XLS-M2DURA460BP	9891026	2x DURA-460	5,916 lm	12 Hours
XLS-M4S1160BP	9891033	4x XIL-S1160	1,720 lm	12 Hours
XLS-M2UMX4460BP	9891040	2x XIL-UMX4460	6,902 lm	7.5 Hours

# INDUSTRIAL / MARINE DOME LIGHT



BEAM PATTERNS 180°	WARRANTY Extended	<b>DIMENSIONS</b> 6.81" x 1.18"
RAW LUMENS 452 lm (ea)	EFFECTIVE LUMENS 316 lm	<b>METRIC</b> 173mm x 173mm x 30mm
<b>WATTAGE / AMPS</b> 4W / 0.33A @12V DC	VIBRATION RATING 8.6 Grms	<b>WEIGHT</b> 0.60 lb / 270g

















ITEM#	PART#	QTY	COLORS
XIL-DL5RW	9898704	1	WHITE AND RED